

EASISOLV 680

INK REMOVER & SCREEN WASH

EasiSolv 680 Ink Remover & Screen Wash is designed to dissolve all types of ink from the screen printing mesh before removing the emulsion. This product is applied to the screen printing mesh and rinsed with water. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process. This product does not contain APEO, making it compliant with many restricted substance lists; including Nike, Gildan, 3M, VF, Levi Strauss.

Appearance:	Clear, amber
Odor:	Mild Floral
Ph:	Not Determined
Flash Point:	99°C / 210°F
Specific Gravity:	0.997 g/cc @ 20°C/68°F
Weight/gl:	Not Determined
VOCs:	736 grams/liter
Dot Shipping:	Non-hazardous

Quart	
Gallon	680-1 GL
5 Gallon pail	680-5 GL
55 Gallon Drum	680-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents.

PRODUCT FEATURES

- Fast ink dissolution for efficient cleaning
- Simultaneous degreasing simplifies process
- Low odor enhances workplace environment
- Biodegradable detergents with low foam ensure superior ink removal
- Versatile application methods for optimal performance and longevity

APPLICATION/USE

Scrape excess ink from the screen, apply EasiSolv 680 to the ink side and print side of the screen and scrub. Using a good high pressure washer, spray rinse the screen starting at the bottom on the ink side and work up. Give good attention to the image area. Rinse the print side of the screen. Apply an Easiway emulsion remover. If stubborn stains remain, apply EasiSolv 601 as a stain remover.

COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- UV/Solvent
- Conductive
- Industrial