EASISOLV 991 SCREEN WASH



EasiSolv 991 Screen Wash was designed to remove all types of ink from the screen printing mesh. This product can be applied manually by spray bottle or used in a machine (recirculation). EaslSolv 991 also contains surfactants to aid in degreasing mesh.

Appearance:	Clear
Odor:	Mild
Ph:	Neutral
Flash Point:	> 200°F
Specific Gravity:	1.03 @ 20°C / 68°F
Weight/gl:	Not Determined
VOCs:	814 grams/liter
Dot Shipping:	Non-hazardous

Quart	991-1 QT
Gallon	991-1 GL
5 Gallon pail	991-5 GL
55 Gallon Drum	991-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents and acids. Preferable storage is in a location designed for liquids with secondary spill containment.

PRODUCT FEATURES

- For use in machine or by hand
- Water Soluble
- High Flash Point
- Non-hazardous/Non-flammable
- ZDHC MRSL Compliant
- Surfactant boost for improved cleaning

APPLICATION/USE

Scrape excess ink from the screen. Apply EasiSolv 991 to the ink (well) and print side of the screen. Scrub if necessary. Squeegee excess off the screen. Using a good high-pressure washer, spray rinse the screen starting at the bottom of the ink side and work up. Give good attention to the image area of the screen. Rinse the print side of the screen. Apply an Easiway -approved emulsion/stencil remover. If stubborn stains remain, apply EasiSolv 701 as a stain remover and high-pressure rinse.

COMPATIBLE INK TYPES

- Plastisol
- Waterbased
- UV
- Silicone