



EasiSolv C29 lnk & Emulsion Remover is a revolutionary product to address the low VOC restrictions on solvent-based screen cleaning products in California. By combing ink removal and emulsion removal in one step, EasiSolv C29 meets the most strict VOC limits of 100 grams/liter, while reducing labor and the number of products required to reclaim a screen.

Appearance:	Clear
Odor:	Mild
Ph:	Neutral
Flash Point:	93°C / >200°F
Specific Gravity:	1.02 @ 20°C / 68°F
Weight/gl:	0.8 lbs/gallon
VOCs:	96 grams/liter
Dot Shipping:	Non-hazardous

Quart	
Gallon	C29-1 GL
5 Gallon pail	C29-5 GL
55 Gallon Drum	C29-55 GL

STORAGE REQUIREMENTS

Keep the container tightly closed. Store in a dry, cool and well ventilated place away from incompatible materials such as oxidizing agents, bases, and acids.

PRODUCT FEATURES

- Alternative to EasiStrip SUPRA for low VOC restricted areas
- For use in dip tank
- Zero VOCs
- Low Odor
- Non-Flammable

APPLICATION/USE

When you're done at the press, scrape excess ink from the screen, remove the tape and place the screen in your dip tank. Make sure the frame is fully submerged in the solution for 30 seconds to 1 minute or unit1 the ink and emulsion loosen from the mesh. High pressure rinse both sides of the screen. If there is emulsion residue, excess ink, or stains left in the mesh, apply Easi-Solv 701N Screen Wash & Stain Remover.

COMPATIBLE INK TYPES

- Plastisol
- UV
- Waterbase
- Conventional/Solvent