

EASISOLV 630

Ink Remover

EasiSolv 630 Ink Remover & Automated Ink Wash is designed to dissolve all types of ink from the screen printing mesh before removing the emulsion. This product is applied to the screen printing mesh and rinsed with water. 630 Should be used at 100% strength in automated equipment. This provides ease of use for re-filling and topping up equipment.

SPECIAL FEATURES:

- EasiSolv 630 dissolves all inks, allowing mesh to be rinsed clean with water.
- EasiSolv 630 is a low odor product, providing a more pleasant environment for employees.
- EasiSolv 630 is non-flammable which makes it safer for handling, storage and rag disposal than conventional screen washes.
- EasiSolv 630 contains low-foam, biodegradeable detergents which contribute to superior ink removal, while providing complete rinsability with water.

APPLICATION FOR USE AS AS SCREEN WASH:

- Scrape excess ink from screen.
- Apply EasiSolv 630 to the (well) ink and print side of the screen. Scrub if necessary.
- Using a good high pressure washer, spray rinse the screen starting at the bottom of the well side and work up. Give good attention to the image area of the screen. Rinse the print side of the screen.
- Apply an Easiway Systems approved emulsion/stencil remover. The screen will now be ready for reuse. (no need to use an additional degreaser)
- If stubborn stains remain, apply EasiSolv 701 as a stain remover and high pressure rinse.

APPLICATION FOR USE AS AS SCREEN WASH:

• EasiSolv 630 Should be used at 100% strength in automated equipment.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear amber liquid with mild odor

Specific Gravity:

1.011 @ 20° C / 68° F

pH:

N/A

VOC:

279 grams/liter

Flash Point:

> 98.9 ° C / 210 ° F

Ink Types:

Conventional/Solvent

UV

Electronic

Water Base

Plastisol

Product Family:

Textile

Graphic