

EASISOLV 700

PHYSICAL AND

CHEMICAL DATA.

SCREEN WASH & STAIN REMOVER

EasiSolv 700 Screen Wash is designed to perform in enclosed, automatic screen washing systems. This product is used to dissolve all types of ink from the screen printing mesh before removing the emulsion. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process. This product does not remain homogenous, the entire container must be emptied into your machine per use for ultimate performance.

SPECIAL FEATURES:

• EasiSolv 700 dissolves all inks and ink stains quickly, allowing mesh to be rinsed clean with water.	
• EasiSolv 700 degreases as it dissolves inks, eliminating the additional step and expense of degreasing	Appearance & Odor:
chemicals.	
• EasiSolv 700 is a low odor product, providing a more pleasant environment for employees.	Specific Gravity:
• EasiSolv 700 is non-flammable (flash point of 196°F) which makes it safer for handling, storage and rag	
disposal than	
conventional screen washes.	pH:
• EasiSolv 700 contains low-foam, biodegradable detergents which contribute to superior ink and stain	
removal, while providing complete rinsability with water.	VOC:
• EasiSolv 700 may be applied manually or recirculated through the EasiFlo™ System, or in an enclosed,	
automatic screen washing system, providing superior product life and economy.	Flash Point:
• EasiSolv 700 may be applied to a wet screen for use as a stain remover, without causing damage to the	
mesh.	
	Ink Types:
APPLICATION FOR USE AS AS SCREEN WASH:	
• Scrape excess ink from screen.	Product Family:
• Apply EasiSolv 700 to the (well) ink and print side of the screen. Scrub if necessary.	
Squeegee excess off screen.	
• Using a good high pressure washer, spray rinse the screen starting at the bottom of the well side and	
work up. Give good attention to the image area of the screen. Rinse the print side of the screen.	
ullet Apply an Easiway Systems approved emulsion/stencil remover. The screen will now be ready for reuse. $igert$	

(no need to use n additional degreaser)If stubborn stains remain, apply EasiSolv 700 as a stain remover and high pressure rinse.

ENVIRONMENTALLY SAFE SCREEN PRINTING CHEMICALS AND EQUIPMENT



EASISOLV 700

SCREEN WASH & STAIN REMOVER

EasiSolv 700 Screen Wash is designed to perform in enclosed, automatic screen washing systems. This product is used to dissolve all types of ink from the screen printing mesh before removing the emulsion. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process. This product does not remain homogenous, the entire container must be emptied into your machine per use for ultimate performance.

SPECIAL FEATURES:

- EasiSolv 700 dissolves all inks and ink stains quickly, allowing mesh to be rinsed clean with water.
- EasiSolv 700 degreases as it dissolves inks, eliminating the additional step and expense of degreasing chemicals.
- EasiSolv 700 is a low odor product, providing a more pleasant environment for employees.
- EasiSolv 700 is non-flammable which makes it safer for handling, storage and rag disposal than conventional screen washes.
- EasiSolv 700 contains low-foam detergents which contribute to superior ink and stain removal, while providing complete rinsability with water.
- EasiSolv 700 may be applied manually or recirculated through the EasiFlo[™] System, or in an enclosed, automatic screen washing system, providing superior product life and economy.
- EasiSolv 700 may be applied to a wet screen for use as a stain remover, without causing damage to the mesh.

APPLICATION FOR USE AS AS STAIN REMOVER:

- Remove all ink and emulsion from screen.
- Apply stain remover to the (well) ink and print side of the screen, scrub.

• High pressure rinse both sides of screen, followed by a slow or flood rinse to activate degreasing agents.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:
Specific Gravity:
pH:
VOC:
Flash Point:
Ink Types:
Product Family:

ENVIRONMENTALLY SAFE SCREEN PRINTING CHEMICALS AND EQUIPMENT