



EASISOLV 930

SCREEN WASH & STAIN REMOVER

EasiSolv 930 Screen Wash is designed to dissolve plastisol and UV inks from the screen printing mesh before removing the emulsion. This product is applied to the screen printing mesh and rinsed with water. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process.

SPECIAL FEATURES:

- EasiSolv 930 dissolves plastisol and UV inks and stains quickly, allowing mesh to be rinsed clean with water.
- EasiSolv 930 is a low odor product, providing a more pleasant environment for employees.
- EasiSolv 930 is non-flammable which makes it safer for handling, storage and rag disposal than conventional screen washes.
- EasiSolv 930 contains low-foam detergents which contribute to superior ink and stain removal, while providing complete rinsability with water.
- EasiSolv 930 may be applied manually or recirculated through the EasiFlo System, or in an enclosed, automatic screen washing system, providing superior product life and economy.

APPLICATION FOR USE AS AS SCREEN WASH:

- Scrape excess ink from screen.
- Apply EasiSolv 930 to the (well) ink and print side of the screen. Scrub.
- Using a good high pressure washer, spray rinse the screen starting at the bottom of the well side and work up. Give good attention to the image area of the screen. Rinse the print side of the screen.
- Repeated applications may be required for extreme conditions.
- Apply an Easiway Systems approved emulsion/stencil remover. The screen will now be ready for reuse.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear amber liquid with mild odor

Specific Gravity:

1.05 @ 20° C / 68° F

pH:

Neutral

VOC:

820 grams/liter

Flash Point:

93 ° C / > 200 ° F

Ink Types:

Plastisol
UV

Product Family:

Textile
Graphic



EASISOLV 930

SCREEN WASH & STAIN REMOVER

EasiSolv 930 Screen Wash is designed to dissolve plastisol and UV inks from the screen printing mesh before removing the emulsion. This product is applied to the screen printing mesh and rinsed with water. It also contains surfactants that degrease the screen printing mesh when used as a final step in the reclaiming process.

SPECIAL FEATURES:

- EasiSolv 930 dissolves plastisol and UV inks and stains quickly, allowing mesh to be rinsed clean with water.
- EasiSolv 930 is a low odor product, providing a more pleasant environment for employees.
- EasiSolv 930 is non-flammable which makes it safer for handling, storage and rag disposal than conventional screen washes.
- EasiSolv 930 contains low-foam detergents which contribute to superior ink and stain removal, while providing complete rinsability with water.
- EasiSolv 930 may be applied manually or recirculated through the EasiFlo System, or in an enclosed, automatic screen washing system, providing superior product life and economy.

APPLICATION FOR USE AS STAIN REMOVER:

- Remove all ink and emulsion from screen.
- Apply stain remover to the (well) ink and print side of the screen, scrub.
- High pressure rinse both sides of the screen, followed by a flood rinse to activate degreasing agents.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear amber liquid with mild odor

Specific Gravity:

1.05 @ 20° C / 68° F

pH:

Neutral

VOC:

820 grams/liter

Flash Point:

93 ° C / > 200 ° F

Ink Types:

Plastisol
UV

Product Family:

Textile
Graphic