

EASISOLV C29

INK & EMULSION REMOVER

EasiSolv™ C29 Ink & Emulsion Remover is a revolutionary product to address the low VOC restrictions on solvent based screen cleaning products in California. By combining ink removal and emulsion removal in one step, EasiSolv C29 meets the most strict VOC legal limits of 100 grams/liter, while reducing labor and the number of products required to reclaim a screen.

SPECIAL FEATURES:

- EasiSolv C29 has a VOC of less than 100 grams/liter, making it compliant in California where VOC limits are the most strict.
- EasiSolv C29 dissolves and cleans ink, emulsion & blockout in one step which makes the job of screen reclaiming much faster and more efficient.
- EasiSolv C29 has no odor which makes the job of screen reclaiming much more pleasant.
- EasiSolv C29 works on virtually all inks and emulsions, allowing mesh to be rinsed clean with water.

APPLICATION FOR USF IN A DIP TANK:

- Mix EasiSolv C29 at a ratio of up to 1:3 with water in a plastic tank.
- Scrape excess ink from screen and place screen in the dip tank.
- Let soak in tank until the emulsion/film loosens from screen, usually 2-3 minutes.
- High pressure rinse screen, then flood rinse.
- If stubborn stains remain, apply an Easiway Systems approved stain remover, scrub and rinse.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear liquid with mild odor

Specific Gravity:

1.02 @ 20° C / 68° F

pH:

Neutral

VOC:

96 grams/liter

Flash Point:

93 ° C / > 200 ° F

Ink Types:

Plastisol

UV

Conventional/Solvent

Waterbase

Product Family:

Graphic

Textile



EASISOLV C29

INK & EMULSION REMOVER

EasiSolv™ C29 Ink & Emulsion Remover is a revolutionary product to address the low VOC restrictions on solvent based screen cleaning products in California. By combining ink removal and emulsion removal in one step, EasiSolv C29 meets the most strict VOC legal limits of 100 grams/liter, while reducing labor and the number of products required to reclaim a screen.

SPECIAL FEATURES:

- EasiSolv C29 has a VOC of less than 100 grams/liter, making it compliant in California where VOC limits are the most strict.
- EasiSolv C29 dissolves and cleans ink, emulsion & blockout in one step which makes the job of screen reclaiming much faster and more efficient.
- EasiSolv C29 has no odor which makes the job of screen reclaiming much more pleasant.
- EasiSolv C29 works on virtually all inks and emulsions, allowing mesh to be rinsed clean with water.

APPLICATION FOR MANUAL USE:

- Scrape excess ink from screen.
- · Wet screen with water.
- Wet both sides of screen with water.
- Apply EasiSolv C29 by brush, wipe, scrub pad or spray to the print side of screen and scrub.
- Apply to the ink side of screen and scrub.
- High pressure rinse from the well side followed by high pressure rinse from the print side, giving good attention to the image area and frame.
- Flood rinse entire screen with low pressure water.
- If stubborn stains remain, apply an Easiway approved stain remover and high pressure rinse.

PHYSICAL AND CHEMICAL DATA:

Appearance & Odor:

Clear liquid with mild odor

Specific Gravity:

1.02 @ 20° C / 68° F

pH:

Neutral

VOC:

96 grams/liter

Flash Point:

93 ° C / > 200 ° F

Ink Types:

Plastisol

UV

Conventional/Solvent

Waterbase

Product Family:

Textile

Graphic