

DESCRIPTION

- RainStick is North America's first circulating shower system that provides twice the flow rate compared to standard showers in the market, creating an enhanced spa-like experience while saving up to 80% water and 80% of energy in each use.
- Available in two finishes to match any bathroom aesthetic.
- Guaranteed backflow prevention.

OPERATION

- Offers two shower modes using its patented showerhead.
- Its tiltable showerhead can be positioned for optimal warmth and coverage.
- Easy to use central controller to navigate multi-functions.
- Maximum water temperature setting up to (111°F) 44°C.
- RainStick Shower App to track water and energy savings, amongst other pre-set functions.

STANDARDS

• Designed and manufactured to comply with the applicable requirements of CSA, ASME A112.18.1/CSA B-125.1, ASSE 1014, UL 1951 and all applicable specifications referenced therein.

INSTALLATION

- Suitable for new and remodelling bathroom projects.
- ADA Compliant

RAINSTICK COMPONENTS	PRICE
Shower System	Included
Showerhead	Included
Shower Arm	Included
Handheld Shower	Included
Foot Spout	Included
Reservoir	Included
6 month's supply of RainStick	Included
Original Cleaning Product	
9	

FLOW RATE	Circulating default mode, 0.5 GPM from grid (3 GPM experience at the showerhead). Traditional mode, 1.8 GPM.
ELECTRICAL SUPPLY	GFCI-protected electrical circuit with a waterproof connector within the shower enclosure. WiFi 2.4 GHz network (optional)
ELECTRICAL REQUIREMENTS	AC 120V, 60Hz, 2 Amps
CLEANING CYCLE	Automatic cleaning session starts after each use. A deep cleaning session is required after 60 circulating shower uses.
ASSEMBLY	RainStick comes assembled except for the reservoir and the showerhead which need to be connected during installation.
FINISHES	Matte Black Brushed Nickel

