

PRODUCT DATA SHEET NEO9R





2 - PRODUCT DATA SHEET V240430

NEO9R

PRODUCT DESCRIPTION

NEO9R is the absolute powerhouse among trailrunning headlamps. Whether cross-country, uphill or downhill – thanks to its extreme power and endurance, NEO9R is a true legend out on the trails. The superior light image ensures precise short-range and long-range illumination at all times. The particularly powerful, replaceable battery with integrated rear light sits at the back of the head for optimum weight distribution and can be charged easily and quickly via magnetic contact.

- Extremely powerful trailrunning headlamp with outstanding light image; multiple adaptable light sources provide
 perfect separated short-range and long-range illumination at all times
- Ergonomic design with removable overhead strap for perfect fit and wearing comfort during outdoor activities; included chest belt as additional attachment option
- Tilting lamphead for individual adjustment of the light cone
- 360° visibility thanks to red flashing rear light and reflective headband
- Extremely powerful, replaceable battery; rechargeable via Magnetic Charge System with status LED

TECHNICAL DATA	
Head diameter [mm]	57
Weight incl. batteries [g]	199
Weight without batteries [g]	106
Focus function	No
Head material	PC
Tube material	PC
Optic	Plastic lense (PMMA)
Headband material	Elastic fabric
Headband type	Side overhead headband
Head movement type	Stepless movement
Head movement angle [°]	45
Headband specifications	Elastic, reflecting

POWER SUPPLY	
Power source type	Rechargeable battery
Battery quantity	1
Battery type	Li-ion
Battery replaceable	Yes
Total battery voltage [V]	3.7
Total battery capacity [mAh]	5000
Total battery energy ² [Wh]	18.5
Rechargeable	Yes
Charging time ⁵ [min]	330
Energy status indicator	Battery Indicator,
	Charge Indicator,
	Low Battery Warning

FURTHER SPECIFICATIONS	
IP class	IP54
Drop test (drop height) [m]	2
Working temperature range [°C]	-20 to +40

LIGHT FUNCTIONS

Boost, Power, Mid Power, Low Power

LIGHT SOURCE	
Amount LEDs	3
LED type	Xtreme LED
Color	White
Color temperature [K]	5200 to 6200
Color rendering index (CRI)	70

LIGHT VALUES	5			
ANSI – Energy Saving	Boost	Power	Mid Power	Low Power
Light output ¹ [lm]	1200	600	200	20
Beam distance ¹ [m]	200	120	60	5
Run time ¹ [h]		5	12	120

SWITCH

Front Switch

FEATURES

Rear light , Transportation lock , Backup Mode

TECHNOLOGIES

Temperature Control System, Magnetic Charge System, Fusion Beam



3 - PRODUCT DATA SHEET v240430

NEO9R

PACKAGING AND LOGISTICS





PACKAGING INFORMATION		
Type of packaging	Вох	
Scope of delivery	1 set of rechargeable batteries, Comfort Pad, Magnetic charging cable (USB-C), chest belt	
Item No.	502324	
Customs tariff number	85131000000	
Color	black / gray	
MSRP price (€)	115.00	

SINGLE PACKAGE	
Dimensions W x H x D [cm]	14.5 x 8.5 x 8.5
Gross weight [g]	380
GTIN-13	4058205024167

EXPORT CARTON	
Unit	24
Dimensions W x D x H [cm]	38 x 29.5 x 34.5
Gross weight [kg]	9.82
GTIN-13	4058205024143

PACKAGING INFORMATION	
Type of packaging	Box
Scope of delivery	1 set of rechargeable batteries, Comfort Pad, Magnetic charging cable (USB-C), chest belt
Item No.	502715
Customs tariff number	85131000000
Color	black / blue
MSRP price (€)	115.00

SINGLE PACKAGE	
Dimensions W x H x D [cm]	14.5 x 8.5 x 8.5
Gross weight [g]	380
GTIN-13	4058205030021

INNER CARTON

EXPORT CARTON	
Unit	24
Dimensions W x D x H [cm]	38 x 29.5 x 34.5
Gross weight [kg]	9.82
GTIN-13	4058205030014



5 - PRODUCT DATA SHEET V240430

NEO9R

PRODUCT SERIES

Lighter, smaller, faster: the new Ledlenser NEO series provides you with the perfect light to bring out the best in you during fast-paced activities in the dark. Your NEO headlamp is your partner on the way to your next goal – no matter whether you run on or off the trails, skate, parkour or practice other fast-paced sports where customized lighting is essential. The headlamps of the NEO series are optimized in every detail for their intended use – from the perfect light image and clever light functions to weight, size and sophisticated details. Let the run begin!



