

***Hisense***

**Minisplit inverter solo frío**

- AT121CB
- AT122CB
- AT242CB

## Características generales

- Display LED Panel Frontal
- Control Remoto
- Panel removible y lavable
- Filtro de alta densidad
- Regulador de intensidad
- Temporizador de encendido/apagado
- 3 Velocidades de ventilación
- Función “Sleep”
- Auto reinicio al regresar la corriente
- Deshumidificación

# AT121CB

## Inverter Sólo Frío

# Inverter

## 1 Ton / 110Vts



**Peso producto 9 kg**

**INVERTER  
EXPERT**  
hasta **SEER 17**



**FILTRO**



**Deflexión  
de 4 Vías**



**I FEEL**

## Ficha técnica

- Capacidad de enfriamiento 11K (BTU/h)
- Alimentación en enfriamiento 1,000 (W)
- Corriente en enfriamiento 8.8 (A)
- Remoción de humedad 1.2 (L/h)
- Circulación de aire (Max.) 550 (m<sup>3</sup>/h)
- SEER 17 (Posible Incremento)
- Voltaje, Frecuencia 115 V~,60 Hz
- Tipo de refrigerante R410A
- Cobre/Aluminio

**Hisense**



RESURTIDORA  
DE AIRE Y CALEFACCIÓN

# AT122CB

## Inverter Sólo Frío

# Inverter

## 1 Ton / 220Vts



**Peso producto 9 kg**

**INVERTER  
EXPERT**  
hasta **SEER 16**



**FILTRO**



**Deflexión  
de 4 Vías**



**I FEEL**

## Ficha técnica

- Capacidad de enfriamiento 11K (BTU/h)
- Alimentación en enfriamiento 1,040 (W)
- Corriente en enfriamiento 4.6 (A)
- Remoción de humedad 1.2 (L/h)
- Circulación de aire (Max.) 550 (m<sup>3</sup>/h)
- SEER 16
- Voltaje, Frecuencia 230 V~,60 Hz
- Tipo de refrigerante R410A
- Cobre/Aluminio

**Hisense**



RESURTIDORA  
DE AIRE Y CALEFACCIÓN

# AT242CB

## Inverter Sólo Frío

# Inverter

## 2 Ton /220Vts



**Peso producto 14.5 kg**

**INVERTER  
EXPERT**  
hasta **SEER 16**



**FILTRO**



**Deflexión  
de 4 Vías**



**I FEEL**

## Ficha técnica

- Capacidad de enfriamiento 22K (BTU/h)
- Alimentación en enfriamiento 2,300 (W)
- Corriente en enfriamiento 10.2 (A)
- Remoción de humedad 2 (L/h)
- Circulación de aire (Max.) 1,100 (m<sup>3</sup>/h)
- SEER 16
- Voltaje, Frecuencia 230 V~,60 Hz
- Tipo de refrigerante R410A
- Cobre/Aluminio

**Hisense**



RESURTIDORA  
DE AIRE Y CALEFACCIÓN

Factory Model		AS-12TR1SYRCB00A(PX5)	AS-12TR5SYRCB00A(PX5)	AS-22TR5SXTCB00A(PX5)
Mexico Hisense Model		AT121CB	AT122CB	AT242CB
Type		Cooling Only	Cooling Only	Cooling Only
Cooling Capacity	Btu/h	11000	11000	22000
Heating Capacity	W	NA	NA	NA
Power Input-Cooling	W	1000	1040	2300
Power Input-Heating	W	NA	NA	NA
Moisture Removal	L/H.r	1.2	1.2	2
Air Circulation	m3/h	550	550	1100
Design SEER for Cooling	Btu/h/W	17.0	16.0	16.0
Test result by NYCE:SEER for Cooling(Show at carton box)	Btu/h/W	17.89	17.01	17.65
HSPF for Heating	Btu/h/W	NA	NA	NA
Refrigerant		R410a	R410a	R410a
	g	510	510	800
indoor Sound Pressure(L/M/H)	dB (A)	40	40	48
outdoor Sound pressure	dB (A)	51	51	56
Rated Current	Cooling (A)	8.8	4.6	10.2
	Heating (A)	NA	NA	NA
Rated Current (Max)	Cooling (A)	13.5	7.5	13.6
	Heating (A)	NA	NA	NA
Power Supply				
Voltage, Frequency, Phase		115V~,60Hz,1P	230V~,60Hz,1P	230V~,60Hz,1P
System				
Compressor type		Rotary	Rotary	Rotary
Compressor Model No.		GS104MJA	GS104MJA	ATM150D43TFZ
Compressor MFG		LG	LG	GMCC
Expansion Device		Capillary	Capillary	Capillary
Evaporator		Copper tube and Aluminum Fin	Copper tube and Aluminum Fin	Copper tube and Aluminum Fin
Condenser		Micro-channel	Micro-channel	Micro-channel
Max Suction pressure	MPa	1.6	1.6	1.6
Max Discharge pressure	MPa	4.15	4.15	4.15
Connecting Pipe Diameter				
Liquid Pipe	inch	1/4	1/4	3/8
Gas Pipe	inch	3/8	3/8	5/8
Maximum connection pipe length	m	15	15	15
Maximum height difference	m	5	5	5
Features				
LCD Wireless Remote Control (Backlit display,Fluorescent button)		L1-12	L1-12	L1-12
Removable and washable Panel		Yes	Yes	Yes
Washable HD Filter		Yes	Yes	Yes
4 in 1 Filter(Vitamin C,Catechin,Silver Ion,HEPA)		Yes	Yes	Yes
Adjustable Horizontal Louver (Automatic)		Auto	Auto	Auto
Adjustable Vertical Louver (Manual / Automatic)		Auto	Auto	Auto
Comfort air flow (Cooling)		Yes	Yes	Yes
Comfort air flow (Heating)		NA	NA	NA
Cold Air Protection		NA	NA	NA
Fan Speed Control (Cooling / Heating)		Yes,3 fan speeds + Super +Quiet	Yes,3 fan speeds + Super +Quiet	Yes,3 fan speeds + Super +Quiet
Power On/ Off Switch in IDU		Yes	Yes	Yes
Auto Clean		Yes	Yes	Yes
Sleep Function		4 sleep modes	4 sleep modes	4 sleep modes
Smart Function		Yes	Yes	Yes
Super		Yes	Yes	Yes
Quiet mode		Yes	Yes	Yes
2 Ways Draining Connection (Left or Right)		Yes	Yes	Yes
Dimmer		Yes	Yes	Yes
Realtimer		Yes	Yes	Yes
Auto Restart		Yes	Yes	Yes
Auto Defrost		NA	NA	NA
Econermy		Yes	Yes	Yes
Self Diagnosis (Error Code)		Yes	Yes	Yes
Dimension				
Net Dimensions WxHxD (mm)	Indoor Unit	790×255×200	790×255×200	998×325×225
	Outdoor Unit	660×482×240	660×482×240	810×585×280
Packing Dimensions WxHxD (mm)	Indoor Unit	850×325×255	850×325×255	1060×390×315
	Outdoor Unit	785×530×340	785×530×340	940×630×385
Loading Capacity (20'/40'/40'HC ) with pipe		146/298/339	146/298/339	85/170/192
Weight				
Net Weight (Kg)	Indoor Unit	7	7	12
	Outdoor Unit	24	23	36
Gross Weight (Kg)(With pipe)	Indoor Unit	9	9	14
	Outdoor Unit	26	25	40