

[54] **AUTO EXHAUST SCRUBBER WITH CATALYST**
 [76] Inventor: **Howard Alliger**, 10 Ponderosa Dr., Melville, L. I., N.Y. 11746
 [22] Filed: **Feb. 16, 1971**
 [21] Appl. No.: **115,397**

2,677,601 5/1954 Ruth 55/DIG. 30
 2,849,294 8/1958 Ruth 23/284
 3,032,968 5/1962 Novak et al. 55/256 UX
 3,216,181 11/1965 Carpenter et al. 55/256
 3,391,521 7/1968 Pal 55/256 X
 3,566,583 3/1971 Ashmore 55/255

Primary Examiner—Barry S. Richman
 Attorney—Kenneth S. Goldfarb

[52] U.S. Cl. 23/288 F, 23/284, 55/229, 55/255, 55/256, 55/DIG. 30, 60/310, 261/92, 261/122
 [51] Int. Cl. F01n 3/14, B01j 9/04
 [58] Field of Search 55/255, 256, 229, 55/DIG. 30; 23/288 F, 284; 261/92, 122; 60/310; 423/213, 214

[56] **References Cited**
UNITED STATES PATENTS
 1,637,516 8/1927 Brilliant 55/DIG. 30
 2,138,153 11/1938 Grisdale 55/255 X
 2,602,730 7/1952 Finn 23/288 F UX

[57] **ABSTRACT**

A gas scrubber for an internal combustion engine comprising a tank having an intake gas tube to which a composite cylindrical filter formed of a plurality of screens is secured. A clean gas outlet is provided at the top of the tank and a pump is provided in the tank for pumping scrubbing liquid from the interior of the tank back into the filter so that the gas to be scrubbed mixes with the scrubbing liquid and passes through the filter with the scrubbing liquid.

3 Claims, 6 Drawing Figures

