

new PUEBLO™ (Office Zone)
Square Lay-in & Tegular
smooth texture

SUSTAIN™
High Performance
Sustainable Ceiling Systems

**GREENGUARD
Gold Certified**
(details below)

Declare.

LEED® WELL | LBC

70% RECYCLED CONTENT

Calculate sustainability with Green Genie™
armstrongceilings.com/greengenie

- energy management
- construction waste mgmt
- regional materials
- design for flexibility
- EPD
- recyclable/producer resp.
- biobased materials
- recycled content
- sourcing of raw materials
- material ingredient reporting
- low emitting materials
- lighting quality
- acoustics

LOCATION DEPENDENT

VISUAL SELECTION

armstrongceilings.com/suspdwgs	Susp. Dwg.	Item No.	Dimensions (Inches)
PUEBLO™ (Office Zone) High NRC 15/16" Square Lay-in		1864	24 x 24 x 1"
		1865	24 x 48 x 1"
9/16" Beveled Tegular		1866	24 x 24 x 1"
		1867	24 x 48 x 1"
15/16" Beveled Tegular		1868	24 x 24 x 1"
		1869	24 x 48 x 1"
PUEBLO™ (Office Zone) 15/16" Square Lay-in		1812	24 x 24 x 3/4"
		1837	24 x 48 x 3/4"
9/16" Beveled Tegular		1813	24 x 24 x 3/4"
		1838	24 x 48 x 3/4"
15/16" Beveled Tegular		1814	24 x 24 x 3/4"
		1839	24 x 48 x 3/4"


PERFORMANCE SELECTION

Dots represent high level of performance.

\$\$\$\$

Acoustics		Total Acoustics ¹	Fire Performance	Light Reflect	Bio-Block	Humi-Guard+	Certified Low VOC Emissions	Durability	Recycle Program	30-Yr Warranty
NRC	CAC									
0.90*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.90*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.90*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.90*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.70*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.70*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.70*	30	N/A	Class A	0.82	*	*	*	Std	*	*
0.70*	30	N/A	Class A	0.82	*	*	*	Std	*	*

SUSPENSION SYSTEMS



PHYSICAL DATA

Material
Wet-formed mineral fiber with acoustically transparent membrane.

Surface Finish
Acoustically transparent membrane with factory-applied latex paint.

Fire Performance
Class A: ASTM E84 and CAN/ULC S102 surface burning characteristics. Flame Spread Index 25 or less. Smoke Developed Index 50 or less (UL labeled).

ASTM E1264 Classification
Type IV, Form 2, Pattern E
Fire Class A

Humidity/Sag Resistance
HumiGuard™ Plus ceiling panels are recommended for areas subject to high humidity, up to, but not including, standing water and outdoor applications.

Anti-Mold/Mildew
Ceiling panels with BioBlock™ performance resist the growth of mold and mildew on the panel surface.

VOC Emissions
GREENGUARD Gold Certified
Third-party certified compliant with California Department of Public Health CDPH/EHLB/Standard Method Version 1.2, 2017. This standard is the guideline for low emissions in LEED™, WELL Building Standard™, Living Building Challenge™ (LBC), CalGreen Title 24, ANSI/ASHRAE/USGBC/IES Standard 189; ANSI/GBI Green Building Assessment Protocol.

Acoustical Performance
CAC testing conducted using Prelude XL suspension system for 15/16" edge detail and Silhouette suspension system for 9/16" edge detail.

High Recycled Content
Classified as containing greater than 50% total recycled content. Total recycled content based on product composition of post-consumer and pre-consumer (post-industrial) recycled content per FTC guidelines.



Insulation Value
1812, 1813, 1814, 1837, 1838, 1839 – R Factor – 2.1 (BTU units)
R Factor – 0.27 (Watts units)
1864, 1865, 1866, 1867, 1868, 1869 – R Factor – 2.9 (BTU units)
R Factor – 0.445 (Watts units)

30-Year Performance Guarantee & Warranty
When installed with Armstrong™ Suspension System. Details at armstrongceilings.com/warranty

Weight; Square Feet/Carton
1812, 1837 – 1.08 LBS/SF; 48 SF/CTN
1813, 1814, 1838, 1839 – 1.05 LBS/SF; 48 SF/CTN
1866, 1868 – 1.09 LBS/SF; 32 SF/CTN
1867, 1869 – 1.09 LBS/SF; 48 SF/CTN
1864 – 1.12 LBS/SF; 32 SF/CTN
1865 – 1.12 LBS/SF; 48 SF/CTN

Minimum Order Quantity
1 carton

MINERAL FIBER – Standard

