acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

SECTION 1: Identification

1.1 Product identifier

Trade name Mega Foam

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Foaming vehicle wash Concentrate

1.3 Details of the supplier of the safety data sheet

Detail Geek Auto Care Inc. PO Box 32154 Regina, Saskatchewan S4N 7L2

1-866-417-9175 info@detailgeekautocare.com

http://detailgeekautocare.com

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500 24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard state- ment
A.3	serious eye damage/eye irritation	1	Eye Dam. 1	H318
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects
The product is combustible and can be ignited by potential ignition sources.

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

GHS05



United States: en Page: 1 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

- Hazard statements

H227 Combustible liquid.

H318 Causes serious eye damage.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 Immediately call a poison center/doctor.

P370+P378 In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling

sodium laureth sulfate, sodium [dodecanoyl(methyl)amino]acetate

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).

Harmful to aquatic life with long lasting effects (GHS category 3: aquatic toxicity - acute and/or chronic).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
cocamidopropylhydroxysultaine	CAS No 68139-30-0	3-<12	Eye Irrit. 2A / H319
sodium laureth sulfate	CAS No 68585-34-2	3-<12	Acute Tox. 4 / H312 Skin Irrit. 2 / H315 Eye Dam. 1 / H318
dipropylene glycol monomethyl ether	CAS No 34590-94-8	3-<12	Flam. Liq. 4 / H227
Propan-2-ol	CAS No 67-63-0	1-<3	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225
2-methylpentane-2,4-diol	CAS No 107-41-5	1-<3	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319
sodium [dodecanoyl(methyl)amino]acetate	CAS No 137-16-6	1-<3	Acute Tox. 2 / H330 Skin Irrit. 2 / H315 Eye Dam. 1 / H318

United States: en Page: 2 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. Provide fresh air.

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, Alcohol resistant foam, BC-powder, Carbon dioxide (CO2)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NOx), Carbon monoxide (CO), Carbon dioxide (CO2)

United States: en Page: 3 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it.

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

United States: en Page: 4 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

- Ventilation requirements

Use local and general ventilation. Ground/bond container and receiving equipment.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)

Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	hexylene glycol	107-41-5	PEL (CA)					25	125		Cal/ OSHA PEL
US	hexylene glycol	107-41-5	REL					25	125		NIOS H REL
US	hexylene glycol	107-41-5	TLV®				10			i, aer- osol	AC- GIH® 2019
US	hexylene glycol	107-41-5	TLV®	25		50				vap	AC- GIH® 2019
US	(2-methoxy- methylethoxy)pro- panol	34590- 94-8	TLV®	100		150					AC- GIH® 2019

United States: en Page: 5 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Occup	Occupational exposure limit values (Workplace Exposure Limits)										
Coun try	Name of agent	CAS No	Iden- tifier	TWA [ppm]	TWA [mg/ m³]	STEL [ppm]	STEL [mg/ m³]	Ceil- ing-C [ppm]	Ceil- ing-C [mg/ m³]	Nota tion	Sourc e
US	dipropylene glycol methyl ether	34590- 94-8	PEL (CA)	100	600	150	900				Cal/ OSHA PEL
US	dipropylene glycol methyl ether	34590- 94-8	REL	100 (10 h)	600 (10 h)	150	900				NIOS H REL
US	dipropylene glycol methyl ether	34590- 94-8	PEL	100	600						29 CFR 1910.1 000
US	2-propanol	67-63-0	TLV®	200		400					AC- GIH® 2019
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/ OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOS H REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1 000

Notation

aerosol as aerosols

Ceiling-C ceiling value is a limit value above which exposure should not occur

inhalable fraction

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless

otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted

average (unless otherwise specified

vap as vapors

Biological limit values										
Country	Name of agent	Parameter	Nota- tion	Identifier	Value	Source				
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH®				

2019

Relevant DNELs of components of the mixture									
Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time			
sodium laureth	68585-34-2	DNEL	175 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic			

United States: en Page: 6 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Relevant DNELs of components of the mixture							
Name of sub- stance	CAS No	End- point	Threshold level	Protection goal, route of expos- ure	Used in	Exposure time	
sulfate						effects	
sodium laureth sulfate	68585-34-2	DNEL	2,750 mg/ kg bw/day	human, dermal	worker (industry)	chronic - systemic effects	
sodium laureth sulfate	68585-34-2	DNEL	132 μg/cm²	human, dermal	worker (industry)	chronic - local ef- fects	
dipropylene glycol monomethyl ether	34590-94-8	DNEL	950 mg/kg	human, dermal	worker (industry)	chronic - systemic effects	
dipropylene glycol monomethyl ether	34590-94-8	DNEL	404 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects	
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
2-methylpentane-2,4- diol	107-41-5	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
2-methylpentane-2,4- diol	107-41-5	DNEL	49 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects	
2-methylpentane-2,4- diol	107-41-5	DNEL	98 mg/m³	human, inhalatory	worker (industry)	acute - local effects	
2-methylpentane-2,4- diol	107-41-5	DNEL	42 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects	
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	DNEL	5 mg/m ³	human, inhalatory	worker (industry)	chronic - local ef- fects	
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	DNEL	71 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects	
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects	

Relevant PNECs of components of the mixture

Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
sodium laureth sulfate	68585-34-2	PNEC	0.24 ^{mg} / _I	aquatic organisms	freshwater	short-term (single instance)
sodium laureth sulfate	68585-34-2	PNEC	0.024 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)

United States: en Page: 7 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Relevant PNECs o	f components	of the mi	xture			
Name of sub- stance	CAS No	End- point	Threshold level	Organism	Environmental compartment	Exposure time
sodium laureth sulfate	68585-34-2	PNEC	10 ^g / _l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
sodium laureth sulfate	68585-34-2	PNEC	0.92 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
sodium laureth sulfate	68585-34-2	PNEC	0.092 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
sodium laureth sulfate	68585-34-2	PNEC	7.5 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (singl instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _I	microorganisms	sewage treatment plant (STP)	short-term (singl instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	19 ^{mg} / _l	aquatic organisms	freshwater	short-term (singl instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	1.9 ^{mg} / _l	aquatic organisms	marine water	short-term (singlinstance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	4,168 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (sing instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	2.2 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (sing instance)
dipropylene glycol monomethyl ether	34590-94-8	PNEC	192 ^{mg} / _l	aquatic organisms	water	intermittent relea
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	freshwater	short-term (sing instance)
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	marine water	short-term (singlinstance)
Propan-2-ol	67-63-0	PNEC	2,251 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (sing instance)
Propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	benthic organisms	sediment	short-term (singlinstance)
Propan-2-ol	67-63-0	PNEC	552 ^{mg} / _{kg}	pelagic organisms	sediment	short-term (sing instance)
Propan-2-ol	67-63-0	PNEC	160 ^{mg} / _{kg}	(top) predators	water	short-term (sing instance)
Propan-2-ol	67-63-0	PNEC	28 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (sing instance)
Propan-2-ol	67-63-0	PNEC	141 ^{mg} / _l	aquatic organisms	water	intermittent relea
2-methylpentane-2,4- diol	107-41-5	PNEC	0.43 ^{mg} / _l	aquatic organisms	freshwater	short-term (sing instance)
2-methylpentane-2,4- diol	107-41-5	PNEC	0.043 ^{mg} / _l	aquatic organisms	marine water	short-term (sing instance)

United States: en Page: 8 / 21

acc. to 29 CFR 1910.1200 App D



Relevant PNECs of components of the mixture

Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

stance	CAS NO	point	level	Organism	compartment	Exposure time
2-methylpentane-2,4- diol	107-41-5	PNEC	20 ^{mg} / _I	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
2-methylpentane-2,4- diol	107-41-5	PNEC	1.6 ^{mg} / _{kg}	aquatic organisms	freshwater sediment	short-term (single instance)
2-methylpentane-2,4- diol	107-41-5	PNEC	0.16 ^{mg} / _{kg}	aquatic organisms	marine sediment	short-term (single instance)
2-methylpentane-2,4- diol	107-41-5	PNEC	0.066 ^{mg} / _{kg}	terrestrial organ- isms	soil	short-term (single instance)
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	10 ^{mg} / _l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	0.034 ^{mg} / _{kg}	benthic organisms	sediment	short-term (single instance)
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	0.0034 ^{mg} / kg	pelagic organisms	sediment	short-term (single instance)
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	0.3 ^{mg} / _l	aquatic organisms	water	intermittent release
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	0.009 ^{mg} / _l	aquatic organisms	freshwater	short-term (single instance)
sodium [dodecanoyl(methyl)a mino]acetate	137-16-6	PNEC	0.001 ^{mg} / _l	aquatic organisms	marine water	short-term (single instance)

sewage treatment plant (STP)

freshwater sediment

marine sediment

soil

short-term (single

instance)

short-term (single

instance)

short-term (single

instance)

short-term (single

instance)

8.2 Exposure controls

sodium

[dodecanoyl(methyl)a

mino]acetate

sodium

[dodecanoyl(methyl)a mino]acetate

sodium

[dodecanoyl(methyl)a

mino]acetate

sodium

[dodecanoyl(methyl)a

mino]acetate

137-16-6

137-16-6

137-16-6

137-16-6

Appropriate engineering controls General ventilation.

United States: en Page: 9 / 21

 $3 \frac{mg}{l}$

 $0.064 \frac{mg}{kg}$

 $0.006 \frac{mg}{kg}$

 $0.008 \frac{mg}{ka}$

aquatic organisms

aquatic organisms

aquatic organisms

terrestrial organ-

isms

PNEC

PNEC

PNEC

PNEC

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	imperial blue
Particle	not relevant (liquid)
Odor	fruity

Other safety parameters

pH (value)	7-8
Melting point/freezing point	not determined
Initial boiling point and boiling range	82 °C
Flash point	70 °C at 101 kPa closed cup
Evaporation rate	Not determined
Flammability (solid, gas)	not relevant, (fluid)

United States: en Page: 10 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

	•
Explosive limits	
- Lower explosion limit (LEL)	1.1 vol%
- Upper explosion limit (UEL)	3 vol%
Vapor pressure	4.3 kPa at 20 °C
Density	1 ^g / _{ml}
Vapor density	this information is not available
Solubility(ies)	
- Water solubility	miscible in any proportion
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	270 °C (auto-ignition temperature (liquids and gases))
Viscosity	not determined
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment:

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

United States: en Page: 11 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture

Name of substance	CAS No	Exposure route	ATE
sodium laureth sulfate	68585-34-2	dermal	≥2,000 ^{mg} / _{kg}
sodium [dodecanoyl(methyl)amino]acetate	137-16-6	inhalation: dust/mist	>0.05 ^{mg} / _l /4h

Skin corrosion/irritation

Shall not be classified as corrosive/irritant to skin.

Serious eye damage/eye irritation

Causes serious eye damage.

Respiratory or skin sensitization

Shall not be classified as a respiratory or skin sensitizer.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Carcinogenicity

Shall not be classified as carcinogenic.

United States: en Page: 12 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans							
Name of substance CAS No Classification Number							
Propan-2-ol 67-63-0 3							

Legend

Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Shall not be classified as a reproductive toxicant.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Shall not be classified as a specific target organ toxicant (repeated exposure).

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Harmful to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
cocamidopropylhy- droxysultaine	68139-30-0	LC50	1.7 – 2 ^{mg} / _l	algae	72 h
cocamidopropylhy- droxysultaine	68139-30-0	LC50	1.7 – 2 ^{mg} / _l	daphnia	48 h
cocamidopropylhy- droxysultaine	68139-30-0	LC50	1.7 – 2 ^{mg} / _l	fish	96 h
cocamidopropylhy- droxysultaine	68139-30-0	EC50	11 ^{mg} / _l	aquatic invertebrates	48 h
cocamidopropylhy- droxysultaine	68139-30-0	ErC50	0.32 ^{mg} / _l	algae	72 h
sodium laureth sulfate	68585-34-2	LC50	7.1 ^{mg} / _l	fish	96 h
sodium laureth sulfate	68585-34-2	EC50	7.2 ^{mg} / _l	aquatic invertebrates	48 h
sodium laureth sulfate	68585-34-2	ErC50	27 ^{mg} / _I	algae	72 h
dipropylene glycol monomethyl ether	34590-94-8	LC50	>150 ^{mg} / _I	fish	72 h
dipropylene glycol monomethyl ether	34590-94-8	ErC50	>969 ^{mg} / _I	algae	72 h

United States: en Page: 13 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Aquatic toxicity (acute) of components of the mixture						
Name of substance	CAS No	Endpoint	Value	Species	Exposure time	
Propan-2-ol	67-63-0	LC50	10,000 ^{mg} / _l	fish	96 h	
2-methylpentane-2,4-di- ol	107-41-5	LC50	9,910 ^{mg} / _l	fish	96 h	
2-methylpentane-2,4-di- ol	107-41-5	EC50	5,410 ^{mg} / _l	aquatic invertebrates	48 h	
2-methylpentane-2,4-di- ol	107-41-5	ErC50	>429 ^{mg} / _I	algae	72 h	
sodium [dodecanoyl(methyl)ami no]acetate	137-16-6	LC50	107 ^{mg} / _l	fish	96 h	
sodium [dodecanoyl(methyl)ami no]acetate	137-16-6	EC50	30 ^{mg} / _l	aquatic invertebrates	48 h	
sodium [dodecanoyl(methyl)ami no]acetate	137-16-6	ErC50	79 ^{mg} / _l	algae	72 h	

Aquatic toxicity (chronic) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
sodium laureth sulfate	68585-34-2	EC50	0.37 ^{mg} / _l	aquatic invertebrates	21 d
sodium laureth sulfate	68585-34-2	LC50	0.74 ^{mg} / _l	aquatic invertebrates	21 d
Propan-2-ol	67-63-0	LC50	>10,000 ^{mg} / _I	aquatic invertebrates	24 h
sodium [dodecanoyl(methyl)ami no]acetate	137-16-6	EC50	>1,000 ^{mg} / _l	microorganisms	3 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

Data are not available.

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

Data are not available.

12.6 Endocrine disrupting properties

None of the ingredients are listed.

United States: en Page: 14 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1	UN number	not subject to transport regulations
------	-----------	--------------------------------------

14.2 UN proper shipping name not relevant
 14.3 Transport hazard class(es) not assigned
 14.4 Packing group not assigned

14.5 Environmental hazards non-environmentally hazardous acc. to the dangerous

goods regulations

14.6 Special precautions for user

There is no additional information.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code

The cargo is not intended to be carried in bulk.

Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information Not subject to transport regulations.

International Maritime Dangerous Goods Code (IMDG) - Additional information Not subject to IMDG.

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information Not subject to ICAO-IATA.

United States: en Page: 15 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question National regulations (United States)

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings

Name of substance	CAS No	Remarks	Effective date
Propan-2-ol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	carrier fluid / dis- solver	
ammonium alcohol ether sulfate	68037-05-8	surfactant	
cocamidopropylhydroxysultaine	68139-30-0	surfactant	
sodium laureth sulfate	68585-34-2	surfactant	
dipropylene glycol monomethyl ether	34590-94-8	surfactant	
Propan-2-ol	67-63-0	alcohols	OEHHA RELs
2-methylpentane-2,4-diol	107-41-5	humectant	
sodium [dodecanoyl(methyl)amino]acetate	137-16-6	surfactant	
sodium chloride	7647-14-5	viscosity modifier	
polyethylene oxide lauryl ether	9002-92-0	surfactant	
d-limonene	5989-27-5	fragrance	EU Fragrance Allergens
eugenol	97-53-0	fragrance	EU Fragrance Allergens
alcohols, C12-14 secondary, ethoxylated	84133-50-6	surfactant	

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshol d	De Minimis Con- centration Threshold
Propan-2-ol	67-63-0				1.0 %

United States: en Page: 16 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
dipropylene glycol monomethyl ether	34590-94-8	A, O	
Propan-2-ol	67-63-0	A, N, O	
2-methylpentane-2,4-diol	107-41-5	Α	

Legend

American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1998, available from NIOSH, Biblications Discountification (City Property of Company).

National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
 Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910,

O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
dipropylene glycol monomethyl ether	34590-94-8		F2
Propan-2-ol	67-63-0		F3
2-methylpentane-2,4-diol	107-41-5		F2

Legend

F2 Flammable - Second Degree F3 Flammable - Third Degree

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
PROPANOL, (2-METHOXYMETHYLETH-OXY)-	34590-94-8	
2-PROPANOL	67-63-0	E
2,4-PENTANEDIOL, 2-METHYL-	107-41-5	

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
dipropylene glycol monomethyl ether	34590-94-8	Т
Propan-2-ol	67-63-0	T, F
2-methylpentane-2,4-diol	107-41-5	Т

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

United States: en Page: 17 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals Type of the toxicity CAS No Wt% Name of substance Name acc. to inventory Remarks 75-21-8 ethylene oxide ethylene oxide 0.000019 cancer ethylene oxide ethylene oxide 75-21-8 0.000019 female 0.000019 ethylene oxide ethylene oxide 75-21-8 developmental, male 1,4-dioxane 123-91-1 0.00019 1,4-dioxane cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 7.1 %

- Regulated Volatile Organic Compounds (VOC-Cal ARB) 7.1 %

Industry or sector specific available guidance(s) NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	3	major injury likely unless prompt action is taken and medical treatment is given
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperat- ures before ignition can occur
Health	3	material that, under emergency conditions, can cause serious or permanent injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

United States: en Page: 18 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg.
REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control

United States: en Page: 19 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

	·
Abbr.	Descriptions of used abbreviations
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
STEL	Short-term exposure limit
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative
·	

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

United States: en Page: 20 / 21

acc. to 29 CFR 1910.1200 App D



Mega Foam

Version number: GHS 1.0 Date of compilation: 2021-05-28

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H227	Combustible liquid.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H336	May cause drowsiness or dizziness.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.

United States: en Page: 21 / 21