

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

SECTION 1: Identification

1.1 Product identifier

Trade name

Paint Sealant

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Paint sealer with resin

1.3 Details of the supplier of the safety data sheet

Detail Geek Auto Care Inc.
PO Box 32154
Regina, Saskatchewan
S4N 7L2

1-866-417-9175

info@detailgeekautocare.com

<http://detailgeekautocare.com>

1.4 Emergency telephone number

Emergency information service

USA 1.800.535.5053, INTL 1.352.323.3500
24 hour emergency number

SECTION 2: Hazard(s) identification

2.1 Classification of the substance or mixture

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Section	Hazard class	Category	Hazard class and category	Hazard statement
A.2	skin corrosion/irritation	2	Skin Irrit. 2	H315
A.7	reproductive toxicity	2	Repr. 2	H361f
A.9	specific target organ toxicity - repeated exposure	1	STOT RE 1	H372
B.6	flammable liquid	4	Flam. Liq. 4	H227

For full text of abbreviations: see SECTION 16.

The most important adverse physicochemical, human health and environmental effects

Delayed or immediate effects can be expected after short or long-term exposure. The product is combustible and can be ignited by potential ignition sources. The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

2.2 Label elements

Labelling acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

- Signal word danger

- Pictograms

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

GHS07, GHS08



- Hazard statements

H227	Combustible liquid.
H315	Causes skin irritation.
H361f	Suspected of damaging fertility.
H372	Causes damage to organs through prolonged or repeated exposure.

- Precautionary statements

P202	Do not handle until all safety precautions have been read and understood.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	If on skin: Wash with plenty of water.
P308+P313	If exposed or concerned: Get medical advice/attention.
P314	Get medical advice/attention if you feel unwell.
P321	Specific treatment (see on this label).
P332+P313	If skin irritation occurs: Get medical advice/attention.
P362	Take off contaminated clothing and wash it before reuse.
P370+P378	In case of fire: Use sand, carbon dioxide or powder extinguisher to extinguish.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- Hazardous ingredients for labelling octamethylcyclotetrasiloxane, stoddard solvent

2.3 Other hazards

This material is combustible, but will not ignite readily.

Hazards not otherwise classified

Contains Ethyl methylphenylglycidate. May produce an allergic reaction.
May be harmful if inhaled (GHS category 5: acutely toxic - inhalation).
Very toxic to aquatic life with long lasting effects (GHS category 1: aquatic toxicity - acute and/or chronic).

Results of PBT and vPvB assessment

Containing a PBT-/vPvB-substance in a concentration of $\geq 0,1\%$.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not relevant (mixture)

3.2 Mixtures

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Description of the mixture

Name of substance	Identifier	Wt%	Classification acc. to GHS
distillates (petroleum) hydrotreated, light	CAS No 64742-47-8	3 - < 12	Asp. Tox. 1 / H304
odorless mineral spirits	CAS No 64742-48-9	3 - < 12	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT SE 3 / H336 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
octamethylcyclotetrasiloxane	CAS No 556-67-2	3 - < 12	Repr. 2 / H361f Flam. Liq. 3 / H226
decamethylcyclopentasiloxane	CAS No 541-02-6	1 - < 3	Flam. Liq. 4 / H227
Propan-2-ol	CAS No 67-63-0	1 - < 3	Eye Irrit. 2 / H319 STOT SE 3 / H336 Flam. Liq. 2 / H225
N,N-bis(2-Hydroxyethyl)oleamide	CAS No 93-83-4	1 - < 3	Skin Irrit. 2 / H315 Eye Irrit. 2 / H319
stoddard solvent	CAS No 64742-47-8	1 - < 3	Acute Tox. 3 / H331 Skin Irrit. 2 / H315 STOT RE 1 / H372 Asp. Tox. 1 / H304 Flam. Liq. 3 / H226
Ethyl methylphenylglycidate	CAS No 77-83-8	0.1 - < 1	Skin Sens. 1B / H317
methanol	CAS No 67-56-1	0.1 - < 1	Acute Tox. 3 / H301 Acute Tox. 3 / H311 Acute Tox. 3 / H331 STOT SE 1 / H370 Flam. Liq. 2 / H225

Hazardous ingredients, Consideration of other advice

This table, if present, includes all GHS classified ingredients present above their cut-off limits, even if the finished product is not classified as hazardous by GHS.

Exact percentage of ingredients is withheld as a trade secret.

For full text of abbreviations: see SECTION 16.

SECTION 4: First-aid measures

4.1 Description of first-aid measures

General notes

Do not leave affected person unattended. Remove victim out of the danger area. Keep affected person warm, still and covered. Take off immediately all contaminated clothing. In all cases of doubt, or when symptoms persist, seek medical advice. In case of unconsciousness place person in the recovery position. Never give anything by mouth.

Following inhalation

If breathing is irregular or stopped, immediately seek medical assistance and start first aid actions. In case of respiratory tract irritation, consult a physician. Provide fresh air.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Following skin contact

Wash with plenty of soap and water.

Following eye contact

Remove contact lenses, if present and easy to do. Continue rinsing. Irrigate copiously with clean, fresh water for at least 10 minutes, holding the eyelids apart.

Following ingestion

Rinse mouth with water (only if the person is conscious). Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms and effects are not known to date.

4.3 Indication of any immediate medical attention and special treatment needed

none

SECTION 5: Fire-fighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water spray, BC-powder, Carbon dioxide (CO₂)

Unsuitable extinguishing media

Water jet

5.2 Special hazards arising from the substance or mixture

In case of insufficient ventilation and/or in use, may form flammable/explosive vapor-air mixture. Solvent vapors are heavier than air and may spread along floors. Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures.

Hazardous combustion products

Nitrogen oxides (NO_x), Carbon monoxide (CO), Carbon dioxide (CO₂)

5.3 Advice for firefighters

In case of fire and/or explosion do not breathe fumes. Coordinate firefighting measures to the fire surroundings. Do not allow firefighting water to enter drains or water courses. Collect contaminated firefighting water separately. Fight fire with normal precautions from a reasonable distance.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Remove persons to safety.

For emergency responders

Wear breathing apparatus if exposed to vapors/dust/aerosols/gases.

6.2 Environmental precautions

Keep away from drains, surface and ground water. Retain contaminated washing water and dispose of it. If substance has entered a water course or sewer, inform the responsible authority.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

6.3 Methods and material for containment and cleaning up

Advice on how to contain a spill

Covering of drains

Advice on how to clean up a spill

Wipe up with absorbent material (e.g. cloth, fleece). Collect spillage: sawdust, kieselgur (diatomite), sand, universal binder

Appropriate containment techniques

Use of adsorbent materials.

Other information relating to spills and releases

Place in appropriate containers for disposal. Ventilate affected area.

6.4 Reference to other sections

Hazardous combustion products: see section 5. Personal protective equipment: see section 8. Incompatible materials: see section 10. Disposal considerations: see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Recommendations

- Measures to prevent fire as well as aerosol and dust generation

Use local and general ventilation. Avoidance of ignition sources. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharge. Use only in well-ventilated areas. Due to danger of explosion, prevent leakage of vapours into cellars, flues and ditches. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools.

- Specific notes/details

Places which are not ventilated, e.g. unventilated below ground level areas such as trenches, conduits and shafts, are particularly prone to the presence of flammable substances or mixtures. Vapors are heavier than air, spread along floors and form explosive mixtures with air. Vapors may form explosive mixtures with air.

Advice on general occupational hygiene

Wash hands after use. Do not eat, drink and smoke in work areas. Remove contaminated clothing and protective equipment before entering eating areas. Never keep food or drink in the vicinity of chemicals. Never place chemicals in containers that are normally used for food or drink. Keep away from food, drink and animal feedingstuffs.

7.2 Conditions for safe storage, including any incompatibilities

Managing of associated risks

- Explosive atmospheres

Keep container tightly closed and in a well-ventilated place. Use local and general ventilation. Keep cool. Protect from sunlight.

- Flammability hazards

Keep away from sources of ignition - No smoking. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharge. Protect from sunlight.

Control of the effects

Protect against external exposure, such as

frost

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

- Ventilation requirements
Use local and general ventilation. Ground/bond container and receiving equipment.
- Packaging compatibilities
Only packagings which are approved (e.g. acc. to the Dangerous Goods Regulations) may be used.

7.3 Specific end use(s)

See section 16 for a general overview.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	petroleum distillates (naphtha) (rubber solvent)	64742-48-9	PEL	500	2,000						29 CFR 1910.1000
US	methanol	67-56-1	TLV®	200		250				H	ACGIH® 2019
US	methyl alcohol	67-56-1	REL	200 (10 h)	260 (10 h)	250	325				NIOSH REL
US	methyl alcohol	67-56-1	PEL	200	260						29 CFR 1910.1000
US	methyl alcohol (methanol)	67-56-1	PEL (CA)	200	260	250	325	1,000			Cal/OSHA PEL
US	2-propanol	67-63-0	TLV®	200		400					ACGIH® 2019
US	isopropyl alcohol	67-63-0	PEL (CA)	400	980	500	1,225				Cal/OSHA PEL
US	isopropyl alcohol	67-63-0	REL	400 (10 h)	980 (10 h)	500	1,225				NIOSH REL
US	isopropyl alcohol	67-63-0	PEL	400	980						29 CFR 1910.1000

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Occupational exposure limit values (Workplace Exposure Limits)											
Country	Name of agent	CAS No	Identifier	TWA [ppm]	TWA [mg/m ³]	STEL [ppm]	STEL [mg/m ³]	Ceiling-C [ppm]	Ceiling-C [mg/m ³]	Notation	Source
US	Polytetrafluoroethylene, decomposition products	9002-84-0	PEL (CA)							PTFE-decomp	Cal/OSHA PEL

Notation

Ceiling-C ceiling value is a limit value above which exposure should not occur absorbed through the skin

H Thermal decomposition of the fluorocarbon chain in air leads to the formation of oxidized products containing carbon, fluorine and oxygen. An index of exposure to these products is possible through their alkaline hydrolysis followed by a quantitative determination of fluoride content. No particular concentration limit is specified pending evaluation of the toxicity of the products but concentrations should be kept below the sensitivity of the analytical method

STEL short-term exposure limit: a limit value above which exposure should not occur and which is related to a 15-minute period (unless otherwise specified)

TWA time-weighted average (long-term exposure limit): measured or calculated in relation to a reference period of 8 hours time-weighted average (unless otherwise specified)

Biological limit values						
Country	Name of agent	Parameter	Notation	Identifier	Value	Source
US	methanol	methanol		BEI®	15 mg/l	ACGIH® 2019
US	isopropanol	acetone		BEI®	40 mg/l	ACGIH® 2019

Relevant DNELs of components of the mixture						
Name of substance	CAS No	Endpoint	Threshold level	Protection goal, route of exposure	Used in	Exposure time
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
octamethylcyclotetrasiloxane	556-67-2	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
decamethylcyclopentasiloxane	541-02-6	DNEL	97 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Relevant DNELs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
decamethylcyclopentasiloxane	541-02-6	DNEL	24 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
Propan-2-ol	67-63-0	DNEL	888 mg/kg	human, dermal	worker (industry)	chronic - systemic effects
Propan-2-ol	67-63-0	DNEL	500 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	DNEL	73 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	DNEL	4.2 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	DNEL	31 µg/cm ²	human, dermal	worker (industry)	chronic - local effects
stoddard solvent	64742-47-8	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
stoddard solvent	64742-47-8	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
stoddard solvent	64742-47-8	DNEL	44 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
stoddard solvent	64742-47-8	DNEL	55 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
stoddard solvent	64742-47-8	DNEL	80 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
stoddard solvent	64742-47-8	DNEL	30 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects
Ethyl methylphenylglycidate	77-83-8	DNEL	2.5 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
Ethyl methylphenylglycidate	77-83-8	DNEL	0.7 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - systemic effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - systemic effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	chronic - local effects
methanol	67-56-1	DNEL	130 mg/m ³	human, inhalatory	worker (industry)	acute - local effects
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	chronic - systemic effects

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Relevant DNELs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Protection goal, route of exposure	Used in	Exposure time
methanol	67-56-1	DNEL	20 mg/kg bw/day	human, dermal	worker (industry)	acute - systemic effects

Relevant PNECs of components of the mixture

Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.059 mg/kg	pelagic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	1.7 mg/kg	(top) predators	water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.44 µg/l	aquatic organisms	freshwater	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.044 µg/l	aquatic organisms	marine water	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	3 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.3 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.59 mg/kg	benthic organisms	sediment	short-term (single instance)
octamethylcyclotetrasiloxane	556-67-2	PNEC	0.16 mg/kg	terrestrial organisms	soil	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	benthic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	13 mg/kg	(top) predators	water	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	pelagic organisms	sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.2 µg/l	aquatic organisms	freshwater	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	0.12 µg/l	aquatic organisms	marine water	short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
decamethylcyclopentasiloxane	541-02-6	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	11 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.1 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
decamethylcyclopentasiloxane	541-02-6	PNEC	1.3 mg/kg	terrestrial organisms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	141 mg/l	aquatic organisms	freshwater	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	141 mg/l	aquatic organisms	marine water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	2,251 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	benthic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	552 mg/kg	pelagic organisms	sediment	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	160 mg/kg	(top) predators	water	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	28 mg/kg	terrestrial organisms	soil	short-term (single instance)
Propan-2-ol	67-63-0	PNEC	141 mg/l	aquatic organisms	water	intermittent release
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	0.007 mg/l	aquatic organisms	freshwater	short-term (single instance)
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	0.001 mg/l	aquatic organisms	marine water	short-term (single instance)
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	830 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	1.2 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	0.12 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	PNEC	0.24 mg/kg	terrestrial organisms	soil	short-term (single instance)
stoddard solvent	64742-47-8	PNEC	0.14 mg/l	aquatic organisms	freshwater	short-term (single instance)
stoddard solvent	64742-47-8	PNEC	0.35 mg/l	aquatic organisms	marine water	short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Relevant PNECs of components of the mixture						
Name of substance	CAS No	End-point	Threshold level	Organism	Environmental compartment	Exposure time
stoddard solvent	64742-47-8	PNEC	1.1 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
stoddard solvent	64742-47-8	PNEC	0.14 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	0.084 mg/l	aquatic organisms	water	intermittent release
Ethyl methyl-phenylglycidate	77-83-8	PNEC	0.008 mg/l	aquatic organisms	freshwater	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	8.4 µg/l	aquatic organisms	marine water	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	10 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	0.21 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	0.021 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
Ethyl methyl-phenylglycidate	77-83-8	PNEC	0.038 mg/kg	terrestrial organisms	soil	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	microorganisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	benthic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	pelagic organisms	sediment	short-term (single instance)
methanol	67-56-1	PNEC	1,540 mg/l	aquatic organisms	water	intermittent release
methanol	67-56-1	PNEC	21 mg/l	aquatic organisms	freshwater	short-term (single instance)
methanol	67-56-1	PNEC	2.1 mg/l	aquatic organisms	marine water	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/l	aquatic organisms	sewage treatment plant (STP)	short-term (single instance)
methanol	67-56-1	PNEC	77 mg/kg	aquatic organisms	freshwater sediment	short-term (single instance)
methanol	67-56-1	PNEC	7.7 mg/kg	aquatic organisms	marine sediment	short-term (single instance)
methanol	67-56-1	PNEC	100 mg/kg	terrestrial organisms	soil	short-term (single instance)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

8.2 Exposure controls

Appropriate engineering controls

General ventilation.

Individual protection measures (personal protective equipment)

Eye/face protection

Wear eye/face protection.

Skin protection

- Hand protection

Wear suitable gloves. Chemical protection gloves are suitable, which are tested according to EN 374. Check leak-tightness/impermeability prior to use. In the case of wanting to use the gloves again, clean them before taking off and air them well. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

- Other protection measures

Take recovery periods for skin regeneration. Preventive skin protection (barrier creams/ointments) is recommended. Wash hands thoroughly after handling.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

Use appropriate container to avoid environmental contamination. Keep away from drains, surface and ground water.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	liquid
Color	coral
Particle	not relevant (liquid)
Odor	sweet - fruity

Other safety parameters

pH (value)	not determined
Melting point/freezing point	not determined
Initial boiling point and boiling range	>65 °C at 1 atm
Flash point	61 °C at 101 kPa 142 °F at 1 atm closed cup
Evaporation rate	Not determined

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Flammability (solid, gas)	not relevant, (fluid)
Explosive limits	
- Lower explosion limit (LEL)	0.6 vol%
- Upper explosion limit (UEL)	6 vol%
Vapor pressure	4.3 kPa at 20 °C
Density	not determined
Vapor density	this information is not available
Relative density	0.99 (water = 1)
Solubility(ies)	not determined
Partition coefficient	
- n-octanol/water (log KOW)	this information is not available
Auto-ignition temperature	262 °C (auto-ignition temperature (liquids and gases))
Viscosity	
- Kinematic viscosity	5,556 mm ² /s at 25 °C
- Dynamic viscosity	5,500 cP at 25 °C
Explosive properties	none
Oxidizing properties	none
Temperature class (USA, acc. to NEC 500)	T2B (maximum permissible surface temperature on the equipment: 260 °C)

SECTION 10: Stability and reactivity

10.1 Reactivity

Concerning incompatibility: see below "Conditions to avoid" and "Incompatible materials". The mixture contains reactive substance(s). Risk of ignition.

If heated:

Risk of ignition

10.2 Chemical stability

See below "Conditions to avoid".

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

10.3 Possibility of hazardous reactions

No known hazardous reactions.

10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints to prevent fire or explosion

Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

10.5 Incompatible materials

Oxidizers

10.6 Hazardous decomposition products

Reasonably anticipated hazardous decomposition products produced as a result of use, storage, spill and heating are not known. Hazardous combustion products: see section 5.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Test data are not available for the complete mixture.

Classification procedure

The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

Classification acc. to OSHA "Hazard Communication Standard" (29 CFR 1910.1200)

Acute toxicity

Shall not be classified as acutely toxic.

GHS of the United Nations, annex 4: May be harmful if inhaled.

Acute toxicity estimate (ATE) of components of the mixture			
Name of substance	CAS No	Exposure route	ATE
odorless mineral spirits	64742-48-9	inhalation: vapor	>5 mg/l/4h
stoddard solvent	64742-47-8	inhalation: vapor	>5.5 mg/l/4h
methanol	67-56-1	oral	100 mg/kg

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/eye irritation

Shall not be classified as seriously damaging to the eye or eye irritant.

Respiratory or skin sensitization

Contains Ethyl methylphenylglycidate. May produce an allergic reaction.

Germ cell mutagenicity

Shall not be classified as germ cell mutagenic.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Carcinogenicity

Shall not be classified as carcinogenic.

IARC Monographs on the Evaluation of Carcinogenic Risks to Humans

Name of substance	CAS No	Classification	Number
Propan-2-ol	67-63-0	3	

Legend

3 Not classifiable as to carcinogenicity in humans

Reproductive toxicity

Suspected of damaging fertility.

Specific target organ toxicity - single exposure

Shall not be classified as a specific target organ toxicant (single exposure).

Specific target organ toxicity - repeated exposure

Causes damage to organs through prolonged or repeated exposure.

Aspiration hazard

Shall not be classified as presenting an aspiration hazard.

SECTION 12: Ecological information

12.1 Toxicity

Very toxic to aquatic life with long lasting effects.

Aquatic toxicity (acute) of components of the mixture

Name of substance	CAS No	Endpoint	Value	Species	Exposure time
octamethylcyclotetrasiloxane	556-67-2	LC50	>22 µg/l	fish	96 h
octamethylcyclotetrasiloxane	556-67-2	EC50	>1,000 mg/l	aquatic invertebrates	96 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	96 h
decamethylcyclopentasiloxane	541-02-6	EC50	>2.9 µg/l	aquatic invertebrates	48 h
Propan-2-ol	67-63-0	LC50	10,000 mg/l	fish	96 h
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	LC50	5.1 mg/l	fish	96 h
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	EC50	3.2 mg/l	aquatic invertebrates	48 h
stoddard solvent	64742-47-8	LC50	0.18 mg/l	fish	96 h

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Aquatic toxicity (acute) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
stoddard solvent	64742-47-8	LL50	41 mg/l	fish	96 h
stoddard solvent	64742-47-8	EL50	2.5 mg/l	algae	96 h
stoddard solvent	64742-47-8	EC50	0.58 mg/l	algae	96 h
Ethyl methylphenylglycidate	77-83-8	LC50	4.2 mg/l	fish	96 h
Ethyl methylphenylglycidate	77-83-8	EC50	95 mg/l	aquatic invertebrates	24 h
Ethyl methylphenylglycidate	77-83-8	ErC50	36 mg/l	algae	72 h
methanol	67-56-1	LC50	15,400 mg/l	fish	96 h
methanol	67-56-1	EC50	12,700 mg/l	fish	96 h
methanol	67-56-1	ErC50	22,000 mg/l	algae	96 h

Aquatic toxicity (chronic) of components of the mixture					
Name of substance	CAS No	Endpoint	Value	Species	Exposure time
odorless mineral spirits	64742-48-9	EC50	15 mg/l	microorganisms	40 h
octamethylcyclotetrasiloxane	556-67-2	LC50	10 µg/l	fish	14 d
octamethylcyclotetrasiloxane	556-67-2	EC50	>500 mg/l	aquatic invertebrates	24 h
decamethylcyclopentasiloxane	541-02-6	LC50	>16 µg/l	fish	14 d
decamethylcyclopentasiloxane	541-02-6	EC50	>15 µg/l	aquatic invertebrates	21 d
Propan-2-ol	67-63-0	LC50	>10,000 mg/l	aquatic invertebrates	24 h
stoddard solvent	64742-47-8	EL50	1.2 mg/l	aquatic invertebrates	21 d
stoddard solvent	64742-47-8	EC50	0.33 mg/l	aquatic invertebrates	21 d
Ethyl methylphenylglycidate	77-83-8	EC50	95 mg/l	aquatic invertebrates	24 h

12.2 Persistence and degradability

Data are not available.

12.3 Bioaccumulative potential

The substance fulfills the very bioaccumulative criterion.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

12.4 Mobility in soil

Data are not available.

12.5 Results of PBT and vPvB assessment

The mixture contains a substance that was identified as a PBT (persistent, bioaccumulative and toxic). The mixture contains a substance that was identified as vPvB (very persistent and very bioaccumulative).

12.6 Endocrine disrupting properties

The mixture contains substance(s) with an endocrine disrupting potential.

12.7 Other adverse effects

Data are not available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste treatment-relevant information

Solvent reclamation/regeneration.

Sewage disposal-relevant information

Do not empty into drains. Avoid release to the environment. Refer to special instructions/safety data sheets.

Waste treatment of containers/packages

Only packagings which are approved (e.g. acc. to DOT) may be used. Completely emptied packages can be recycled. Handle contaminated packages in the same way as the substance itself.

Remarks

Please consider the relevant national or regional provisions. Waste shall be separated into the categories that can be handled separately by the local or national waste management facilities.

SECTION 14: Transport information

14.1 UN number

DOT	UN 3082
IMDG-Code	UN 3082
ICAO-TI	UN 3082

14.2 UN proper shipping name

DOT	Environmentally hazardous substance, liquid, n.o.s.
IMDG-Code	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
ICAO-TI	Environmentally hazardous substance, liquid, n.o.s.
Technical name (hazardous ingredients)	decamethylcyclopentasiloxane, odorless mineral spir-its

14.3 Transport hazard class(es)

DOT	9
IMDG-Code	9

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0


Date of compilation: 2021-05-28

ICAO-TI	9
14.4 Packing group	
DOT	III
IMDG-Code	III
ICAO-TI	III
14.5 Environmental hazards	hazardous to the aquatic environment
Environmentally hazardous substance (aquatic environment)	decamethylcyclopentasiloxane, odorless mineral spirits
14.6 Special precautions for user	
There is no additional information.	
14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code	
The cargo is not intended to be carried in bulk.	


Information for each of the UN Model Regulations

Transport of dangerous goods by road or rail (49 CFR US DOT) - Additional information

Not regulated under DOT until packaged in single containers larger than 119 gallons each - liquid, or 882 lbs each - solid.

Particulars in the shipper's declaration	UN3082, Environmentally hazardous substance, liquid, n.o.s., (contains: decamethylcyclopentasiloxane, odorless mineral spirits), 9, III
Reportable quantity (RQ)	4,439,737 lbs (2,015,641 kg) (methanol) (ethylbenzene)
Danger label(s)	9, fish and tree
	
Environmental hazards	yes (hazardous to the aquatic environment)
Special provisions (SP)	8, 146, 173, 335, IB3, T4, TP1, TP29
ERG No	171

International Maritime Dangerous Goods Code (IMDG) - Additional information

Marine pollutant	yes (hazardous to the aquatic environment) (odorless mineral spirits)
Danger label(s)	9, fish and tree
	
Special provisions (SP)	274, 335, 969
Excepted quantities (EQ)	E1
Limited quantities (LQ)	5 L
EmS	F-A, S-F
Stowage category	A

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

International Civil Aviation Organization (ICAO-IATA/DGR) - Additional information

Environmental hazards YES (hazardous to the aquatic environment)

Danger label(s) 9, fish and tree



Special provisions (SP) A97, A158, A197

Excepted quantities (EQ) E1

Limited quantities (LQ) 30 kg

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations specific for the product in question

National regulations (United States)

Toxic Substance Control Act (TSCA) all ingredients are listed

Superfund Amendment and Reauthorization Act (SARA TITLE III)

- The List of Extremely Hazardous Substances and Their Threshold Planning Quantities (EPCRA Section 302, 304)

none of the ingredients are listed

- Specific Toxic Chemical Listings (EPCRA Section 313)

Toxics Release Inventory: Specific Toxic Chemical Listings			
Name of substance	CAS No	Remarks	Effective date
methanol	67-56-1		1986-12-31
Propan-2-ol	67-63-0	only persons who manufacture by the strong acid process are subject, supplier notification not required	1986-12-31

Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA)

- List of Hazardous Substances and Reportable Quantities (CERCLA section 102a) (40 CFR 302.4)

Name of substance	CAS No	Remarks	Statutory code	Final RQ pounds (Kg)
methanol	67-56-1		3 4	5000 (2270)

Legend

3 "3" indicates that the source is section 112 of the Clean Air Act

4 "4" indicates that the source is section 3001 of the Resource Conservation and Recovery Act (RCRA)

Clean Air Act

none of the ingredients are listed

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Right to Know Hazardous Substance List

- Cleaning Product Right to Know Act Substance List (CA-RTK)

Name of substance	CAS No	Functionality	Authoritative Lists
water	7732-18-5	solvent	
distillates (petroleum) hydrotreated, light	64742-47-8	solvents	
odorless mineral spirits	64742-48-9	solvents	Canada PBiTs EC Annex VI CMRs - Cat. 1B
octamethylcyclotetrasiloxane	556-67-2	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
polydimethylsiloxane	63148-62-9	surface modifier	
amino-alkoxy dimethylsiloxane	71750-80-6	surface modifier	
decamethylcyclopentasiloxane	541-02-6	solvents	Canada PBiTs CECBP - Priority Chemicals EC PBTs
Propan-2-ol	67-63-0	alcohols	OEHHA RELs
N,N-bis(2-Hydroxyethyl)oleamide	93-83-4	surfactant	
polytetrafluoroethylene	9002-84-0	polymer	
stoddard solvent	8052-41-3	solvents	ATSDR Neurotoxicants CWA 303(d) EC Annex VI CMRs - Cat. 1B
Dimethyl Siloxane, HO-term Rxn Methyltrimethoxysilane & Aminoethylaminopropyltrimethoxysilane	69430-37-1	surface modifier	
China Clay, calcined	66402-68-4	abrasive	
ethylene glycol monomontanate	73138-45-1	wax	
Propylene glycol	57-55-6	humectant	
Ethyl methylphenylglycidate	77-83-8	fragrance	
alkyl polyether polydimethylsiloxane	212335-52-9	surfactant	
methanol	67-56-1	alcohols	CA TACs NTP OHAT - Repr. or Dev. Toxicants OEHHA RELs Prop 65
2,2'-iminodiethanol	111-42-2	impurity	CA TACs IARC Carcinogens - 2B OEHHA RELs Prop 65
EDTA, anhydrous	64-02-8	chelate / sequestrant	
ethyl butyrate	105-54-4	fragrance	
Isostearyl alcohol	27458-93-1	lubricant	

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Name of substance	CAS No	Functionality	Authoritative Lists
1-Dodecene	112-41-4	solvents	
Propylene oxide polymer with ethylene oxide	9003-11-6	surfactant	
toluene	108-88-3	solvents	ATSDR Neurotoxicants CA MCLs CA TACs CDC 4th National Exposure Report CWA 303(c) CWA 303(d) IRIS Neurotoxicants OEHHA RELs Prop 65

- Toxic or Hazardous Substance List (MA-TURA)

Name of substance	CAS No	DEP CODE	PBT / HHS / LHS	PBT / HHS Threshold	De Minimis Concentration Threshold
methanol	67-56-1				1.0 %
Propan-2-ol	67-63-0				1.0 %

- Hazardous Substances List (MN-ERTK)

Name of substance	CAS No	References	Remarks
stoddard solvent	8052-41-3	A, N, O	
Propan-2-ol	67-63-0	A, N, O	
odorless mineral spirits	64742-48-9	A, O	

Legend

- A American Conference of Governmental Industrial Hygienists (ACGIH), "Threshold Limit Values for Chemical Substances and Physical Agents and Biological Exposure Indices for 1992-93", available from ACGIH
- N National Institute for Occupational Safety and Health (NIOSH), "Recommendations for Occupational Safety and Health Standards," August 1988, available from NIOSH, Publications Dissemination Office, Division of Standards Development and Technology Transfer
- O Occupational Safety and Health Administration (OSHA), Safety and Health Standards, Code of Federal Regulations, title 29, part 1910, subpart Z, "Toxic and Hazardous Substances, 1990." General information: Minnesota Department of Labor and Industry, Occupational Safety and Health Division

- Hazardous Substance List (NJ-RTK)

Name of substance	CAS No	Remarks	Classifications
stoddard solvent	8052-41-3		F2
methanol	67-56-1		TE F3
Propan-2-ol	67-63-0		F3

Legend

- F2 Flammable - Second Degree
- F3 Flammable - Third Degree
- TE Teratogenic

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

- Hazardous Substance List (Chapter 323) (PA-RTK)

Name acc. to inventory	CAS No	Classification
STODDARD SOLVENT	8052-41-3	
METHANOL	67-56-1	E
2-PROPANOL	67-63-0	E

Legend

E Environmental hazard

- Hazardous Substance List (RI-RTK)

Name of substance	CAS No	References
stoddard solvent	8052-41-3	T
methanol	67-56-1	T, F
Propan-2-ol	67-63-0	T, F

Legend

F Flammability (NFPA®)
T Toxicity (ACGIH®)

California Environmental Protection Agency (Cal/EPA): Proposition 65 - Safe Drinking Water and Toxic Enforcement Act of 1987

Proposition 65 List of chemicals					
Name of substance	Name acc. to inventory	CAS No	Wt%	Remarks	Type of the toxicity
toluene	toluene	108-88-3	0.01		developmental
methanol	methanol	67-56-1	0.11		developmental
ethylbenzene	ethylbenzene	100-41-4	0.0066		cancer
2,2'-iminodiethanol	diethanolamine	111-42-2	0.083		cancer
cumene	cumene	98-82-8	0.0066		cancer
Basic Violet 10	D&C Red No. 19	81-88-9	0.0014		cancer

VOC content

- Regulated Volatile Organic Compounds (VOC-EPA) 16 %
- Regulated Volatile Organic Compounds (VOC-Cal ARB) 16 %

Industry or sector specific available guidance(s)

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

NPCA-HMIS® III

Hazardous Materials Identification System. American Coatings Association.

Category	Rating	Description
Chronic	*	chronic (long-term) health effects may result from repeated overexposure
Health	2	temporary or minor injury may occur
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Physical hazard	0	material that is normally stable, even under fire conditions, and will not react with water, polymerize, decompose, condense, or self-react. Non-explosive
Personal protection	-	

NFPA® 704

National Fire Protection Association: Standard System for the Identification of the Hazards of Materials for Emergency Response (United States).

Category	Degree of hazard	Description
Flammability	2	material that must be moderately heated or exposed to relatively high ambient temperatures before ignition can occur
Health	2	material that, under emergency conditions, can cause temporary incapacitation or residual injury
Instability	0	material that is normally stable, even under fire conditions
Special hazard		

National inventories

Country	Inventory	Status
CA	DSL	all ingredients are listed
EU	REACH Reg.	not all ingredients are listed
US	TSCA	all ingredients are listed

Legend

DSL Domestic Substances List (DSL)
REACH Reg. REACH registered substances
TSCA Toxic Substance Control Act

15.2 Chemical Safety Assessment

Chemical safety assessments for substances in this mixture were not carried out.

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

SECTION 16: Other information, including date of preparation or last revision

Abbreviations and acronyms

Abbr.	Descriptions of used abbreviations
29 CFR 1910.1000	29 CFR 1910.1000, Tables Z-1, Z-2, Z-3 - Occupational Safety and Health Standards: Toxic and Hazardous Substances (permissible exposure limits)
49 CFR US DOT	49 CFR U.S. Department of Transportation
ACGIH®	American Conference of Governmental Industrial Hygienists
ACGIH® 2019	From ACGIH®, 2019 TLVs® and BEIs® Book. Copyright 2019. Reprinted with permission. Information on the proper use of the TLVs® and BEIs®: http://www.acgih.org/tlv-bei-guidelines/policies-procedures-presentations/tlv-bei-position-statement
Acute Tox.	Acute toxicity
Asp. Tox.	Aspiration hazard
ATE	Acute Toxicity Estimate
Cal/OSHA PEL	California Division of Occupational Safety and Health (Cal/OSHA): Permissible Exposure Limits (PELs)
Cal ARB	California Air Resources Board
CAS	Chemical Abstracts Service (service that maintains the most comprehensive list of chemical substances)
Ceiling-C	Ceiling value
DEP CODE	Department of Environmental Protection Code
DGR	Dangerous Goods Regulations (see IATA/DGR)
DNEL	Derived No-Effect Level
DOT	Department of Transportation (USA)
EC50	Effective Concentration 50 %. The EC50 corresponds to the concentration of a tested substance causing 50 % changes in response (e.g. on growth) during a specified time interval
EL50	Effective Loading 50 %: the EL50 corresponds to the loading rate required to produce a response in 50% of the test organisms
EmS	Emergency Schedule
EPA	Environmental Protection Agency. An agency of the federal government of the United States charged with protecting human health and the environment
ErC50	≡ EC50: in this method, that concentration of test substance which results in a 50 % reduction in either growth (EbC50) or growth rate (ErC50) relative to the control
ERG No	Emergency Response Guidebook - Number
Eye Dam.	Seriously damaging to the eye
Eye Irrit.	Irritant to the eye
Flam. Liq.	Flammable liquid
GHS	"Globally Harmonized System of Classification and Labelling of Chemicals" developed by the United Nations
HHS	Higher hazard substance

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Abbr.	Descriptions of used abbreviations
IATA	International Air Transport Association
IATA/DGR	Dangerous Goods Regulations (DGR) for the air transport (IATA)
ICAO	International Civil Aviation Organization
ICAO-TI	Technical instructions for the safe transport of dangerous goods by air
IMDG	International Maritime Dangerous Goods Code
IMDG-Code	International Maritime Dangerous Goods Code
LC50	Lethal Concentration 50%: the LC50 corresponds to the concentration of a tested substance causing 50 % lethality during a specified time interval
LHS	Lower hazard substance
LL50	Lethal Loading 50 %: the LL50 corresponds to the loading rate causing 50 % lethality
MARPOL	International Convention for the Prevention of Pollution from Ships (abbr. of "Marine Pollutant")
NFPA®	National Fire Protection Association (United States)
NIOSH REL	National Institute for Occupational Safety and Health (NIOSH): Recommended Exposure Limits (RELs)
NPCA-HMIS® III	National Paint and Coatings Association: Hazardous Materials Identification System - HMIS® III, Third Edition
OSHA	Occupational Safety and Health Administration (United States)
PBT	Persistent, Bioaccumulative and Toxic
PEL	Permissible exposure limit
PNEC	Predicted No-Effect Concentration
ppm	Parts per million
Repr.	Reproductive toxicity
RTECS	Registry of Toxic Effects of Chemical Substances (database of NIOSH with toxicological information)
Skin Corr.	Corrosive to skin
Skin Irrit.	Irritant to skin
Skin Sens.	Skin sensitization
STEL	Short-term exposure limit
STOT RE	Specific target organ toxicity - repeated exposure
STOT SE	Specific target organ toxicity - single exposure
TLV®	Threshold Limit Values
TWA	Time-weighted average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and very Bioaccumulative

Safety Data Sheet

acc. to 29 CFR 1910.1200 App D



Paint Sealant

Version number: GHS 1.0

Date of compilation: 2021-05-28

Key literature references and sources for data

OSHA Hazard Communication Standard (HCS), 29 CFR 1910.1200.

Transport of dangerous goods by road or rail (49 CFR US DOT). International Maritime Dangerous Goods Code (IMDG). Dangerous Goods Regulations (DGR) for the air transport (IATA).

Classification procedure

Physical and chemical properties: The classification is based on tested mixture.

Health hazards, Environmental hazards: The method for classification of the mixture is based on ingredients of the mixture (additivity formula).

List of relevant phrases (code and full text as stated in chapter 2 and 3)

Code	Text
H225	Highly flammable liquid and vapor.
H226	Flammable liquid and vapor.
H227	Combustible liquid.
H301	Toxic if swallowed.
H304	May be fatal if swallowed and enters airways.
H311	Toxic in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H336	May cause drowsiness or dizziness.
H361f	Suspected of damaging fertility.
H370	Causes damage to organs.
H372	Causes damage to organs through prolonged or repeated exposure.

Disclaimer

This information is based upon the present state of our knowledge. This SDS has been compiled and is solely intended for this product.