

Carpetshield FR



Non-slip, flame retardant carpet protection for use during final construction stages to protect carpets and stairs.

Features & Benefits

- ◆ Reverse wound, enabling quick and easy installation
- ◆ Lightweight for ease of handling around site
- ◆ Requires no taping, saving time
- ◆ Low tack adhesive to avoid any residue being left behind after removal

Applications

- ◆ Designed to protect synthetic carpets only and for up to a maximum of 4 weeks
- ◆ Not suitable for rugs, loose fitting carpet tiles or worn carpets
- ◆ Not suitable for use on surfaces with under floor heating

Product Specification

Material	Embossed Flame Retardant LPDE Film
Colour	White with markings
Thickness	80 micron
Weight Per Roll	600mm x 100m - 4kg 800mm x 100m - 5.5kg 900mm x 100m - 6kg 1200mm x 100m - 7kg

Range

Available sizes and product codes:

Size	Code
600mm x 100m	CARPETSHIELD600
800mm x 100m	CARPETSHIELD800
900mm x 100m	CARPETSHIELD900
1200mm x 100m	CARPETSHIELD1200

Certification



Flame Retardant - Certifire – Approved to TS63 - Certificate No. CF 5088.

Installation Instructions/Guidelines

- ◆ Refer to full guidelines issued with the product prior to installation and check suitability
- ◆ Clear all debris from the carpet prior to installation
- ◆ Simply roll out the reverse wound product
- ◆ Apply pressure to the film on to the carpet to activate the adhesive
- ◆ Where carpet has been installed using a glue or adhesive, do not install for at least 72 hours so that the adhesive vapours can dissipate before application.
- ◆ Do not apply to damp carpet or in areas that may be subject to moisture accumulation
- ◆ Excessive traffic and exposure to direct sunlight or intense heat may accelerate adhesive transfer

Handling & Storage

Store and install in ambient conditions. The rolls should be stored at room temperature 24 hours prior to installation.

We've got you covered.

Freephone 0800 834 704

Mobile friendly +44 1625 855600

enquiries@protection.co.uk

www.protection.co.uk



Product Disclaimer

The information provided in all product, safety and technical data sheets is to the best of our knowledge correct but not all-inclusive and without warranty and is to be used solely as a guide. Similarly, all technical advice, whether verbal, in writing, or as a result of sample trials, is for guidance and is given in good faith but without warranty, since site conditions, care and skill of application are beyond our control. Protec International Ltd can accept no liability for the performance of our products, or any damage resulting from handling or contact beyond the value of the material supplied. This does not affect your statutory rights.

Every effort to ensure the accuracy of the images of our products has been made, however the accuracy of the colours may differ and vary according to your computer monitor.

Please contact our Customer Services Department on 0800 834 704 for further information.

DOC REF: [CarpetShieldFR/P-28.07.2020](#)