


Multi Acoustic Roll

Typical applications: Internal walls & floors and drylining systems



Description

Superglass Multi Acoustic Roll is a lightweight, non-combustible glass mineral wool insulation roll. The flexible roll is perforated at 2x600mm and 3x400mm widths to allow easy installation between common stud/joist spacings and minimum on-site cutting and waste. Manufactured at a minimum density of 10kg/m³.

Application

Superglass Multi Acoustic Roll is designed to provide thermal and acoustic insulation for the following applications:

- Internal walls and floors
- Separating walls and floors
- Timber and metal stud partitions
- Drylining system



BRE Green Guide Rating

Multi Acoustic Roll has a generic BRE Green Guide Rating of A+.



Fire Performance

Multi Acoustic Roll has a fire classification of A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.



Acoustic Insulation

Multi Acoustic Roll provides excellent sound absorption performance.



Recycled Content

Multi Acoustic Roll is manufactured from up to 84% recycled glass.



Easy & Quick To Install

Friction fits between studs and joists.



Multi Acoustic Roll | Characteristics

Product dimensions and information					
Thickness (mm)	Length (m)	Width (mm)	Pack Area (m ²)	Packs per pallet	Code
60	11.25	1200/2x600/3x400	13.50	24	5510
75	8.50	1200/2x600/3x400	10.20	24	5514*
80	10.40	1200/2x600/3x400	12.48	24	5511
100	10.10	1200/2x600/3x400	12.12	24	5504

*Non-Standard Products

Density

Multi Acoustic Roll is manufactured at a minimum density of 10kg/m³.

Fire Performance

All Superglass products are deemed non-combustible and have a fire classification of A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.

Environment

- Manufactured in accordance with ISO 14001:2015 - Environmental Management Systems (EMS).
- Zero Ozone Depletion Potential (ODP) & zero Global Warming Potential (GWP).
- Generic BRE Green Guide Rating of A+.

Recycled Content

All Superglass products are manufactured from up to 84% recycled glass which would otherwise go to landfill.

Standards

Manufactured in accordance with:

- BS EN 13162:2012(+A1:2015) Thermal insulation products for buildings - Factory made mineral wool (MW) products
- BS EN 13172: 2012 Thermal insulation products - Evaluation of conformity.

Quality

All Superglass products are manufactured in accordance with BS EN ISO 9001:2015 - Quality Management Systems (QMS).

Durability

All Superglass products are non-hygroscopic, will not rot, degrade or sustain vermin and will not encourage the growth of mould, bacteria or fungi.

Vapour Resistance

All Superglass products offer negligible vapour resistance allowing vapour to pass freely through the insulation.

Handling & Storage

All Superglass products are easy to handle, cut and install. The products are supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors or under a waterproof covering in order to protect from weather damage. The products should not be left permanently exposed to the elements.

Certification

- CE Marked to BS EN 13162:2012(+A1:2015).
- Designation Code = MW-13162-T1.
- A copy of the Multi Acoustic Roll Declaration of Performance (DoP) ref: DOP0009 can be downloaded from the Superglass website.

Associated Products

Acoustic Partition Roll (APR)

Building Information Modelling (BIM)

BIM objects for this product can be downloaded from www.bimstore.co.uk or www.superglass.co.uk



Superglass Insulation Limited. Thistle Industrial Estate, Kerse Road, Stirling, Scotland FK7 7QQ

Technical

Hotline: **0808 1645 134**

Email: technical@superglass.co.uk

Sales

Tel: **01786 451170**

Email: sales@superglass.co.uk

Social

www.facebook.com/TNintl/

www.twitter.com/TNintl

www.linkedin.com/company/tninternational/

All rights are reserved, including those of photomechanical reproduction and storage in electronic media. Commercial use of the processes and work activities presented in this document is not permitted. Extreme caution was observed when putting together the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of errors pointed out.

