

SAFETY DATA SHEET

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifiers

Product Name: Artisan Acrylic Nail Powder - Premium White

Recommended Use of the substance or mixture and Restrictions on Use

Industrial and professional cosmetic use

Details of the Distributor of the Safety Data Sheet

Distributor Address

The Nail Superstore
3804 Carnation St
Franklin Park, IL 60131
USA
Website: www.nailsuperstore.com

Emergency Telephone Numbers

Company Phone Number: 1(847)260-4000 (Mon-Fri 9:00 am - 5:30 pm CST)
Emergency 24-Hr. Telephone: INFOTRAC: 1(800)535-5053 (Outside U.S: 1(352)323-3500)

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Hazard Class - *Physical, Health, Environmental*

Eye Damage/Irritation

Skin sensitizer

Category

2A

1

OSHA Defined Hazards

Combustible dust, may form combustible dust concentrations in air, explosion hazard

Label Elements - Pictograms, Signal Word, Hazard Statements, Precautionary Statements, & Supplemental Information



Signal Word

Warning

Hazards Statements

H317 May cause an allergic skin reaction

H319 Causes serious eye irritation

Precautionary Statements - Prevention, Response, & Disposal

P210 Keep away from heat/sparks/open flames/hot surfaces

– No smoking

P235 Keep cool

P240 Ground and bond container and receiving equipment

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P264 Wash hands and exposed skin thoroughly after handling

P272 Contaminated work clothing should not be allowed out of the workplace

P280	Wear protective gloves/protective clothing/eye protection/face protection
P321	Specific treatment (see ... on this label)
P363	Wash contaminated clothing before reuse
P302+P352	IF ON SKIN: Wash with soap and water
P305+P351 +P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P333+P313	If skin irritation or a rash occurs: Get medical advice/attention
P337+P313	Get medical advice/attention
P370+P378	In case of fire: Use CO2 for extinction
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container to an authorized disposal facility

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Cas No.	Weight-%	GHS Ratings
2-Propenoic acid, 2-methyl-, ethyl ester, homopolymer	9003-42-3	40 — 50	Eye Damage/Irritation 2B (H320)
2-Propenoic acid, 2-methyl-, ethyl ester, polymer with methyl 2-methyl-2-propenoate	25685-29-4	40 — 50	Eye Damage/Irritation 2B (H320)
Benzoyl Peroxide	94-36-0	1 — 5	Eye Damage/Irritation 2A (H319) Skin Sensitizer 1 (H317)
Titanium Dioxide (CI 77891)	13463-67-7	1 — 5	

4. FIRST AID MEASURES

General Advice

Provide the SDS to medical personnel for treatment.

Inhalation:

Remove victim to fresh air. Seek immediate medical attention.

Eye Contact:

If product gets in the eyes, flush with lukewarm water for at least 15 minutes. If irritation occurs, contact a physician.

Skin Contact:

Rinse thoroughly with lukewarm water, followed by a thorough washing of the affected area with soap and water. If irritation, redness or swelling persists, contact a physician immediately.

Clothing:

Remove contaminated clothing, wash thoroughly before reuse.

Ingestion:

If ingested, do not induce vomiting. If product has been swallowed, drink plenty of water or milk IMMEDIATELY. If the patient is vomiting, continue to offer water or milk. Never give anything by mouth to an unconscious person. Provide an estimate of the time at which the material was ingested and the amount of the substance that was swallowed. Get medical attention immediately.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Water, Chemical (alcohol-resistant) foam, dry chemical, or carbon dioxide.

Unsuitable Extinguishing Media

Water may not be effective in extinguishing this fire.

Specific Hazards Arising from the Chemical

Polymers are combustible dusts, care should be taken to avoid creating explosive concentrations in the air. Follow grounding and bonding procedures.

Special Fire Fighting Procedures:

Avoid extinguishing methods, which may generate dust clouds. Water stream can disperse dust into air producing a fire hazard and possible explosion hazard if exposed to ignition source. Firefighters should wear self-contained breathing apparatus.

Protective Equipment and Precautions for Firefighters

Polymer dust is combustible. The explosive limits of the polymer particles suspended in air are approximately those of coal dust. Polymers are sensitive to static discharge, follow grounding and bonding procedures. Polymers are not sensitive to mechanical impacts.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

Personal Precautions

Before cleaning any spill or leak, individuals must wear appropriate Personal Protective Equipment that is specified in section 8. Keep airborne particulates at a minimum when cleaning up spills. Deny entry to all unprotected individuals. Remove any contaminated clothing and wash thoroughly before reuse.

Environmental Precautions

Extinguish all ignition sources. Keep spills and cleaning runoffs out of municipal sewers and open bodies of water. US Regulations (CERCLA) require reporting spills and releases to soil, water and air in excess of reportable quantities. The toll free number for the US Coast Guard National Response Center is (800) 424-8802.

Methods and Material for Containment and Cleaning Up

Methods for Containment

Prevent further leakage or spillage if safe to do so. Dike and contain spill with inert material (e.g. sand or earth). May contaminate water supply.

Methods for Cleaning Up

Maximize ventilation (open doors and windows) and secure all sources of ignition. Use good, local ventilation with a minimum capture velocity of 100 ft/min (30 m/min) at point of product release. Place into appropriate closed container(s) for disposal in accordance with local, state and federal regulations. Wash all affected areas with plenty of warm water and soap. Not a RCRA Hazardous waste.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Advice on Safe Handling

Use in well ventilated areas. Avoid contact with skin, eyes and clothing. Avoid breathing dust. Use good personal hygiene and

housekeeping. Avoid prolonged contact with the product. Use in a well-ventilated location (e.g., local exhaust ventilation, fans). After use, wash hands and exposed skin with soap and water. Do not eat, drink or smoke while handling product.

Conditions for Safe Storage, Including any Incompatibilities

Storage Conditions

Store containers in a cool, dry location, away from direct sunlight, heat, sparks, flame, other light sources, or sources of intense heat. The temperature should remain at or under 72°F (22°C) at all times. Storing above recommended temperature will cause product performance issues. Store in accordance with National Fire Protection Association recommendations. Observe all label precautions until the container is cleaned, reconditioned, or destroyed.

Incompatible Materials

Strong oxidizers, strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
2-Propenoic acid, 2-methyl-, ethyl ester, homopolymer 9003-42-3			
2-Propenoic acid, 2-methyl-, ethyl ester, polymer with methyl 2-methyl-2-propenoate 25685-29-4			
Benzoyl Peroxide 94-36-0	5 mg/m3 TWA	5 mg/m3 TWA	NIOSH: 5 mg/m3 TWA
Titanium Dioxide (CI 77891) 13463-67-7	15 mg/m3 TWA (total dust)	10 mg/m3 TWA	

Engineering Controls

Use local explosion-proof ventilation that is adequate to keep employee exposure to airborne concentrations below exposure limits. Please refer to the ACGIH document, Industrial Ventilation, A Manual of Recommended Practices, most recent edition, for details.

Personnel Protective Equipment (PPE)

Respiratory Protection

A respirator should be worn whenever workplace conditions warrant use of a respirator. If dust conditions are present, a N95 respirator dust mask is required. None required if airborne concentrations are maintained below any exposure limit that may be listed above. If necessary, use only respiratory protection authorized per U.S. OSHA's requirement in 29 CFR §1910.134 or other appropriate governing standard.

Eye/Face Protection

Wear safety glasses, chemical goggles when splashing is possible, when dealing with this material. If necessary, refer to U.S. OSHA 29 CFR §1910.133, or other appropriate governing standard. Ensure that an eyewash station, sink or washbasin is available in case of exposure to eyes.

Skin and Body Protection

Complete suit protecting against chemicals, the type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact:

Material: Nitrile rubber

Minimum layer thickness: 0.4 mm

Splash contact:

Material: Nitrile rubber

Minimum layer thickness: 0.11 mm

Break through time: 480 min

Break through time: 120 min

General Hygiene Considerations

Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly after handling. An eyewash station and a safety shower are recommended. Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Wash hands thoroughly before eating, drinking, or smoking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White Odor: Faint Flammable Limit (Air Volume%, 0% Lower/Upper) Boiling Range (low - high) 2500°C	Physical State: Powder Flash Point: 576 F,302 C Evaporation Rate No data available Specific Gravity 2.07
--	---

10. STABILITY AND REACTIVITY

Material stability

Stable

Incompatible materials

Strong oxidizers

Hazardous decomposition products

Methacrylate Monomer and Oxides of Carbon when burned

Possibility of hazardous reactions

Hazardous polymerization will not occur.

11. TOXICOLOGICAL INFORMATION

Mixture Toxicity

Component Toxicity

Routes of Exposure

Inhalation Eye Contact Ingestion

Target Organs

Eyes Lungs Skin Respiratory System

Effects of Overexposure

Inhalation	Overexposure by inhalation of titanium dioxide may include mild and temporary upper respiratory irritation with cough and shortness of breath.
Skin Contact	No data found.
Eye Contact	No data found.
Ingestion	No data found.

Product Components Listed as Carcinogenic

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
13463-67-7	Titanium Dioxide (CI 77891)	1 to 5%	Titanium Dioxide (CI 77891): NIOSH: <u>potential occupational carcinogen</u> IARC: <u>Possible human carcinogen</u> OSHA: <u>listed</u>

12. ECOLOGICAL INFORMATION**Component Ecotoxicity****13. DISPOSAL CONSIDERATIONS****Waste Treatment Methods****Disposal of Wastes**

Dispose waste material in accordance with Federal, State, and Local regulations. It is the responsibility of the generator to determine at the time of disposal whether the product meets the criteria of a hazardous waste. Comply with all applicable federal, state and local regulations. Waste disposal options include landfilling solids at permitted sites. Incinerate in a chemical incinerator equipped with an afterburner and scrubber. Use registered transporters.

Contaminated Packaging

Reuse of empty drums or containers is not recommended. Employees should be advised of the potential hazards, due to residual flammable material, associated with empty containers. Dispose of all empty containers properly, in accordance with Federal, State and Local regulations

14. TRANSPORT INFORMATION

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Not Regulated, Polymer, NOS			
IATA	Not Regulated, Polymer, NOS			
IMDG	Not Regulated, Polymer, NOS			

15. REGULATORY INFORMATION**State of California Safe Drinking Water and Toxic Enforcement Act of 1986**

(Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

13463-67-7 Titanium Dioxide (CI 77891) 1 to 5 % Carcinogen

SARA 313

Benzoyl Peroxide 94-36-0

US State Right-to-Know Regulations

- None

<u>Country</u>	<u>Regulation</u>	<u>All Components Listed</u>
	EINECS	Yes
	SARA Hazard categories	No
	TSCA Inventory	Yes


16. OTHER INFORMATION

Hazardous Material Information System (HMIS)

National Fire Protection Association (NFPA)

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0
PERSONAL PROTECTION	B

HMIS & NFPA Hazard Rating Legend
* = Chronic Health Hazard
0 = INSIGNIFICANT
1 = SLIGHT
2 = MODERATE
3 = HIGH



The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not considered a warranty or quality specification. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials on in any process, unless specified in the text.