•

Material Safety Data Sheet

Common Name	Artisan FlexWrap Base Resin	Code 1731-09-99		
D: . : !	— The Nail Superstore	MSDS# 3-TB-20-0198		
The Nail Superstore 3804 Carnation St, Franklin Park, IL 60131		Validation Date 12/3/2001		
Synonym	Not available.	Print Date 12/3/2001		
Trade name	TB1785 Thick	Responsible Name Company		
Material Uses	Industrial applications: Cyanoacrylate adhesive	In Case of Monday-Friday, 830 Emergency 513-779-7300 ES		

Section 2. Composition, Information on Ingredients			
Name	CAS#	% by Weight	Exposure Limits
1) Ethyl 2-cyanoacrylate	7085-85-0	90-95	TWA: 0.2 (ppm) from ACGIH (TLV) TWA: 1 (mg/m³) from ACGIH (TLV)

Section 3, Hazard	s Identification
Physical State and Appearance	Liquid. (Transparent Liquid.)
Emergency Overview	EMERGENCY OVERVIEW Combustible liquid. Rapid polymerization occurs upon contact with water or alkaline sustances. Skin inflamation or burns may occur upon contact during this polymerization. Will bond skin. May cause mucous membrane and respiratory tract damage. Use with adequate ventilation. Wear suitable protective clothing and gloves. Store and use away from heat, sparks, open flame, or any
Routes of Entry	other Ignition source (See section 8). Inhalation.
	yes Slightly hazardous in case of eye contact (irritant). kin Bonds skin instantly.
	ion Concentrated vapors are hazardous if inhaled.
Ingest	ion No known hazard
Potential Chronic Health Effects	Repeated use may result in irritation of mucous membrane and upper respiratory tract.
Medical Conditions Aggravated by Overexposure:	Repeated or prolonged exposure is not known to aggravate any medical conditions.
Overexposure /Signs/Symptoms See Toxicological Informati	Side effects are asthma, bronchitis & other chronic lung conditions/upper respiratory tract irritant. on (section 11)

Continued on Next Page



	Page: 2/6
Section 4. First A	Aid Measures
Eye Contact	IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Do not attempt to pull apart bonded eyelid. Seek medical attention.
Skin Contact	After contact with skin, wash immediately with plenty of water. Gently and thoroughly wash the contaminated skin with running water and soap. Seek medical attention to remove cured material. Wash contaminated clothing before reusing.
Inhalation	If symptoms of prolonged exposure to concentrated material vapors appear, remove to fresh air. If breathing is difficult, loosen any restrictive clothing and provide oxygen and get medical care if necessary.
Ingestion	Do not induce vomiting. Saliva will cause cyanoacrylate to polymerize in the mouth. If lips are bonded together, use warm water to gently separate the lips apart
Notes to Physician	Cured adhesive does not pose a health risk

Section 5. Fire Fight	ing Measures
Flammability of the Product	Combustible.
Auto-Ignition Temperature	>200°C (392°F)
Flash Points	The lowest known value is CLOSED CUP: 79°C (174.2°F). (Ethyl 2-cyanoacrylate)
Flammable Limits	Not available.
Products of Combustion	Not available.
Fire Hazards in Presence of Various Substances	Not available.
Explosion Hazards in Presence of Various Substances	None known
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemical powder. LARGE FIRE: Use water spray, fog or foam. Do not use water jet.
Protective Clothing (Fire)	Vapor respirator or a self contained breathing apparatus.
Special Remarks on Fire Hazards	No additional remark.
Special Remarks on Explosion Hazards	No additional remark.

Small Spill and Leak	Absorb with an inert material and put the spilled material in an appropriate waste disposal.
Large Spill and Leak	Combustible material. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Finish cleaning by spreading water on the contaminated surface and allow to evacuate through the sanitary system. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Continued on Next Page



Section 7, Ha	ndling and Storage
Handling	To avoid fire, minimize ignition sources. Avoid contact with skin and eyes. In case of insufficient ventilation, wear suitable respiratory equipment. May react in presence of moisture. May react or be incompatible with alkalies.
Storage	Contains moisture sensitive material; store in a dry place. Keep away from sources of ignition. Keep container tightly closed and dry. Keep in a cool, well-ventilated place.

Page: 3/6

Engineering Controls	Good general ventilation should be sufficient to control airborne levels in small quantity use. Local exhaus is recommended for bulk repackaging or continous large quantity use.
Personal Protection Eyes	Safety glasses.
Body	Synthetic apron.
Respiratory	Wear appropriate respirator when ventilation is inadequate.
Hands	Gloves (impervious).
Feet	Wear chemical resistant shoes



Personal Protection in Case of a Large Spill

A self contained breathing apparatus should be used to avoid inhalation of the product. Boots. Full suit. Gloves. Safety glasses.

Product Name

Exposure Limits

1) 2-Propenoic acid, 2-cyano-, ethyl ester

TWA: 0.2 (ppm) from ACGIH (TLV) TWA: 1 (mg/m³) from ACGIH (TLV)

Consult local authorities for acceptable exposure limits.

Physical State and Appearance	Liquid. (Transparent Liquid.)	Odor	Acrid.
Molecular Weight	Mixture.	Taste	Not available.
Molecular Formula	Mixture.	Color	Transparent.
pH (1% Soln/Water)	Not applicable.		
Boiling/Condensation Point	The lowest known value is >190°C (374°F) (Ethyl 2-cyanoacrylate).		
Melting/Freezing Point	Not available.		
Critical Temperature	Not available.		
Specific Gravity	1.05 (Water = 1)		
Vapor Pressure	0.0075 mm of Hg (@ 20°C)		
Vapor Density	The highest known value is >1 (Air = 1) (Ethyl 2-cyanoacrylate).		
Volatility	Not available.		



TB1785		Page: 4/6
Odor Threshold	Not available.	
Evaporation Rate	Not available.	
voc	Not available.	
Viscosity	Kinetic: 85 cP	
LogKow	Not available.	
Ionicity (in Water)	Not applicable.	
Dispersion Properties	Not available.	
Solubility	Insoluble in cold water.	
Physical Chemical Comm	ents Insoluble in water	

Stability and Reactivity	The product is stable but it is water reactive.
Conditions of Instability	Rapid polymerization occurs upon contact with water or alkaline sustances. As a result, heat is generated Skin inflamation or burns may occur upon contact during this polymerization.
Incompatibility with Various Substances	Reactive with alkalis, moisture, peroxides.
Hazardous Decomposition Products	Not available.
Hazardous Polymerization	Yes due to heat generated during polymerization.

Toxicity to Animals	LD50: Not available.
Chronic Effects on Humans	The substance is toxic to mucous membranes, upper respiratory tract.
Other Toxic Effects on Humans	Slightly hazardous in case of skin contact (irritant). Concentrated vapors are hazardous in inhaled.
Special Remarks on Toxicity to Animals	Not available.
Special Remarks on Chronic Effects on Humans	Continous high volume usage without adequate ventillation can irritate eyes and nose.
Special Remarks on Other Toxic Effects on Humans	Vapors are irritating to mucous membrane and upper respirator tract. Under normal conditions of use of this product, no respiratory protection is required. Aproved breathing apparatus is required if large spill occurs.

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Biodegradable/OECD	Not available.
Mobility	Not available.
Products of Degradation	Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.



		Page: 5/6
Toxicity of the Products of Biodegradation	Not available.	1 4
Special Remarks on the Products of Biodegradation	Not available.	Lucius de la companya

Section 13. Disposal Considerations Waste Information Cured products may be landfilled. Uncured product must be handled according to local regulations. Waste Stream Consult your local authority. Consult your local hazardous waste management for advice. Consult your local or regional authorities.

Section 14. Transport Information		
DOT Classification	Combustible.	
	Label not required for shipments less than 450 liter or 119 gallons. Con	mbustible Liquid, n.o.s. , 3, NA1993, I
Marine Pollutant	Not available.	
Special Provisions for Transport	Quantity of 450 liters (119 gallons) or less are not regulated; the Combustible liquid,n.o.s., 3, NA1993, III. Quantity limitations: Passenger aircraft or railcar: 60 L. Cargo aircraft only: 220 L.	following apply to larger quantities:
ADR/RID Classification	Not controlled under ADR (Europe).	
IMO/IMDG Classification	Not controlled under IMDG.	
ICAO/IATA Classification	Not controlled under IATA.	

ICS Classification	Class: Combustible liquid having a flash point between 37.8°C (100°F) and 93.3°C (200°F).
U.S. Federal Regulations	All ingredients are in compliance with TSCA.
	SARA 302/304/311/312 extremely hazardous substances: No products were found.
	SARA 302/304 emergency planning and notification: No products were found.
	SARA 302/304/311/312 hazardous chemicals: No products were found. SARA 311/312 MSDS distribution - chemical inventory - hazard identification: No products were found.
	SARA 313 toxic chemical notification and release reporting: No products were found.
	Clean water act (CWA) 307: No products were found.
	Clean water act (CWA) 311: No products were found.
	Clean air act (CAA) 112 accidental release prevention: No products were found.
	Clean air act (CAA) 112 regulated flammable substances: No products were found.
	Clean air act (CAA) 112 regulated toxic substances: No products were found.
International Regulations	
EINECS	Not available.
DSCL (EEC)	This product is not classified according to the EU regulations.
International Lists	No products were found.
State Regulations	No products were found.
	California prop. 65: No products were found.



Section 16. Other Information Combustible liquid. Label Requirements Rapid polymerization occurs upon contact with water or alkaline sustances. Skin inflamation or burns may occur upon contact during this polymerization. Will bond skin. May cause mucous membrane and respiratory tract damage. Use with adequate ventilation. **Hazardous Material National Fire** Health Fire Hazard **Information System** Protection Fire Hazard Health 2 (U.S.A.) Association (U.S.A.) Reactivity 2 Reactivity Specific Hazard Personal Protection C - - Manufacturer's Material Safety Data Sheet. References Other Special Skin, lips, eyelids or other body part bonded by cyanoacrylate are best separated by passive nonsurgical first aid. Considerations Generaly warm water and gentle manipulation will break the cyanoacrylate bond.

Monday-Friday, 830-500pm, 513-779-7300 EST. OR 800-424-9300 - 24 hours

Validated by Company on 12/3/2001.

The data contained herein is based upon information that The Nail Superstore believes to be reliable. Users of this product have the responsibility to determine the suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and involved in said use. All statements or suggestions are made without warranty, express or implied, regarding accuracy of the information, the hazards connected with the use of the material or results to be obtained form the use thereof.

Verified by Company.

Printed 12/3/2001.





Page: 6/6