

basecoat

BaseCoat, available in a single component or Ready to Use versions, is a Polymeric Cementitious System suitable for leveling irregular or damaged surfaces, cover tiles, and preparing the surface adding extra strength to MicroCement finishing coats. It may also be used as a finish product thanks to its refined aesthetic textured design. It can be applied on both horizontal and vertical surfaces, accessories, interior or exterior, on both new substrates and over existing coatings such as tile.

The better you prepare the **decco Basecoat**, the easier it will be to achieve the desired MicroCement finish. Make sure that the Basecoat has fully covered the tiles and/or the fiberglass mesh in case of use. Do not skip sanding in between each coat of Basecoat and Finishing Coats (MicroTop One/Industrial).

Mixing Process:

1. Approximately 6-8 quarts of water in 5 gallon mixing pail.
2. Put in one pail of decco Basecoat powder
3. Mix with paddle mixer until lump free
4. Let "False Set" for 5 minutes
5. Remix, adding small amount of water if needed

Application:

1. Clean Floor with Floor Machine and Cleaning and fill any crack with Crack Repair Material and let dry.
2. Roll decco Primer - diluted 1:1 with water on the surface and let dry. Alternatively use decco Flex Membrane over tiled floors.
3. Apply decco Basecoat on dry primer. If necessary, mist water on dry primer to give more working time. Use the Black Series Stainless Steel Trowl at a 45-degree angle and/or Magic trowel for smooth finish coat.
4. Repeat Step 1, 2 & 3 for finish coat (2nd coat is mandatory in order to achieve the final look)
5. Completely sweep and vacuum up dust if Sanding was done
6. Seal using our proprietary sealers: Ultra Seal, Eco Seal and/or Epoxy Seal

Clean Up:

Clean skin with soap and water. Tools and equipment should be cleaned with Xylene or Lacquer thinner. Consult MSDS for safety and health precautions.

Maintenance:

After completing the installation, the applicator should provide the owner with maintenance instructions. If floors become slippery due to animal fats, oil, grease, or soap film, clean and rinse thoroughly. Properly sealed Beasecoat is easily cleaned with neutral soaps or detergents. Routine mechanical scrubbing is recommended for all surfaces having a non-skid texture. Treating the surface with a floor finish (Decco WAX) is optional. Long periods of heavy traffic may cause wear patterns necessitating application of a finish coat.

Coverage: 300 to 350 Sq Ft (30 to 35 sq mt) per pail per coat

Presentation: 45 lbs **Shelf Life:** 12 months

Warranty:

decco Basecoat, a proprietary product, is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product. If you have any questions, please contact Bluetrade Building Materials, Inc.

**decco Europe**

Poligono Industrial "El Pla"
Nave 19 Valencia, ES 46290

decco USA

243 Grandview Avenue
Staten Island, NY 10303

decco Latam

8411 NW 74th Street,
Medley, FL 33166

www.heydecco.com
Follow us! @heydecco