

microwall

MicroWall is a decorative microcement plaster that allows to reproduce the tactile like lived concrete and naturally aged, also tracing the details to characterize modern environments that evoke metropolitan atmosphere.

MicroWall is suitable for application to interior walls, columns and ceilings

Product Benefits

- Extreme Pot Life (Materials remains active and workable for over 48 hs if left in the mixing container)
- Extended Open Time with Superior Hand and Workability (Materials exhibits incredible workability and creaminess in excess of 10 minutes during trowel application)
- Great Flexibility (Our products don't crack under certain conditions)
- Eco-Friendly (we only use WB Components)
- Same Day Return to Service in mostly cases
- Extreme bonding on any kind of surface, included Tile ("Remodel without Removal")
- Natural Look. Stylish & Natural Look in all our finishes.
- Solid Integral colors. Twenty colors available.

Mixing Process:

1. Add 1 bottle of decco Color Toner (INTEGRAL COLOR) into water in order to get approximately 8 - 10 quarts of liquid in 5-gallon mixing pail.
2. Put in one pail of decco microwall powder.
3. Mix with paddle mixer until lump free.
4. Let "false set" for 5 minutes.
5. Remix, adding small amount of water if needed.

Application:

1. Roll decco Primer – diluted 1:1 with water on the surface and let dry.
2. Apply decco microwall on dry primer. If necessary, mist water on dry primer to give more working time. Use the Black Series Stainless Steel Trowel at a 45-degree angle and/or Magic trowel for smooth finish coat. It is important to trowel thin but not heavy pressure that could create heavy black burnish marks unless this is requested by customer.
3. Let dry and sand the cured Finish coat with 320 grit Sanding screens for smoother finish.
4. Repeat Step 1, 2 & 3 for finish coat (2nd coat is mandatory in order to achieve the final look).

12 hours depending on material thickness, temperature, substrate conditions and humidity.

5. Once the material has dried and the color has stabilized, a second thin coat can be applied. Each additional coat will help darken the color.
6. For maximum color development, once the surface is completely dry, sand with 220 grit sanding screen and lightly spray a solution of 50% white vinegar and 50% water across the surface.
7. It is not recommended to seal OxyTop.

Clean Up:

Clean skin with soap and water. Tools and equipment should be cleaned with Xylene or Lacquer thinner. Consult MSDS for safety and health precautions.

Coverage:

200 sq.ft. per pail per coat

Presentation: 20 lbs

Shelf Life: 6 months

Warranty:

decco MicroWall, a proprietary product, is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product. If you have any questions, please contact Bluetrade Building Materials, Inc.



decco - Miami
8217-19 NW 66th Street
Miami, FL 33166
Tel: +1 (786) 282-4097
info@heydecco.com

decco - New York
243 Grandview Ave
Staten Island, NY 10303
Tel: +1 (347) 801-2855
sales@dfstudio.nyc

www.heydecco.com
Follow us! @heydecco