

oxytop

Two-component Iron based coating, designed following the latest trends in architecture and interior design, giving a rusty and corroded metal finish, with bits of silver shining through bumpy coarse texture.

Application Environments

- Facades
- Interior Walls
- Interior Columns
- Plant Pots
- Furniture
- Decorative Elements

Mixing Process:

1. OxyTop is packaged in pre-measured kits for easy transport and mixing.

2. In a clean and dry pail, mix the entire contents of Part A and Part B with a mixing blade and drill. Mix until a creamy lump free consistency is achieved.

3. For thinner consistency, the system can be diluted 10% with water. (2 lb. or 3.75 cups per 20 lb kit).

4. The mix ratio for OxyTop is 1 Part A Resin to 3 Parts B Powder.

5. Pot life is approximately 2 hours. Longer pot life can be achieved in a closed container.

Application:

1. OxyTop is best applied with a trowel. Trowel size and shape will vary based on the project scope and size.

2. Apply material in thin coats. Do not overwork.

3. Natural variations in finish are expected and will help create a more natural "patina" effect.

4. Once applied, OxyTop will begin to react and change color. This process can take from 2 to

12 hours depending on material thickness, temperature, substrate conditions and humidity.

5. Once the material has dried and the color has stabilized, a second thin coat can be applied. Each additional coat will help darken the color.

6. For maximum color development, once the surface is completely dry, sand with 220 grit sanding screen and lightly spray a solution of 50% white vinegar and 50% water across the surface.

7. It is not recommended to seal OxyTop.

Clean Up:

Clean skin with soap and water. Tools and equipment should be cleaned with Xylene or Lacquer thinner. Consult MSDS for safety and health precautions.

Coverage:

200 sq.ft. per pail per coat

Presentation: 20 lbs

Shelf Life: 6 months

Warranty:

decco OxyTop, a proprietary product, is warranted to be of uniform quality within manufacturing tolerances. Since control is not exercised over its use, no warranty, expressed or implied, is made as to the effects of such use. Seller's and manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective. The user assumes all other risks and liabilities resulting from use of this product. If you have any questions, please contact Bluetrade Building Materials, Inc.



decco - Miami
8217-19 NW 66th Street
Miami, FL 33166
Tel: +1 (786) 282-4097
info@heydecco.com

decco - New York
243 Grandview Ave
Staten Island, NY 10303
Tel: +1 (347) 801-2855
sales@dfstudio.nyc

www.heydecco.com
Follow us! @heydecco