

Horizon

CRB-160

Creaser

**A cover creaser that communicates
with BQ-160 binder!**



BQ-160

CRB-160


Features

1. Impact scoring position is set automatically according to the book thickness inserted into the BQ-160.
2. Clean and sharp impact creases can be made even with heavier and laminated stock.
3. Stand alone model is also available with an integrated touch screen operation console.
4. A wide variety of impact scoring patterns can be selected from the touch screen.
5. Suitable for crease covers, restaurant menus, greeting cards and all digital print applications.

Eliminate the problem of image cracking of heavier covers and digital printed sheets.

Operation console

The CRB Creasers can be set-up through the BQ-160 color touch screen. Cover creasing and a variety of other creasing patterns can be selected from the touch screen.



Delivery tray

Creased sheets are delivered at a comfortable height for easy handling.



Impact creasing section

Impact creasing position is automatically set according to the book thickness inserted into the BQ-160.

Depth of the creasing can also be set depending on cover thickness.



CRB-160

CRS-36 (Stand alone model)

A stand alone model is available with built in touch screen. Suitable for impact creasing restaurant menus, greeting cards and various types of heavier stock.



CRS-36

CRB-160 / CRS-36 Major Specifications

Installation Type	Floor Model	
Sheet Feeding System	Manual Feed	
Sheet Size		Width x Length Max. 364 x 650 mm or 14.33" x 25.59" Min. 140 x 180 mm or 5.52" x 7.09" 12 x 18", A3, 11" x 17", JIS B4, 8.5 x 14", A4, 8.5" x 11", JIS B5, and A5
Sheet Weight Range	Normal Paper, Coated Paper 81.4 to 407 gsm, 24 lb bond to 150 lb cover	
Impact Creasing Mechanism	One set of positive and negative	
Number of Impact Crease Lines	Max. Eight Creasing Lines	
Production Speed	Length 430 mm or 16.92", Four Creasing Lines, 4 seconds per sheet A4, short-edge feeding, one creasing line, 1.5 seconds per sheet	
Voltage/Frequency	Single Phase 115 to 120 V, 50 or 60 Hz Single Phase 200 to 240 V, 50 or 60 Hz	
Rated Current	Single Phase 115 to 120 V, 50 or 60 Hz, 1.1 A Single Phase 200 to 240 V, 50 or 60 Hz, 0.5 A	
Machine Dimensions	CRB-160: W1,326 x D610 x H980 mm or W52.3" x D24.1" x H38.6" When the delivery tray is folded W752 x D610 x H980 mm or W29.7" x D24.1" x H38.6" CRS-36: W1,326 x D630 x H1,272 mm or W52.3" x D24.9" x H50.1" When the delivery tray is folded W752 x D630 x H1,272 mm or W29.7" x D24.9" x H50.1"	
Machine Weight	CRB-160: 82 kg or 180.8 lb, CRS-160: 85 kg or 187.4 lb	

*The machine design and specifications are subject to change without any notice.

Distributed by

HORIZON INTERNATIONAL, INC.

510 Kuze Ooyabu-cho, Minami-ku, Kyoto, 601-8206, Japan Phone : +81-(0)75-934-6700, Fax : +81-(0)75-934-6708, www.horizon.co.jp