

4.5' - 6' DOUBLE LEG STRETCH INTERNAL SHOCK ABSORBING LANYARDS



Key Features

- · Lightweight and Durable
- Lanyard Stretch Helps Reduce Potential Tripping Hazards
- · Vibrant Orange Color Provides High Visibility
- 1" Polyester Web
- Alloy Steel Connectors with Minimum Breaking Strength of 5,000 lbs.
- Alloy Steel Connector Gates with Minimum Breaking Strength of 3,600 lbs. for Side and Front Load
- Meets ANSI Z359.13-2013, ANSI A10.32-12, OSHA 1926 Subpart M, OSHA 1910.66, OSHA 1926.502
- · Worker Capacity Range: 130-310 lbs.

The 4.5' – 6' Double Leg Stretch Internal Shock Absorbing Lanyard is specifically designed to help reduce the hazards of tripping or catching on nearby machinery found on many of today's industrial and construction sites. This lanyard is ideal for work in tight spaces and around machinery. The lanyard is designed to stretch from 4.5' when at rest out to 6' when needed. It is available in multiple connector options. Double leg lanyards are for fall arrest and 100% tie off.

Part #	Part Name	Weight
C5106	4.5' - 6' Double Leg Stretch Internal Shock Absorbing Lanyard with 3 Steel Snap Hooks	4.2 lbs.
C5117	4.5' - 6' Double Leg Stretch Internal Shock Absorbing Lanyard with 2 Rebar Hooks and 1 Steel Snap Hook	6 lbs.

