

VERTICAL LIFELINE ASSEMBLY



The Vertical Lifeline Assembly is a full kit built to the strongest conventional (VLA) standards available today. It is resistant to rot and mildew and unaffected by alkalis and most solvents. The Polyester Rope Vertical Lifeline Assembly offers protection against abrasion and is heat resistant. It has a melting point of over 300°F. Vertical Lifelines may be used for either fall arrest (as part of a P.F.A.S. - personal fall arrest system) or for restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. This kit includes an integral shock absorbing device, a positioning device, and an 18" extension lanyard.

Key Features

- Complete Assembly Includes: Three Strand White Polyester Rope, Shock Absorber, Positioning Device and 18" Extension Lanyard
- Durable and Remains Flexible
- Terminated by Stitch and Plastic Casing
- Includes Alloy Steel Snaphook
- UV Resistant
- 5/8" Polyester 3-Strand Rope
- Meets ANSI Z359.1-07, ANSI A10.32-12, OSHA 1926 Subpart M and OSHA 1910
- Minimum Breaking Strength: 5,000 lbs.
- Worker Capacity Range: 130-310 lbs.
- Webbing Material: Polyester, Alloy Steel and Nylon

Part #	Part Name	Weight
C7050	50' Vertical Lifeline Assembly	10.6 lbs.
C7051	25' Vertical Lifeline Assembly	7.3 lbs.
C7056	100' Vertical Lifeline Assembly	19.3 lbs.

