

XT™ 25 Shingles

PRODUCT INFORMATION

CertainTeed offers a variety of three-tab shingle products that combine exceptional durability with flexibility for better resistance to blow-off. In addition to their suitability for residential applications, these products are ideal for commercial applications. Available in “English” dimensions only – 12" x 36.



XT™ 25 Algae-Resistant (AR) shingles are algae-resistant and help protect against dark or black discoloration, sometimes called staining or streaking, caused by blue-green algae.

Colors: Please refer to the product brochure or CertainTeed website for the colors available in your region.

Limitations: Use on roofs with slopes greater than 2" per foot. Low slope applications (2:12 to < 4:12) require additional underlayment. In areas where icing along the eaves can cause a backup of water, apply CertainTeed WinterGuard® Waterproofing Shingle Underlayment, or its equivalent, according to application instructions provided with the product and on the shingle package.

On slopes greater than 21" per foot, apply a spot of roofing cement under each shingle tab corner according to application instructions provided on the shingle package.

Product Composition: These shingles are composed of a fiber glass mat base. Ceramic-coated mineral granules are tightly embedded in carefully refined, water-resistant asphalt. These shingles have self-sealing adhesive. These are 3-tab shingles.

Applicable Standards:

ASTM D3018 Type I

ASTM D3462

ASTM E108 Class A Fire Resistance

ASTM D3161 Class F Wind Resistance

ASTM D7158 Class H Wind Resistance

UL 790 Class A Fire Resistance

ICC-ES ESR-1389 and ESR-3537

Florida Product Approval # FL5444

Miami-Dade Product Control Approved

Meets TDI Windstorm Requirements

XT 25 – English

Weight/Square (approx.):	190-203
Dimensions (overall):	12" x 36"
Shingles/Square:	80
Weather Exposure:	5"

INSTALLATION

Detailed installation instructions are supplied on each bundle of strip shingles and must be followed. Separate application sheets may also be obtained from CertainTeed.

Hips and Ridges: Use field shingles of a like color for capping hips and ridges.

MAINTENANCE

These shingles do not require maintenance when installed according to manufacturer's application instructions. However, to protect the investment, any roof should be routinely inspected at least once a year. Older roofs should be looked at more frequently.

WARRANTY

XT 25 AR carry a 25-year limited transferable warranty to the consumer against manufacturing defects when applied to stated CertainTeed application instructions for this product. These AR shingles carry a 10-year algae resistance warranty and 5-year SureStart protection. For specific warranty details and limitations, refer to the warranty itself (available from the local supplier, roofing contractor or on-line at www.certainteed.com).

FOR MORE INFORMATION

Sales Support Group: 800-233-8990

Web site: www.certainteed.com

See us at our on-line specification writing tool, CertaSpec, at www.certainteed.com/certaspec.

CertainTeed
20 Moores Road
Malvern, PA 19355

© 02/20 CertainTeed

CertainTeed
SAINT-GOBAIN