



# PREPASTED NON-WOVEN DESIGN2WALL FR 230

satin 2515, 230 g/m<sup>2</sup>

Prepasted high quality satin finish non-woven wallpaper for busy areas

The Prepasted non-woven design2wall FR 230 satin is a high quality non-woven wallpaper for printing with solvent, latex and UV inks and is characterised by high colour brilliance and dimensional stability. Thanks to the water-activated paste on the back, the printed wallpaper can be stuck to the wall immediately after soaking in water. The pre-dose of paste adheres to many different surfaces remaining easy to remove. It is flame retardant and certified. The tough, scratch resistant surface of this wallpaper permits its long-term use in busy areas.

## Advantages

- Wide colour gamut and good colour rendition
- High opacity for good coverage of the underlying surface
- Perfect dosage of paste saves time in use
- Scratch resistant surface
- Good lightfastness
- Dimensionally stable, no wet or dry stretching
- Good coverage of uneven surfaces and cracks
- PVC free
- FSC® certified
- Flame retardant and C-s1, d0 certified according to European Standard EN 13501-1



## General tips

To maintain the high quality of this non-woven, it should be stored and converted in a climate of 30-65% relative humidity and at temperatures of 10-30 °C (50-86°F).

## Physical data

Name	Value	Norm
Weight [g/m <sup>2</sup> ]	230	ISO 536
Thickness (total) [µm]	350	ISO 534
Whiteness, CIE D65/2°	78	ISO 11476
Opacity [%]	85	ISO 2471
Gloss (60°)	5.4	ISO 2813

## Technologies



## Properties

