




EXHIBITION STAND  
CONSTRUCTION / POS /  
EVENTS

# ROLL-UP FILM PLUS 210 SB MATT AQ

matt 3597, 210 µm

Roll-Up Film Plus 210 SB Matt AQ (3597) was designed to produce roll-up and display graphics with waterbased and latex inks. The matt coating on the front ensures excellent scratch resistance and a high print quality and brilliant colour reproduction. The tear-resistant polypropylene/polyester composite guarantees problem-free processing and provides a high level of opacity thanks to the matt silver back. Besides it shows good flatness and constructional stability in roll-up systems. Due to its excellent price-performance ratio, Roll-Up Film Plus 210 SB Matt AQ is the ideal choice for the production of high volume products for short to mid-term use.

## Technologies



## Properties



## Advantages

- Brilliant colour reproduction
- Anti-reflective, matt surface
- Matt, silver back for high opacity
- Good flatness for short to mid-term use
- Tear-resistant
- Scratch-resistant surface and reverse side

## General tips

We recommend that prints are left 24 hours before further processing. The product should be stored in the original packaging at room temperatures of 15 – 25 °C, with a relative humidity of 40-60%.

## Physical data

Name	Value	Norm
Thickness (film) [µm]	210	ISO 4593
Weight [g/m <sup>2</sup> ]	165	ISO 536
Whiteness, CIE D65/2°	123	ISO 11476
Opacity [%]	99.6	ISO 2471
Gloss (60°)	2.6	ISO 2813