

## DATA SHEET

### H965 DOUBLE COATED TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
LINER	3MIL LIGHT PINK MOPP FILM
CARRIER	1MIL (25 $\mu$ ) PET FILM
PEEL ADHESION	PSTC-3 1.8KGS/25MM
LOOP TACK	FINAT-9 2.5KG/25MM
SHEAR STRENGTH	PSTC-7 OVER 24 HOURS WITH 1KG LOADING ON 25MM X 25MM AT 25 $^{\circ}$ C
THICKNESS	0.16 $\pm$ 0.01MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 80 $^{\circ}$ C
SERVICE TEMPERATURE	-20 TO 100 $^{\circ}$ C

### PRODUCT FEATURES AND APPLICATIONS

MOUNTING ON ABS PLASTIC PLATES IN INDUSTRIAL GRADE APPLICATIONS  
 SELF ADHERING JOINING OF RUBBER AND EPDM MATERIALS  
 BONDING TO DECORATIVE TRIM SUCH AS PVC PROFILES, STAINLESS  
 STEEL AND PLASTIC PARTS

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER  
 ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : FEBRUARY 2013