

DATA SHEET

H989 DOUBLE COATED FOAM TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
TACK	J.DOW NO. 16
LINER	90G/M2 WHITE GLASSINE PAPER
CARRIER	CROSSLINKED 4 PCF PE FOAM
PEEL ADHESION	PSTC-3 2.1KGS/25MM
SHEAR STRENGTH	OVER 24 HOURS WITH 1KG SANDWICH LOADING ON 2 STAINLESS STEEL PLATES 25MM X 25MM AT 25°C
THICKNESS	1.0MM ± 0.1MM
SERVICE TEMPERATURE	-20 TO 80°C
COLOUR	WHITE

PRODUCT FEATURES AND APPLICATIONS

HIGH TACK PERMANENT ADHESIVE WITH EXCELLENT AGING AND WEATHER RESISTANT PROPERTIES
SPECIFICALLY DESIGNED FOR MOUNTING AND JOINING NAMEPLATES, PLASTIC TRIM, SIGNS AND EMBLEMS
LONG TERM BONDING PERFORMANCE TO PLASTIC HANGERS AND MIRROR MOUNTING

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : MARCH 2013