

DATA SHEET

H964HD DOUBLE COATED TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
LINER	90G/M2 HONEY GLASSINE RELEASE
CARRIER	0.08MM WHITE MATTED OLEFIN FILM
PEEL ADHESION	PSTC-3 3.1KGS/25MM
TACK	J.DOW NO. 16
SHEAR STRENGTH	PSTC-7 OVER 72 HOURS WITH 1KG LOADING ON 25MM X 25MM AT 25°C
THICKNESS	0.30 ± 0.01MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 80°C
SERVICE TEMPERATURE	-20 TO 100°C (SHORT TIME)

PRODUCT FEATURES AND APPLICATIONS

PERMANENT BONDING RESULTS TO MOST SUBSTRATES, METAL, WOOD, GLASS,
CEMENT AND PLASTICS

EXTENSIVELY USED IN THE FURNITURE INDUSTRY ON PVC PROFILES
FASTENING FOR NAMEPLATES, LABELS AND EMBLEMS

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER
ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JUNE 2021