

DATA SHEET

H965A DOUBLE COATED POLYESTER FILMIC TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
TACK	J.DOW NO. 14
LINER	130G/M2 PE COATED BLEACHED KRAFT PAPER
CARRIER	1 MIL (25μ) TRANSPARENT PET FILM
PEEL ADHESION	PSTC-3 2.1KGS/25MM
SHEAR STRENGTH	PSTC-7 OVER 24 HOURS WITH 1KG LOADING ON 25MM X 25MM 25 °C
THICKNESS	0.15 ± 0.01MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 80 °C
SERVICE TEMPERATURE	-30 TO 120°C

PRODUCT FEATURES AND APPLICATIONS

HIGH TACK PERMANENT ADHESIVE FOR QUICK BONDING RESULTS WITH GOOD TEMPERATURE, CHEMICAL AND UV RESISTANCE
FIXING SIGNS AND PANELS MADE OF METAL OR PLASTIC
USED FOR LAMINATING AND FASTENING APPLICATIONS IN MANUFACTURING OF ELECTRONIC DEVICES

THE USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE AND THE USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH.

DATE OF ISSUE : JUNE 2021