

DTF-MINI300 ECO PRINTING MACHINE



— MACHINE PARAMETER —

Brand	Sublistar
Model	DTF-Mini300 ECO
Print Width	≤300mm
Sprinkler	XP600
Number of Printheads (pieces)	2
Applicable Media	PET Film
Heating And Drying Function	Front Guide Plate Heating, Upper Drying And Curing, Cold Air Cooling Function
Printing Speed	TX600 2Printheads 6pass 2m ² /h 8pass 1.5m ² /h
Printing Accuracy	720dpi/1080dpi/1440dpi
Nozzle Cleaning	Automatic
Heating Method	Front Guide Plate Heating (30°C-65°C)
Platform Suction Adjustment	Have
Print Interface	USB3.0
Working Environment	Temperature 15°C-30°C
Relative Humidity	40-60%
Operating System	XP/Win7/Win10
Rewind Function	Automatic Induction Winding
Rated Power	250±5%W
Packaging size and Weight	Printer: 990mm*630mm*610mm; Weight: 70kg Shaker machine : 990mm*690mm*710mm; Weight: 60kg

— FEATURES —

- High-speed printing, efficient operation, easy to use, labor-saving
- One-time molding, no carving, no hollowing, no waste discharge, no white edge, environmental protection
- Suitable for A3/A4 digital heat transfer printing with a format less than or equal to 30cm
- Japan THK silent guide rail and PID precise temperature control
- Printing & Shaking Powder All-in-One
- High quality foot cup, universal wheel
- White ink easy to stir cycle
- Integrated lift ink stack

— APPLICATION —

