

## Features >

- Sourced by high output 2835 LED, good color conformity and no spot.
- 99.99% gold thread, pure copper bracket coated with silver.
- SDCM≤5 each BIN.
- Special lens design, 160°beaming angle with even light.
- Overmoulded: anti-dusting, anti-moisture, waterproof, anti-shock.
- 50 pcs Max. in a series connection.
- CE, RoHS and UL certified.

## Application >


- Best for 6-15 cm depth signs at airports, metros, banks, buildings and shopping malls, etc.
- Best for 6-15 cm depth single-sided light box at airports, metros, banks, buildings and shopping malls, etc.

Parameters >


Items	Parameters
Part Number	ZE03QG1
CCT ( K )	12000K
Beaming Angle ( ° )	160
CRI ( Ra )	≥70
Luminous Flux ( lm )	150
Voltage ( V )	AC220V
Power ( W )	2
Driving Method	Inner Constant Current
Dimension ( mm )	86*19*8.3
Weight ( g )	15.5
Working Tem. ( °C )	-25 ~ +60
Storage Tem. ( °C )	-25 ~ +70
Protection Grade	IP65

Dimension >

Unit:mm



Beaming Angle >




Reference Scheme >

Depth(mm)	Distance(mm)	Density(pcs/m <sup>2</sup> )	Illumination(lux)
Dz=60	Dx=80 Dy=80	60	3800-4200
Dz=80	Dx=80 Dy=80	60	3400-3800
Dz=100	Dx=80 Dy=80	60	3000-3400
Dz=120	Dx=80 Dy=80	60	2600-3000


Remark:

- The transmittance of the advertising fabric was 32%.
- The above data is for reference only.




Wire Connection >


White&Red wire to positive  
White&Black wire to negative




## Packing



50cs in a string



100pcs in a plastic tray



1000 pcs in a carton

## Packing Specification



- Packed in plastic tray.
- Packing information

Part Number	ZE03QG1
Carton Dimension(mm)	490*450*220
Trays per carton	20
Quantity per carton(pcs)	1000
Net Weight(kg)	12.0(1±10%)
Gross Weight(kg)	13.0(1±10%)

Due to the packing manner difference, please subject to the original products in case of discrepancy found between the picture and actual product.

## Warning



- Disassembling or modifying the product is forbidden.
- Installation with power on is forbidden.
- Any organic solvent chemical is forbidden.
- Acidic or alkaline adhesive is forbidden when install, neutral glass cement could be used for installation purpose, make it drying in open environment for four hours.
- Isolation and corrosion prevention on all wiring points and wire ends.
- Make sure the power wire is thick enough and ensure the voltage and connections are connected correctly before power on.
- This product should be used in a sign, do not expose it in opening site.
- Installation, maintaining should be done by professional staff.
- 50 pcs in a serial connection maximum.
- The power wire between power supply and module should be less than two meters to keep the same brightness on all parts.
- Initial location with 3M tape, then secure with screws.

## Declaration



- Warranty: 3 years.
- In order to ensure the safety, the broken wires need to be replaced by the manufacturer or the service agent, or by the staff with the similar qualification.
- The given data in the specification was based on the laboratory testing, there may be discrepancy found in the actual products.
- The given drawings in the specification are only for reference, there may be discrepancy found in the actual products.
- The products are subject to change without prior notification.



**RoHS**

**Company Address:**

Rm. WS, 9F, LuBan Building, Hongli West Road, Futian District,  
Shenzhen, China 518034

**Factory Address:**

No. B, Xinyongfeng Industrial Area, Yingrenshi Village, Shiyuan Town,  
Bao'an District, Shenzhen, China 518000

**TEL:** +86-755-83544570

**FAX:** +86-755-83056229

**Website:** [www.lbyled.com](http://www.lbyled.com)

**E-mail:** [info@lbyled.com](mailto:info@lbyled.com)



**LBY LED®**  
signs never been so easy