

mary maxim

Kids Cabled Jacket

No: 97494-5

Sizes: 4, 6, 8, 10, 12

■■■■□ INTERMEDIATE



SHOPPING LIST

Yarn (Chunky Weight)



Marvelous Chunky

[7 ounces, 270 yards

(200 grams, 250 meters) per ball]:

Sizes 4, 6, 8 3 balls

Sizes 10, 12 4 balls

Required, but not included

Buttons 5

Knitting Needles:

Size 8 (5.00 mm)

Size 10 (6.00 mm)

or size needed for gauge

SIZE INFORMATION

Finished Chest: 26(28, 30, 32, 34)"

[66(71, 76, 81, 86.5) cm]

Length from Shoulder: 16.5(16.5, 17.5,

18.5, 19.5)" [42(42, 44.5, 47, 49.5) cm]

Sleeve Seam: 10.5(11.5, 12.5, 13.5, 15)"

[26.5(29, 31.5, 34.5, 38) cm]

GAUGE INFORMATION

16 sts and 22 rows to 4" [10 cm]

measured over pattern and

Cable Panel measures 2.5" [6.5 cm]

wide, using **suggested** larger needles

or any size needles which will give the

correct gauge.

STITCH GUIDE

beg begin or beginning

k knit

p purl

cm centimeters

dec decrease or decreasing

inc increase or increasing

rem remain or remaining

rep repeat or repeating

st(s) stitch(es)

sl slip

St st Stocking stitch

tog together

PM place marker

M marker

KB1 knit into back of next stitch.

C8B Slip next 4 sts onto cable needle and hold to back of work, k4 from left-hand needle, then k4 from cable needle.

ssk Slip next 2 sts knitwise one at a time, to right needle, then insert left needle through fronts of both sts from back to front and k2tog as usual.

INSTRUCTIONS

Cable Panel: (worked over 14 sts)

Rows 1 and 3: (right side) K1, p2, k8, p2, k1.

Row 2 and every alternate row: Purl the p sts and knit the k sts as they appear.

Row 5: K1, p2, C8B, p2, k1.

Rows 7 and 9: Repeat Rows 1 and 3.

Row 10: As Row 2.

Repeat these 10 rows of pattern for Cable Panel.

Back: Using smaller needles, cast on 53(57, 61, 65, 69) sts and work in ribbing as follows:

Row 1: (right side) K1, *p1, k1; rep from * to end.

Row 2: P1, *k1, p1; rep from * to end. Repeat these 2 rows once more.

Change to larger needles and work in pattern as follows:

Row 1: (right side) K1, p1, *KB1, p1; rep from * to last st, k1.

Row 2: P1, k to last st, p1.

Repeat these 2 rows for Twisted Rib until piece measures 11.75(11.5, 12, 12.5, 13)" [30(29, 30.5, 31.5, 33) cm] from cast on edge, ending after a wrong side row.

To Shape Armholes: Keeping pattern correct, cast off 4 sts at beg of next 2 rows - 45(49, 53, 57, 61) sts.

Now dec one st at each end of the next row, then every other row following until 39(43, 45, 49, 53) sts rem.

Work even in pattern until armhole measures 3.5(3.75, 4.25, 4.75, 5.25)" [9(9.5, 11, 12, 13.5) cm], ending after a wrong side row.

Next Row: Cast off 10(12, 13, 15, 17) sts at beg of next 2 rows.

Work even in pattern on rem 19 sts until piece measures 16.5(16.5, 17.5, 18.5, 19.5)" [42(42, 44.5, 47, 49.5) cm] from cast on edge, ending after a wrong side row.

Place rem sts on st holder.

Right Front: Using smaller needles, cast on 25(27, 29, 31, 33) sts and work ribbing as follows:

Row 1: (right side) K1, *p1, k1; rep from * to end.

Row 2: P1, *k1, p1; rep from * to end.

Next Row: K2, p2, [inc one st in next st] 4 times, p2, k1, PM, *p1, k1; rep from * to end - 29(31, 33, 35, 37) sts.

Next Row: *P1, k1; rep from * to M, sl M, p1, k2, p8, k2, p2.

Change to larger needles and set patterns in place as follows:

Row 1: (right side) K1, work Row 1 of Cable Panel to M, sl M, *p1, KB1; rep from * to end, but working last st as k1.

Row 2: P1, k to M, slip M, work Row 2 of Cable Panel to last st, p1.

These 2 rows set Twisted Rib and Cable Panel in place.

Now keeping patterns correct as set and slipping M on every row, continue until piece measures 11.75(11.5, 12, 12.5, 13)" [30(29, 30.5, 31.5, 33) cm] from cast on edge, ending after a right side row.

To Shape Armhole:

Next Row: Cast off first 4 sts, k to M, work Cable Panel to last st, p1 - 25(27, 29, 31, 33) sts.

Keeping patterns correct, dec one st at armhole edge on next row, then every alternate row following until 22(24, 25, 27, 29) sts rem.

Now work even, keeping patterns correct, until armhole measures 2.75(3, 3.5, 4, 4.5)" [7(7.5, 9, 10, 11.5) cm], ending after a wrong side row and dec 4 sts over cable by [p2tog] 4 times on last row - 18(20, 21, 23, 25) sts.

To Shape Neck:

Next Row: Cast off first 8 sts, work in pattern to end.

Work 3 rows even. Cast off in pattern.

Left Front: Using smaller needles, cast on 25(27, 29, 31, 33) sts and work ribbing as follows:

Row 1: (*right side*) K1, *p1, k1; rep from * to end.

Row 2: P1, *k1, p1; rep from * to end.

Next Row: (*right side*) *K1, p1; rep from * to last 11 sts, PM, k1, p2, [inc one st in next st] 4 times, p2, k2 - 29(31, 33, 35, 37) sts.

Next Row: P2, k2, p8, k2, p1, sl M, *k1, p1; rep from * to end.

Change to larger needles and set patterns in place as follows:

Row 1: (*right side*) K1, p1, *Kb1, p1; rep from * to M, sl M, work Row 1 of Cable Panel to last st, k1.

Row 2: P1, work Row 2 of Cable Panel to M, sl M, k to last st, p1.

These 2 rows set Twisted Rib and Cable Panel in place.

Now keeping patterns correct as set and slipping M on every row, continue until piece measures 11.75(11.5, 12, 12.5, 13)" [30(29, 30.5, 31.5, 33) cm] from cast on edge, ending after a wrong side row.

To Shape Armhole:

Next Row: Cast off first 4 sts, work Twisted Rib to M, work Cable Panel to last st, k1 - 25(27, 29, 31, 33) sts.

Keeping all patterns correct, dec one st at armhole edge on every alternate row following until 22(24, 25, 27, 29) sts rem.

Now work even, keeping patterns correct, until armhole measures 2.75(3, 3.5, 4, 4.5)" [7(7.5, 9, 10, 11.5) cm], ending after a right side row and dec 4 sts over cable by [k2tog] 4 times on last row - 18(20, 21, 23, 25) sts.

To Shape Neck:

Next Row: Cast off first 8 sts, work in pattern to end.

Work 3 rows even. Cast off in pattern.

Sleeves: Using larger needles, cast on 26(26, 30, 30, 34) sts and work ribbing as follows:

Rows 1 and 2: *K1, p1; rep from * to end.

Next Row: (*right side*) [K1, p1] 4(4, 5, 5, 6) times, PM, k1, p2, [inc one st in next st] 4 times, p2, k1, PM, [k1, p1] 4(4, 5, 5, 6) times - 30(30, 34, 34, 38) sts.

Next Row: [K1, p1] 4(4, 5, 5, 6) times, sl M, p1, k2, p8, k2, p1, sl M, [k1, p1] 4(4, 5, 5, 6) times.

Now work in patterns as follows, slipping M's on every row:

Row 1: K1, p1, *KB1, p1; rep from * to M, work Row 1 of Cable Panel to next M, *p1, KB1; rep from * to end, but work last st as k1.

Row 2: P1, k to M, work Row 2 of Cable Panel to next M, k to last st, p1.

These 2 rows set Twisted Rib and Cable Panel in place.

Continue in patterns as set, slipping M's on every row, AND AT THE SAME TIME, inc one st at each end of the 5th row, then every 6th row following until there are 42(44, 48, 52, 56) sts on the

needle, taking inc sts into Twisted Rib as they become available.

Now work even in patterns until sleeve measures 10.5(11.5, 12.5, 13.5, 15)" [26.5(29, 31.5, 34.5, 38) cm] from cast on edge, ending after a wrong side row.

To Shape Saddle Shoulder:

Cast off 14(15, 17, 19, 21) sts at beg of next 2 rows. (14 sts)

Now working Cable Panel only, continue until saddle measures 2.5(3.25, 3.25, 3.75, 4.25)" [6.5(8, 8, 9.5, 10.5) cm] from cast off row, ending after a right side row.

Next Row: P1, k2, [p2tog] 4 times, k2, p1. (10 sts)

Cast off in pattern.

Buttonband: (worked on Right Front for Boys and Left Front for Girls) Using smaller needles, with right side facing, pick up and k 61(61, 65, 69, 73) sts along front edge, evenly spaced between bottom edge and cast off at beg of neck (about 3 sts for every 4 rows). Work ribbing as follows:

Row 1: (*wrong side*) P1, *k1, p1; rep from * to end.

Row 2: K1, *p1, k1; rep from * to end. Repeat these 2 rows three times more, then Row 1 once. Cast off ribwise.

Buttonhole Band: Work as for Buttonband on opposite front edge until 4 rows have been completed.

Next Row: Buttonhole Row: Rib 2, [work 2tog, yo, rib 11(11, 12, 13, 14)] 4 times, yo, work 2tog, rib to end. Work 4 more rows of ribbing. Cast off ribwise.

Sew Saddle shoulders in place along cast off edges of shoulders on Fronts and Back.

Sew side edge of back neck to top edge of Saddle shoulder, ending at center of Saddle.

Collar: Using smaller needles and with right side facing, beg in center of Buttonband, pick up and k 25 sts evenly up right side of front neck to center of Saddle, k sts from back neck st holder, starting at center of other Saddle, pick up and k 25 sts evenly down left side of front neck - 69 sts. Work ribbing as given for Buttonband until collar measures 3" [7.5 cm]. Cast off loosely ribwise.

To Complete: Sew cast off edges of sleeves to straight edges of armholes. Sew side and sleeve seams (having top 1" [2.5 cm] at each side of sleeves sewn to cast off sts of armholes as top of sleeve seams). Sew on buttons to match buttonholes. Weave in all ends.

We have made every effort to ensure that these instructions are accurate and complete. We cannot be responsible for misinterpretation or errors in individual work. Any corrections that are discovered, will be posted on our website.

Copyright © 2017 by Mary Maxim, Inc. All rights reserved. This publication is protected under federal copyright laws. Reproduction or distribution of this publication or any other Mary Maxim publication, including publications which are out of print, is prohibited unless specifically authorized. This includes, but is not limited to, any form of reproduction or distribution on or through the Internet, including posting, scanning or e-mail transmission.

mary maxim

2001 Holland Ave., Port Huron, MI 48060;
75 Scott Ave., Paris, Ontario, CANADA N3L 3G5

Yarn Imported