

mary maxim

Cabled Comfort Classic

No. 98404-5-6N

Sizes: 32-34, 36-38, 40-42, 44-46

■■■■ D INTERMEDIATE



SHOPPING LIST

Yarn (Bulky Weight)

Mary Maxim Classic

[3.5 oz, 130 yards]

(100 grams, 120 meters) per ball]:

- Sizes 32-34, 36-38 7 balls
- Size 40-42 8 balls
- Size 44-46 9 balls



Knitting Needles

- Size 10 (6.00 mm)
- 32" [80 cm] Circular Needle
- Size 10 (6.00 mm)
- or size needed for gauge

SIZE INFORMATION

Finished Chest: 36(40, 44, 48)"

[91.5(101.5, 111.5, 122) cm]

Length from Back Neck: 24(24.5, 25,

25.5)" [61(62, 63.5, 64.5) cm]

GAUGE INFORMATION

One Cable Panel = 3.75" [9.5 cm] wide and 7 sts and 10 rows to 2" [5 cm] measured over Reverse Stocking st, using **suggested** needles or any size needles which will give the correct gauge.

STITCH GUIDE

k	knit
p	purl
sl	slip
st(s)	stitch(es)
St st	Stocking stitch
beg	begin or beginning
dec	decrease or decreasing
inc	increase or increasing
"	inches
cm	centimeters
mm	millimeter
rem	remain or remaining
rep	repeat
tog	together

yo yarn over
PM place marker
M marker
ssk Slip next 2 sts knitwise, one at a time, to right-hand needle, then insert left-hand needle through fronts of both sts, from back to front and k2tog as usual.

C6F Slip next 3 sts onto cable needle and hold to front of work, k3 from left-hand needle, then k3 from cable needle.

C6B Slip next 3 sts onto cable needle and hold to back of work, k3 from left-hand needle, then k3 from cable needle.

W&T Bring yarn to front of work, slip next st to right-hand needle, take yarn to back of work then slip st back to left-hand needle. Turn work.

Cable Panel: (worked over 18 sts)

Row 1: (right side) C6F, k6, C6B.

Row 2 and every alternate row: Purl.

Row 3: Knit.

Row 5: K3, C6B, C6F, k3.

Row 7: As Row 3.

Row 8: As Row 2.

Repeat these 8 rows for Cable pattern.

INSTRUCTIONS

Back: Using straight needles, cast on 66(74, 82, 90) sts.

Work in ribbing as follows:

Row 1: (right side) K2, *p2, k2; rep from * to end.

Row 2: P2, *k2, p2; rep from * to end. Repeat these 2 rows once more, then Row 1 once.

Next Row: (inc row) K 10(10, 14, 14), PM, [p1, inc one st in next st purlwise] 3 times, [inc one st in next st purlwise, p1] 3 times, PM, k2, [p2, k2] 5(7, 7, 9) times, PM, [p1, inc one st in next st purlwise] 3 times, [inc one st in next st purlwise, p1] 3 times, PM, k 10(10, 14, 14) - 78(86, 94, 102) sts.

Now set pattern in place as follows:

Row 1: (right side) Purl to first M, sl M, work Row 1 of Cable Panel to next M, sl M, work ribbing as set to next M, sl M, work Row 1 of Cable Panel to next M, sl M, p to end.

Row 2: Knit to first M, sl M, work Row 2 of Cable Panel to next M, sl M, work ribbing as set to next M, sl M, work Row 2 of Cable Panel to next M, sl M, k to end.

Cable Panels are now set in place with ribbing in center between panels and Reverse St st at each outside edge (purl on right side rows, knit on wrong side rows).

Continue in patterns as set until piece measures 17" [43 cm] from cast on edge, ending after a right side row.

To Shape Sleeve Caps:

Next Row: K1, k into front and back of next st (kf&b), work in patterns to last 2 sts, kf&b, k1 - 80(88, 96, 104) sts.

PM at each end of last row worked to indicate beg of Sleeve Cap.

Now keeping patterns correct, inc one st at each end of every 6th row following, as before, until there are 88(96, 104, 112) sts, taking inc sts into Reverse St st.

Now work even in patterns until piece measures 24(24.5, 25, 25.5)" [61(62, 63.5, 64.5) cm] from cast on edge, ending after a wrong side row.

Last Row: Cast off first 31(35, 37, 41) sts AND AT THE SAME TIME, dec 6 sts over cable, work in ribbing over next 25(25, 29, 29) sts, then slip these center 26(26, 30, 30) sts onto st holder for collar, cast off rem 31(35, 37, 41) sts AND AT THE SAME TIME, dec 6 sts over cable.

Left Front:

**Cast on 28(32, 36, 40) sts.

Row 1: (right side) *P2, k2; rep from * to end.

Repeat these last row 4 times more.

Next Row: (inc row) K8(10, 12, 14), PM, [p1, inc one st in next st purlwise] 3 times, [inc one st in next st purlwise, p1] 3 times, PM, k8(10, 12, 14) - 34(38, 42, 46) sts.

Now set Cable in place as follows:

Row 1: (right side) Purl to first M, sl M, work Row 1 of Cable Panel to next M, sl M, p to end.

Row 2: K to first M, sl M, work Row 2 of Cable Panel to next M, sl M, k to end.

Cable Panel is now in place, with Reverse St st at each outside edge. Continue in pattern as set until piece measures 12(12.5, 12, 12.5)" [30.5(31.5, 30.5, 31.5) cm] from cast on edge, ending after a wrong side row.**

To Shape Front Neck:

Next Row: Pattern to last 3 sts, p2tog, p1. Place marker at end of last row to indicate beg of neck shaping.

Work 5(5, 7, 7) rows even in pattern. Repeat these last 6(6, 8, 8) rows 7 times more AND AT THE SAME TIME, when piece measures 17" [43 cm] from cast on edge, ending after a right side row, beg to shape sleeve cap as follows:

To Shape Sleeve Cap:

Next Row: Pattern to last 2 sts, kf&b, k1. Place a different color marker at end of last row to indicate beg of sleeve cap.

Now keeping pattern correct, continue to dec for front neck as before AND AT THE SAME TIME, inc one st at end of every 6th row for sleeve cap 4 times - 31(35, 39, 43) sts rem.

Once all inc and dec have been made, continue even in pattern until piece measures 24(24.5, 25, 25.5)" [61(62, 63.5, 64.5) cm] from cast on edge, ending after a wrong side row.

Next Row: (right side) Purl to first M, remove M, [k1, k2tog] 6 times, remove

next M, p to end.

Cast off all sts.

Right Front:

Work as given for Left Front from ** to **.

To Shape Front Neck:

Next Row: P1, p2tog, work in pattern to end. Place marker at beg of last row to indicate beg of neck shaping. Work 5(5, 7, 7) rows even in pattern.

Repeat these last 6(6, 8, 8) rows 7 times more AND AT THE SAME TIME, when piece measures 17" [43 cm] from cast on edge, ending after a right side row, beg to shape sleeve cap as follows:

To Shape Sleeve Cap:

Next Row: K1, kf&b, work in pattern to end. Place a different color marker at beg of last row to indicate beg of sleeve cap.

Now keeping pattern correct, continue to dec for front neck as before AND AT THE SAME TIME, inc one st at end of every 6th row for sleeve cap 4 times - 31(35, 39, 43) sts rem.

Once all inc and dec have been made, continue even in pattern until piece measures 24(24.5, 25, 25.5)" [61(62, 63.5, 64.5) cm] from cast on edge, ending after a wrong side row.

Next Row: (right side) Purl to first M, remove M, [k1, k2tog] 6 times, remove next M, p to end.

Cast off all sts.

Sew both shoulder seams.

Armbands:

Using straight needles, with right side facing and working between marker on Back and marker on front piece, pick up and k 58(62, 70, 74) sts evenly between. Now work in ribbing as follows:

Row 1: (wrong side) P2, *k2, p2; rep from * to end.

Row 2: K2, *p2, k2; rep from * to end.

Row 3: Rib to last 8 sts, W&T, rib to last 8 sts, W&T.

Row 4: Rib to last 16 sts, W&T, rib to last 16 sts, W&T.

Rib to end of needle.

Cast off all sts ribwise.

Repeat for other armband.

Front Bands and Collar:

Using circular needle and with right side facing, beg at bottom right front pick up and k 48(52, 48, 52) sts to beg of neck shaping, pick up and k 54(56, 60, 62) sts up right side of front neck, work sts ribwise from back neck st holder, pick up and k 54(56, 60, 62) sts down to beg of neck shaping, pick up and k 48(52, 48, 52) sts down to bottom left corner - 230(242, 246, 258) sts.

Now work in ribbing as follows:

Row 1: (wrong side) P2, *k2, p2; rep from * to end.

Row 2: K2, *p2, k2; rep from * to end. Repeat these 2 rows twice more.

Next Row: Buttonhole Row: (wrong side) Rib as set to last 48(52, 48, 52) sts, k2tog, yo, rib over next 10 sts, k2tog, yo, rib to end.

Now work in short rows to build Collar as follows:

Next Row: (right side) Rib as set to last 48(52, 48, 52) sts, W&T. Place a marker on wrapped st.

This left marker will be moved.

Next Row: Rib to last 48(52, 48, 52) sts, W&T. Place a marker on this wrapped st.

This right marker will move as well.

Next Row: Rib to 6 sts before left marker, W&T.

Move left marker to this wrapped st.

Next Row: Rib to 6 sts before right marker, W&T.

Move right marker to this wrapped st.
Next Row: Rib to 12 sts before left marker, W&T.
Move left marker to this wrapped st.
Next Row: Rib to 12 sts before right marker, W&T.
Move right marker to this wrapped st.
Next Row: Rib to 12 sts before left marker, W&T.
Move left marker to this wrapped st.
Next Row: Rib to 12 sts before right

marker, W&T.
Move right marker to this wrapped st.
Next Row: Rib to end of needle.
Remove all markers.
Working over all sts, work 7 more rows of ribbing.
Cast off ribwise.

To Complete:

Sew side seams, including armbands, neatly.
Sew buttons securely to left front band, opposite each buttonhole.

We have made every effort to ensure that these instructions are accurate and complete. We cannot be responsible for misinterpretation or errors in individual work. Any corrections that are discovered, will be posted on our website.

Copyright © 2014 by Mary Maxim, Inc. All rights reserved. This publication is protected under federal copyright laws. Reproduction or distribution of this publication or any other Mary Maxim publication, including publications which are out of print, is prohibited unless specifically authorized. This includes, but is not limited to, any form of reproduction or distribution on or through the Internet, including posting, scanning or e-mail transmission.

mary maxim

2001 Holland Ave., Port Huron, MI 48060;
75 Scott Ave., Paris, Ontario, CANADA N3L 3G5

Yarn Imported