

No. 99088N or 99084N  
Child's Tweed Cables  
Sizes: 4, 6



**mary maxim**<sup>®</sup>  
EXCLUSIVE NEEDLEWORK and CRAFTS Inc.



**Materials:** Mary Maxim Aran Irish Tweed or Aran Irish Twist  
Buttons

**4 skeins**

### **Suggested Needles:**

One pair knitting needles size 8 US (Canadian size 6, Metric size 5.00 mm)

### **Measurements:**

Finished Chest Measurement: 25(27)" [63.5(68.5) cm]

Length from Shoulder: 18½(19½)" [47(49.5) cm]

Sleeve Seam (with cuff folded in half): 10½(11½)" [26.5(29) cm]

### **TO SAVE TIME, TAKE TIME TO CHECK GAUGE**

**Gauge:** Cable Panel (32 sts) measures 5" [12.5 cm] wide and 24 rows to 4" [10 cm] using **suggested** needles or any size needles which will give the correct gauge.

**Carefully follow washing and drying instructions printed on yarn label for finished garment.**

**Abbreviations:** K, knit; p, purl; st, stitch; sts, stitches; beg, begin or beginning; dec, decrease or decreasing; inc, increase or increasing; ", inches; yds, yards; gm, gram; cm, centimeters; mm, millimeter; rem, remain or remaining; rep, repeat; tog, together; sl, slip; yo, yarn over; tbl, through back loop; PM, place marker.

### **Special Abbreviations:**

**C4B - Cable 4 Back:** Slip next 2 stitches onto cable needle and hold to back of work, k2 from left needle, then k2 from cable needle.

**C4F - Cable 4 Front:** Slip next 2 stitches onto cable needle and hold to front of work, k2 from left needle, then k2 from cable needle.

**ssk - slip, slip, knit 2 together:** Slip next 2 stitches knitwise, one at a time to right needle, then insert left needle through fronts of both stitches and k2tog as usual.

**Cable Panel:** (worked over 32 sts)

**Row 1:** (right side) P1, C4B, p3, k4, C4B, C4F, k4, p3, C4F, p1.

**Row 2 and every alternate row:** K1, p4, k3, p 16, k3, p4, k1.

**Row 3:** P1, k4, p3, k2, C4B, k4, C4F, k2, p3, k4, p1.

**Row 5:** P1, k4, p3, C4B, k8, C4F, p3, k4, p1.

**Row 6:** As Row 2.

Repeat these 6 rows for Cable Panel.

**Back:** Cast on 57(61) sts.

Now work ribbing as follows:

**Row 1:** (right side) K 0(2), \*p3, k3; rep from \* to last 3(5) sts, p3, k 0(2).

**Row 2:** P 0(2), k3, \*p3, k3; rep from \* to last 0(2) sts, p 0(2).

Repeat these 2 rows until ribbing measures 2½" [6.5 cm], ending after a Row 1.

**Next Row:** (inc row) P 0(2), k3, PM, p1, [inc one st in next st purlwise] twice, k3, p1, [inc one st in next st purlwise] 7 times, p1, k3, [inc one st in next st purlwise] twice, p1, PM, k3, inc one st in next st purlwise, p1, inc one st in next st purlwise, k3, PM, p1, [inc one st in next st purlwise] twice, k3, p1, [inc one st in next st purlwise] 7 times, p1, k3, [inc one st in next st purlwise] twice, p1, PM, k3, p 0(2) - 81(85) sts.

Now set patterns in place as follows:

**Row 1:** (right side) K 0(2), p3, sl M,

work Row 1 of Cable Panel to next marker, sl M, k1, [p1, k1] 5 times, sl M, work Row 1 of Cable Panel to next marker, sl M, p3, k 0(2).

**Row 2:** P 0(2), k3, sl M, work Row 2 of Cable Panel to next marker, sl M, p1, [k1, p1] 5 times, sl M, work Row 2 of Cable Panel to next marker, sl M, k3, p 0(2).

**Row 3:** K 0(2), p3, sl M, work Row 3 of Cable Panel to next marker, sl M, p1, [k1, p1] 5 times, sl M, work Row 3 of Cable Panel to next marker, sl M, p3, k 0(2).

**Row 4:** P 0(2), k3, sl M, work Row 4 of Cable Panel to next marker, sl M, k1, [p1, k1] 5 times, sl M, work Row 4 of Cable Panel to next marker, sl M, k3, p 0(2).

Cable Panels are now set between markers with Double Moss st (rep as given in Rows 1-4), between panels and sts outside of markers.

**\*\*Now keeping all patterns correct, continue until piece measures 13¾(14½)" [35(37) cm] from cast on edge, ending after a wrong side row.\*\***

### **To Shape Armholes:**

Keeping patterns correct, cast off 3(4) sts at beg of next 4 rows - 69(69) sts.

**Next Row:** K1, ssk, work in pattern to last 3 sts, k2tog, k1.

**Next Row:** Work in pattern to end.

Repeat these last 2 rows 2(1) times more - 63(65) sts.

Now work even in patterns until armholes measure  $4\frac{3}{4}(5)$ " [12(12.5) cm], ending after a wrong side row.

**To Shape Shoulders:** Keeping patterns correct, cast off 7(8) sts at beg of next 2 rows, then 6 sts at beg of next 4 rows - 25 sts rem.

Place rem 25 sts on st holder for back neck.

**Left Front:** Cast on 34(36) sts. Now work ribbing and Double Moss front band as follows:

**Row 1:** (right side) K 0(2), [p3, k3] 4 times, PM, [p1, k1] 5 times (these last 10 sts are for front band).

**Row 2:** [P1, k1] 5 times, sl M, [p3, k3] 4 times, p 0(2).

**Row 3:** K 0(2), [p3, k3] 4 times, sl M, [k1, p1] 5 times.

**Row 4:** [K1, p1] 5 times, sl M, [p3, k3] 4 times, p 0(2).

Repeat these 4 rows until ribbing measures  $2\frac{1}{2}$ " [6.5 cm], ending after a right side row.

These last 4 rows also set Double Moss st pattern.

**Next Row:** (inc row) Work Double Moss st to next marker, sl M,

k1, [inc one st in next st purlwise] twice, k3, p1, [inc one st in next st purlwise] 7 times, p1, k3, [inc one st in next st purlwise] twice, p1, PM, k3, p 0(2) - 45(47) sts.

Now set patterns as follows:

**Row 1:** (right side) K 0(2), p3, sl M, work Row 1 of Cable Panel to next marker, sl M, work Double Moss st to end.

**Row 2:** Work Double Moss st to first M, sl M, work Row 2 of Cable Panel to next marker, sl M, k3, p 0(2).

\*\*\*Cable Panel is now set between markers with Double Moss st over front 10 sts for band and rem sts in pattern as set.

Now work from \*\* to \*\* as given for Back. \*\*\*

**To Shape Armhole:**

**Next Row:** (right side) Cast off 3(4) sts, work in pattern to end - 42(43) sts.

**Next Row:** Work in pattern to end.

Repeat these last 2 rows once more - 39(39) sts.

**Next Row:** K1, ssk, work in pattern to end.

**Next Row:** Work in pattern to end.

Repeat these last 2 rows twice (once) more - 36(37) sts.

Now work even in patterns until armhole measures  $2\frac{3}{4}(2\frac{1}{2})$ " [7(6.5) cm], ending after a right side row.

**To Shape Front Neck:**

**Next Row:** Cast off 11 sts, work in pattern to end - 25(26) sts.

**Next Row:** Work in pattern to end.

**Next Row:** Cast off 3 sts, work in pattern to end - 22(23) sts.

Now keeping pattern correct, dec one st at end of next row (right side), then every alternate row twice more - 19(20) sts.

Continue even in pattern until armhole measures  $4\frac{3}{4}(5)$ " [12(12.5) cm], ending after a wrong side row.

**To Shape Shoulder:** Keeping pattern correct, cast off 7(8) sts at beg of next row, then cast off 6 sts at beg of each right side row following twice more.

Fasten off.

**Right Front:** Cast on 34(36) sts. Now work ribbing and Double Moss front band as follows:

**Row 1:** (right side) [K1, p1] 5 times (these 10 sts are for front band), PM,

[k3, p3] 4 times, k 0(2).

**Row 2:** P 0(2), [k3, p3] 4 times, sl M, [k1, p1] 5 times.

**Row 3:** [P1, k1] 5 times, sl M,

[k3, p3] 4 times, k 0(2).

**Row 4:** P 0(2), [k3, p3] 4 times, sl M, [p1, k1] 5 times.

Repeat these 4 rows until ribbing measures  $2\frac{1}{2}$ " [6.5 cm], ending after a right side row.

These last 4 rows also set Double Moss st pattern.

**Next Row:** (inc row) P 0(2), k3, PM, k1, [inc one st in next st purlwise] twice, k3, p1, [inc one st in next st purlwise] 7 times, p1, k3, [inc one st in next st purlwise] twice, k1, sl M, work Double Moss st to end - 45(47) sts.

Now set patterns as follows:

**Row 1:** (right side) Work Double Moss st to first marker, sl M,

work Row 1 of Cable Panel to next marker, sl M, p3, k 0(2).

**Row 2:** P 0(2), k3, sl M, work Row 2 of Cable Panel to next marker, sl M, work Double Moss st to end.

Now work from \*\*\* to \*\*\* as given for Left Front, but ending after a right side row before starting armhole.

**To Shape Armhole:**

**Next Row:** (wrong side) Cast off 3(4) sts, work in pattern to end - 42(43) sts.

**Next Row:** Work in pattern to end.

Repeat these last 2 rows once more - 39(39) sts.

**Next Row:** (wrong side) P1, p2tog, work in pattern to end.

**Next Row:** Work in pattern to end.

Repeat these last 2 rows twice (once) more - 36(37) sts.

Now work even in patterns until armhole measures  $2\frac{3}{4}(2\frac{1}{2})$ " [7(6.5) cm], ending after a wrong side row.

**To Shape Front Neck:**

**Next Row:** Cast off 11 sts, work in pattern to end - 25(26) sts.

**Next Row:** Work in pattern to end.

**Next Row:** Cast off 3 sts, work in pattern to end - 22(23) sts.



**Next Row:** Work in pattern to end.

Now keeping pattern correct, dec one st at beg of next row (right side), then every alternate row twice more - 19(20) sts.

Continue even in pattern until armhole measures  $4\frac{3}{4}(5)$ " [1(12.5) cm], ending after a right side row.

**To Shape Shoulder:** Keeping pattern correct, cast off 7(8) sts at beg of next row, then cast off 6 sts at beg of each wrong side row following twice more. Fasten off.

Sew both shoulder seams.

### Sleeves:

Cast on 31 sts and work in ribbing as follows:

**Row 1:** (right side) K2, \*p3, k3; rep from \* to last 5 sts, p3, k2.

**Row 2:** P2, \*k3, p3; rep from \* to last 5 sts, k3, p2. Repeat these 2 rows until ribbing measures 4" [10 cm], ending after a Row 1.

**Next Row:** (inc row) P2, k3, PM, p1, [inc one st in next st purlwise] twice, k3, p1, [inc one st in next st purlwise] 7 times, p1, k3, [inc one st in next st purlwise] twice, p1, PM, k3, p2 - 42 sts.

Now set patterns as follows:

**Row 1:** [K1, p1] twice, k1, sl M, work Row 1 of Cable Panel to next marker, sl M, k1, [p1, k1] twice.

**Row 2:** [P1, k1] twice, p1, sl M, work Row 2 of Cable Panel to next marker, sl M, p1, [k1, p1] twice.

**Row 3:** [P1, k1] twice, p1, sl M, work Row 3 of Cable Panel to next marker, sl M, p1, [k1, p1] twice.

**Row 4:** [K1, p1] twice, k1, sl M, work Row 4 of Cable Panel to next marker, sl M, k1, [p1, k1] twice.

Cable Panel is now set between markers and sts outside markers are in Double Moss st.

Now continue in patterns, AND AT THE SAME TIME, inc one st at each end of the next row, then every 8th row following until there are 52(56) sts on the needle, taking inc sts into Double Moss st as they become available.

Work even in patterns until sleeve measures  $12\frac{1}{2}(13\frac{1}{2})$ " [31.5(34) cm] from cast on edge, ending after a right side row.

**To Shape Cap:** Keeping patterns correct, cast off 3(4) sts at beg of next 4 rows - 40(40) sts.

Now cast off 2 sts at beg of every row following (slipping first st on every row snugly), until 8 sts rem. Cast off rem sts.

**Collar:** With right side facing, beg at center of right front band, pick up and k 24(28) sts up right side of front neck, k sts from back st holder inc one st in center, pick up and k 24(28) sts down left side of front neck, ending at center of left front band - 74(82) sts.

**Next Row:** K2, \*p2, k2; rep from \* to end.

**Next Row:** P2, \*k2, p2; rep from \* to end.

Repeat these 2 rows of ribbing until collar measures 4" [10 cm]. Cast off in rib.

**To Complete:** Fold sleeves in half lengthwise and pin a fold to each shoulder seam. Sew sleeves in place, easing to fit armholes.

Sew side and sleeves seams.

Fold cuff on each sleeve back.

**Button Loop:** (make 3)

Leaving a long tail, cast on 12 sts. Cast off knitwise. Cut yarn leaving a long tail for sewing.

Place markers for placement of loops along left front edge, to inside of front band, having one  $1\frac{1}{2}$ " below neck edge, then the second  $3\frac{1}{2}$ " [9 cm] below the first marker; and finally the third  $3\frac{1}{2}$ " [9 cm] below the second marker.

Fold a button loop in half and sew in place at each marker securely.

**Button Tie:** (make 3) Using a crochet hook (any size), make a chain 5" [12.5 cm] long. Break yarn and fasten off, leaving a long tail for sewing. Thread Tie through both holes in button, bringing the ends tog. Now sew each button tie in place along right front edge, to inside of front band and opposite each Button Loop.

Thread a button through each loop to close.

Every effort has been made to have the directions contained in this pattern accurate and complete; however, we cannot be responsible for misinterpretation or errors of workmanship.

Reproduction of this pattern in any form, is protected by copyright. Any infringement will lead to prosecution.

mary maxim

2001 HOLLAND AVE., PORT HURON, MI 48060  
75 SCOTT AVE., PARIS, ONTARIO, CANADA N3L 3G5

Yarn Imported