

# PREMIUM WATERBORNE IMPREGNATING SEALER

## PREVIOUSLY KNOWN AS STAIN-PROOF™ WATERBORNE

Sealing technology designed to seal a wide range of stone and masonry surfaces, including granite, travertine, limestone and marble. Premium Waterborne Impregnating Sealer protects against staining from oils and other contaminants while providing long-lasting water repellency.



### PREVIOUS PACKAGING



## TYPICAL APPLICATIONS

Premium Waterborne Impregnating Sealer can be used for a wide variety of indoor and outdoor applications in residential and commercial buildings, including: building facades, floors, walls, countertops, showers, swimming pool surrounds, patios, garages, kitchens and entertaining areas.

## BENEFITS

- Short dwell time for quicker application
- Will not darken appearance of substrate -retains the natural color and finish of the surface.
- Permanently bonds to surface.
- Oil and water repellency for stain protection.
- Superior penetration, breathability, and alkali resistance.

## STORAGE

Keep container closed. IN CASE OF Fire: Use alcohol resistant foam or normal protein foam for extinction.

## DISPOSAL

Dispose of contents in accordance with applicable local/national/ regional/international regulations. .

## CONTENTS

Silicone, fluoroacrylate, water.

## VOC CONTENT

VOC (CALCULATED): < 100g/L

## PACK SIZE

32 fl OZ/.95L | 180112  
1 Gallon/3.79 L | 180133

## HOW TO USE

1. **TEST PRODUCT ON A SMALL, INCONSPICUOUS AREA FIRST. Allow a 24-hour cure time to determine the ease of application and desired results**
2. Apply when surface temperature is between 40 - 95°F (5 - 35°C). Surface must be dry, clean and free of residues
3. DO NOT thin product.
4. Generously apply STAIN-PROOF™ Waterborne Premium Impregnating Sealer using a roller, lambswool or microfiber applicator.
5. Using a white terry cloth towel, remove all excess sealer within 10 minutes or before it complete dries.
6. For second coat, repeat steps 4 and 5 until surface is adequately sealed, usually after 1-2 coat, depending on surface absorption. Avoid contact with surrounding areas. Total application rate is approximately one quart per 20 to 250 sq. ft. (one liter per 2 to 25 sqm), depending on surface absorption. Visit stain-proof.com for our coverage chart
7. After the final coat, wait approximately 10 minutes and remove excess and buff surface with clean, dry white terry cloth or microfiber towels. Avoid moisture contact with the surface for 24 hours after application.
8. Use water to clean equipment

**NOTE:** Sealer will NOT prevent surface etching, scuff marks or wear. Spills should be cleaned up immediately to minimize absorption. For more information, view our maintenance guide on stain-proof.com.

## COUNTRY OF MANUFACTURE

Made in USA with globally sourced materials.

## WARRANTY



\*A 10-YEAR PERFORMANCE WARRANTY is offered when product applied by an Accredited Applicator following our written instructions and surface is maintained regularly using our written maintenance system, as outlined in our warranty document. Visit our website at [www.stain-proof.com](http://www.stain-proof.com) to find your nearest accredited applicator.



FOR MORE INGREDIENT INFORMATION, TECHNICAL DOCS, APPLICATION TIPS & COVERAGE GUIDE, SCAN THIS CODE OR VISIT: [STAIN-PROOF.COM](http://STAIN-PROOF.COM)



150 Dascomb Rd,  
Andover, MA 01810  
USA  
1866 667 5119

30-32 Assembly Drive  
Tullamarine, Vic, 3043  
Australia  
1800 786 617

## FIRST AID

If exposed or concerned get medical advice. IF ON SKIN: Wash with plenty of soap and water. IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing has stopped give artificial respiration. IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Contents: Silicone, fluoroacrylate, water.

## CAUTIONS

**WARNING:** Causes serious eye irritation. May cause an allergic skin reaction. Harmful to aquatic life. **PRECAUTIONS:** Do not handle until all safety precautions have been read and understood. Avoid breathing mist/vapours/spray. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. KEEP OUT OF REACH OF CHILDREN.



150 Dascomb Rd,  
Andover, MA 01810  
USA  
1866 667 5119

30-32 Assembly Drive  
Tullamarine, Vic, 3043  
Australia  
1800 786 617