

DENSE STONE IMPREGNATING SEALER

PREVIOUSLY KNOWN AS STAIN-PROOF PLUS™

Dense Stone Impregnating Sealer is an impregnating, invisible and breathable sealer that protects natural stone countertops from damage caused by water, salts and oil-based stains. Treated countertop surfaces are easier to clean and maintain, and will help to preserve the stone's natural beauty. Dense Stone Impregnating Sealer provides lasting protection for natural stone that comes with a 25 year Performance Warranty*.



TYPICAL APPLICATIONS

Dense Stone Impregnating Sealer is suitable for natural stone, concrete countertops, mosaic, stone tiles & natural stone showers.

BENEFITS

- The next generation sealer, optimized for dense natural stone
- Long lasting premium oil and water repellence. 25-year written performance warranty when applied by an Accredited Applicator
- Three different custom sealing molecules for 3 levels of penetration and maximum stain repellence
- Includes a super penetrator for deep penetration of dense granites and marbles
- Retains natural surface color and finish
- Super breathable: water vapor escapes freely preventing harmful moisture build-up inside the treated material
- Suitable for indoor, outdoor, residential and commercial use

VOC CONTENT

VOC (CALCULATED): < 570g/L

CONTENTS

Ethanol, silane, fluoropolymer.

PACK SIZE

16 fl OZ / .47L | 110712

HOW TO USE

1. **ALWAYS TEST PRODUCT ON A SMALL AREA FIRST and allow a 24-hour cure time to determine the ease of application and desired results.**
2. Apply when surface temperature is between 40 - 95°F (5 - 35°C). Ensure surfaces to be treated are dry, clean and free of residues.
3. DO NOT thin product.
4. Generously apply STAIN-PROOF™ Dense Stone Impregnating Sealer using a low pressure hand sprayer, a clean brush or lamb's wool applicator. Surface should have a mirror like 'wet' look for 3-5 seconds. Avoid contact with surrounding areas.
5. Wait for approximately 10 minutes but before the surface dries, repeat Step 4. Total application rate is approximately one pint for up to 75 sq.ft. (half liter per 7 square meters), depending on surface absorption. Visit stain-proof.com for our coverage chart.
6. After the final coat, wait approximately 10 minutes but, before the surface dries, polish with a clean dry white cloth to remove excess product, moistening cloth with STAIN-PROOF™ Dense Stone Impregnating Sealer to ease polishing.
7. Use an organic solvent e.g. methylated spirits to clean equipment.
8. Avoid moisture contact with the surface for six hours after application. Surface may be used after 24 hours with full cure up to 4 weeks.

NOTE: Sealer will not prevent surface etching, scuff marks or wear and may lighten or darken some surfaces. STAIN-PROOF Dense Stone Impregnating Sealer will make the maintenance and cleaning of a treated surface much easier. Once cured, this product is food contact safe. Spills should be cleaned up immediately to minimize absorption.

COUNTRY OF MANUFACTURE

Made in the USA with globally sourced materials.

WARRANTY



*A 25-YEAR PERFORMANCE WARRANTY is offered when product is applied by an Accredited Applicator following our written instructions and surface is maintained regularly using our written maintenance system, as outlined in our warranty document. Visit our website at www.stain-proof.com to find your nearest accredited applicator.



FOR MORE INGREDIENT INFORMATION, TECHNICAL DOCS, APPLICATION TIPS & COVERAGE GUIDE, SCAN THIS CODE OR VISIT: STAIN-PROOF.COM



150 Dascomb Rd,
Andover, MA 01810
USA
1866 667 5119

30-32 Assembly Drive
Tullamarine, Vic, 3043
Australia
1800 786 617

STORAGE

Keep container tightly sealed in a cool, well ventilated place. It is recommended that this product is best used within seven days of opening to avoid possible spoilage.

DISPOSAL

Dispose of contents in accordance with applicable local/national/regional/international regulations.

CAUTION

DANGER: Highly flammable liquid or vapor. Harmful if inhaled. Causes skin irritation. Causes serious eye irritation. Harmful to aquatic life. **PRECAUTIONS:** Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources- No Smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Keep container tightly closed. Wear protective gloves/protective clothing/eye protection/face protection. **KEEP OUT OF REACH OF CHILDREN.**

FIRST AID

If exposed or concerned seek medical advice. **IF ON SKIN:** Take off immediately all contaminated clothing. Rinse skin with water/shower. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. **IF SWALLOWED:** Call a poison center/physician if you feel unwell.

COVERAGE GUIDE

Surface Type	sq ft/qt**	m ² /L**
Basalt - Dense (European)	120	12
Bluestone (Australian Basalt)	100	10
Bluestone (USA Boston Bluestone)	60	6
Brick	60	6
Poured Concrete - Smooth	75	7.5
Poured Concrete	70	7
Concrete Paver (dry pressed)	40	4
Concrete Paver (wet cast)	70	7
Coral Stone	50	5
Granite Flamed	60	6
Granite Honed	80	8
Granite Polished	120	12
Limestone Honed - Dense	70	7
Limestone Polished	100	10
Marble Honed	100	10
Marble Polished	150	15
Quartzite	100	10
Saltillo	50	5
Sandstone (Indian, hard)	70	7
Sandstone (soft)	40	4
Slate - Dense black	120	12
Slate	70	7
Terracotta dense	70	7
Terracotta porous	50	5
Terrazzo	100	10
Travertine honed	70	7
Travertine polished	100	10

** Minimum Coverage rates as each surface has different absorption rates. Check with your supplier



150 Dascomb Rd,
Andover, MA 01810
USA
1866 667 5119

30-32 Assembly Drive
Tullamarine, Vic, 3043
Australia
1800 786 617