

Page: 1/12

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

1 Identification

· Product identifier

· Trade name: Cavity Wax Spray

· Other means of identification: No other identifiers

· Recommended use and restriction on use

· Recommended use: Coating material

· Restrictions on use: No relevant information available.

Details of the supplier of the Safety Data Sheet

Manufacturer/Supplier:

FERTAN LLC

12485 S West 137th Avenue, Suite 212

Miami, FL 33186

USA

(305) 614-1140

contact@fertanusa.com http://www.fertanusa.com

· Emergency telephone number:

ChemTel Inc.

(800)255-3924 (North America)

+1 (813)248-0585 (International)

2 Hazard(s) identification

· Classification of the substance or mixture

Flam. Aerosol 1 H222 Extremely flammable aerosol.

Press. Gas H280 Contains gas under pressure; may explode if heated.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS).

· Hazard pictograms:







GHS02 GHS04 GHS07

· Signal word: Danger

· Hazard statements:

H222 Extremely flammable aerosol.

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

· Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P211 Do not spray on an open flame or other ignition source.

(Cont'd. on page 2)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 1)

P251 Pressurized container: Do not pierce or burn, even after use.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection.

P302+P352 If on skin: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

Other hazards There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Components:		
64742-95-6	Solvent naphtha (petroleum), light arom. Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315; STOT SE 3, H336	20-60%
106-97-8	Butane Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	10-40%
74-98-6	Propane Flam. Gas 1, H220 Press. Gas, H280 Simple Asphyxiant	10-40%
64742-48-9	Naphtha (petroleum), hydrotreated heavy Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H336	10-40%
8002-74-2	Paraffin waxes and Hydrocarbon waxes	2.5-10%
64742-95-6	Hydrocarbons,C9,aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335-H336	2.5-10%

Additional information:

For the listed ingredient(s), the identity and/or exact percentage(s) are being withheld as a trade secret. For the wording of the listed Hazard Statements, refer to section 16.

4 First-aid measures

(Cont'd. on page 3)



Page: 3/12

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 2)

Description of first aid measures

After inhalation:

Supply fresh air.

Provide oxygen treatment if affected person has difficulty breathing.

Seek medical help for symptoms or if unconscious.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Do not pull solidified product away from the skin.

Wash with soap and water.

Seek medical treatment in case of complaints.

· After eye contact:

Remove contact lenses if worn.

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing:

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; immediately call for medical help.

A person vomiting while lying on their back should be turned onto their side.

Most important symptoms and effects, both acute and delayed:

Breathing difficulty

Dizziness

Coughing

Irritant to skin and mucous membranes.

Mechanical irritation to eyes.

Gastric or intestinal disorders when ingested.

· Danger:

Danger of impaired breathing.

May cause drowsiness or dizziness.

· Indication of any immediate medical attention and special treatment needed:

If swallowed, gastric irrigation with added, activated carbon.

If necessary oxygen respiration treatment.

Later observation for pneumonia and pulmonary edema.

If medical advice is needed, have product container or label at hand.

5 Fire-fighting measures

Extinguishing media

Suitable extinguishing agents:

Foam

Carbon dioxide

Gaseous extinguishing agents

Fire-extinguishing powder

Water fog / haze

For safety reasons unsuitable extinguishing agents:

Water stream.

Water spray

Special hazards arising from the substance or mixture

Highly flammable liquid and vapor.

Formation of toxic gases is possible during heating or in case of fire.

Advice for firefighters

(Cont'd. on page 4)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

· Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

Additional information:

Eliminate all ignition sources if safe to do so.

Cool endangered containers with water fog.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.

Keep away from ignition sources.

For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.

Wear protective clothing.

Environmental precautions

Do not allow to enter sewers/ surface or ground water.

In case of gas release or seepage into the ground inform responsible authorities.

· Methods and material for containment and cleaning up

Allow to solidify. Pick up mechanically.

Absorb with non-combustible liquid-binding material (sand, diatomite, acid binders, universal binders).

Send for recovery or disposal in suitable receptacles.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling

Precautions for safe handling:

Avoid splashes or spray in enclosed areas.

Use only in well ventilated areas.

Avoid breathing mist, vapors, or spray.

Avoid contact with the eyes and skin.

· Information about protection against explosions and fires:

Extremely flammable aerosol.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Fumes can combine with air to form an explosive mixture.

· Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles:

Avoid storage near extreme heat, ignition sources or open flame.

Observe official regulations on storing packagings with pressurized containers.

Information about storage in one common storage facility:

Store away from foodstuffs.

Store away from oxidizing agents.

Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the container bursting.

(Cont'd. on page 5)

(Cont'd. of page 3)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 4)

· Specific end use(s) No relevant information available.

8 Exposure controls/personal protection

· Control parameters

<u> </u>					
•	· Components with limit values that require monitoring at the workplace:				
106-97-8 Butane					
REL (USA)	Long-term value: 1900 mg/m³, 800 ppm				
TLV (USA)	Short-term value: 2370 mg/m³, 1000 ppm (EX)				
EL (Canada)	Short-term value: 750 ppm Long-term value: 600 ppm				
EV (Canada)	Long-term value: 800 ppm revoked as of 01/01/18				
LMPE (Mexico)	Long-term value: 1000 ppm				
74-98-6 Propan	ie e				
PEL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
REL (USA)	Long-term value: 1800 mg/m³, 1000 ppm				
TLV (USA)	refer to Appendix F inTLVs&BEIs book; D, EX				
EL (Canada)	Long-term value: 1000 ppm				
EV (Canada)	Long-term value: 1,000 ppm revoked as of 01/01/18				
LMPE (Mexico)	Long-term value: 1000 ppm				
8002-74-2 Para	ffin waxes and Hydrocarbon waxes				
REL (USA)	Long-term value: 2 mg/m³				
TLV (USA)	Long-term value: 2 mg/m³				
EL (Canada)	Long-term value: 2 mg/m³				
EV (Canada)	Long-term value: 2 mg/m³ fume				
LMPE (Mexico)	Long-term value: 2 mg/m³				

• Exposure controls

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

- Engineering controls: Provide adequate ventilation.
- · Breathing equipment: Suitable respiratory protective device recommended.
- Protection of hands:



(Cont'd. on page 6)



(Cont'd. of page 5)



Safety Data Sheet

according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

· Material of gloves

Butyl rubber, BR Neoprene gloves

Eye protection:



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

- · Body protection: Solvent resistant protective clothing
- Limitation and supervision of exposure into the environment No relevant information available.
- · Risk management measures No relevant information available.

Information on basic physical a	nd chemical properties
Appearance:	
Form:	Aerosol
Color:	Transparent
Odor:	Characteristic
Odor threshold:	Not determined.
pH-value:	Not determined.
Melting point/Melting range:	Not determined.
Boiling point/Boiling range:	Not applicable, as aerosol.
Flash point:	Not applicable, as aerosol.
Flammability (solid, gaseous):	Extremely flammable aerosol.
Auto-ignition temperature:	Not determined.
Decomposition temperature:	Not determined.
Danger of explosion:	Product is not explosive. However, formation of explosive a vapor mixtures are possible.
Explosion limits	
Lower:	0.5 Vol %
Upper:	10.9 Vol %
Oxidizing properties:	Not determined.
Vapor pressure at 20 °C (68 °F):	400 kPa
Density:	
Relative density:	0.67
Vapor density:	Not determined.
Evaporation rate:	Not determined.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 6)

· Viscosity

Dynamic: Not determined. Kinematic at 40 °C (104 °F): 23 mm²/s (liquid)

VOC content: 87.6 %

• Other information No relevant information available.

10 Stability and reactivity

- · Reactivity: No relevant information available.
- · Chemical stability: Stable under normal temperatures and pressures.
- Thermal decomposition / conditions to be avoided:

Danger of receptacles bursting because of high vapor pressure if heated.

No decomposition if used and stored according to specifications.

· Possibility of hazardous reactions

Extremely flammable aerosol.

Can form explosive mixtures in air if heated above flash point and/or when sprayed or atomized.

Toxic fumes may be released if heated above the decomposition point.

Reacts with oxidizing agents.

- · Conditions to avoid Excessive heat.
- · Incompatible materials Oxidizers
- · Hazardous decomposition products

Under fire conditions only:

Carbon monoxide and carbon dioxide

Sulfur oxides (SOx)

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

Acute toxicity.				
· LD/LC50 values that are relevant for classification:				
64742-95-6 Solvent naphtha (petroleum), light arom.				
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		
64742-4	64742-48-9 Naphtha (petroleum), hydrotreated heavy			
Oral	LD50	>5,000 mg/kg (rat)		
Dermal	LD50	>3,000 mg/kg (rabbit)		
64742-9	64742-95-6 Hydrocarbons,C9,aromatics			
Oral	LD50	>6,800 mg/kg (rat)		
Dermal	LD50	>3,400 mg/kg (rab)		

- · Primary irritant effect:
- · On the skin: Irritant to skin and mucous membranes.
- · On the eye: Mechanical irritation only.
- · Sensitization: Based on available data, the classification criteria are not met.

(Cont'd. on page 8)





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 7)

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

· NTP (National Toxicology Program):

None of the ingredients are listed.

· OSHA-Ca (Occupational Safety & Health Administration):

None of the ingredients are listed.

Probable route(s) of exposure:

Inhalation.

Eye contact.

Skin contact.

· Acute effects (acute toxicity, irritation and corrosivity):

Vapors have narcotic effect.

Irritating to skin.

- · Repeated dose toxicity: No relevant information available.
- · Germ cell mutagenicity: Based on available data, the classification criteria are not met.
- · Carcinogenicity: Based on available data, the classification criteria are not met.
- · Reproductive toxicity: Based on available data, the classification criteria are not met.
- STOT-single exposure: May cause drowsiness or dizziness.
- STOT-repeated exposure: Based on available data, the classification criteria are not met.
- · **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

- · Toxicity
- · Aquatic toxicity The product contains materials that are harmful to the environment.
- · Persistence and degradability No relevant information available.
- · Bioaccumulative potential: No relevant information available.
- Mobility in soil: No relevant information available.
- · Ecotoxical effects:
- · Remark: Due to mechanical actions of the product (e.g. agglutinations), damages may occur.
- Additional ecological information
- General notes:

Do not allow product to reach ground water, water course or sewage system.

Due to available data on eliminability/decomposition and bioaccumulation potential prolonged term damage of the environment can not be excluded.

· Other adverse effects No relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Contact waste processors for recycling information.

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes. Residual materials should be treated as hazardous.

(Cont'd. on page 9)





Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 8)

- · Uncleaned packagings · Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR/RID/ADN, IMDG, IATA	UN1950
UN proper shipping name	
DOT ADR/RID/ADN, IMDG	Aerosols AEROSOLS
IATA	Aerosols, flammable
Transport hazard class(es)	
рот	
Class	2.1
Label	2.1
ADR/RID/ADN	
Class	2 5F
Label	2.1
IMDG, IATA	
Class	2.1
Label	2.1
Packing group	Aerosols are not assigned a packing group.
Environmental hazards	Product contains environmentally hazardous substances: Hydrocarbons, C9, aromatics
Marine pollutant:	Substances. Trydrocarbons, 09, aromatics
Yes	
Special precautions for user	Warning: Gases
Danger code (Kemler): EMS Number:	- F-D,S-U





according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 9)

- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.
- Transport/Additional information:
- DOT



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· ADR/RID/ADN



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

· IMDG



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

·IATA



Limited Quantity for packages less than 30 kg gross and inner packagings less than 1 L.

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · United States (USA)
- ·SARA
- Section 302 (extremely hazardous substances):

None of the ingredients are listed.

Section 355 (extremely hazardous substances):

None of the ingredients are listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients are listed.

TSCA (Toxic Substances Control Act)

All ingredients are listed or exempt.

· Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130):

106-97-8	Butane	10000
	Propane	10000

· Proposition 65 (California)

(Cont'd. on page 11)



according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 10)

Page: 11/12

· Chemicals known to cause cancer:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· EPA (Environmental Protection Agency):

None of the ingredients are listed.

· IARC (International Agency for Research on Cancer):

None of the ingredients are listed.

Canadian Domestic Substances List (DSL):

All ingredients listed on DSL or NDSL.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Abbreviations and acronyms:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

OSHA: Occupational Safety & Health Administration

Flam. Gas 1: Flammable gases – Category 1

Flam. Aerosol 1: Aerosols - Category 1

Press. Gas: Gases under pressure - Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Skin Irrit. 2: Skin corrosion/irritation - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

1305 North Florida Avenue

Tampa, Florida USA 33602-2902

(Cont'd. on page 12)





Safety Data Sheet according to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 Regulations

Revision: October 14, 2019

Trade name: Cavity Wax Spray

(Cont'd. of page 11)

Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573 Website: www.chemtelinc.com