



Product name \*

## Universal 3-jaw puller with narrow, quick adjusting jaws

For removing bearings, gears, discs, etc. for tight or difficult-to-access spaces.

Art. No. 30-2+S

Series 30+S

EAN 4021176757051



	Technical attribute	Metric	Imperial
	Spread	35 - 160 mm	1 3/8 - 6 3/8 inch
	Depth	150 mm	5 7/8 inch
	Spread used internal	100 - 220 mm	3 7/8 - 8 5/8 inch
	Hexagon drive (male)	22 mm	
	max. Maximum load	5 t	5.5 US t
	max. Maximum torque	120 Nm	88.5 ft lb
	Weight	3.785 kg	
	Space below	4 mm	3/16 inch
	Space next to it	19 mm	3/4 inch
	Number of jaws	3	3




## Technologies



### GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



### ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



### QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



### SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



## Spare part

<b>Art. No.</b>	<b>Product name</b>
621220	Mechanical pressure spindle.
2-153-S	3 narrow, quick adjusting jaws (set)
30-2-T	3-jaw cross bar

## Accessories

<b>Art. No.</b>	<b>Product name</b>
2-303-S	3 narrow, quick adjusting jaws (set)
2-V-150-S	3 jaw extensions (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws

## Part of

<b>Art. No.</b>	<b>Product name</b>
EVLW-2-INDUSTRIE	Display