



Product name

Universal 3-jaw puller with quick adjusting jaws

For removing bearings, gears, discs, etc.

Art. No. 30-2+

Series 30+

EAN 4021176731631



	Technical attribute	Metric	Imperial
Ü	Spread	35 - 160 mm	1 3/8 - 6 3/8 inch
	Depth	150 mm	5 7/8 inch
Ħ	Spread used internal	100 - 220 mm	3 7/8 - 8 5/8 inch
	Hexagon drive (male)	22 mm	
max.	Maximum load	7 t	7.5 US t
max.	Maximum torque	150 Nm	110.5 ft lb
Δ,Ω	Weight	3.8 kg	
± •	Space below	9 mm	3/8 inch
→ +- 	Space next to it	40 mm	1 5/8 inch
×	Number of jaws	3	3

30-2+ Product data sheet www.kukko.com



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
621220	Mechanical pressure spindle.
2-152-S	3 quick adjusting jaws (set)
30-2-T	3-jaw cross bar

Accessories

Art. No.	Product name
2-152-S	3 quick adjusting jaws (set)
2-302-S	3 pulling arms (set)
2-V-150-S	3 jaw extensions (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws

Also included in

Art. No.	Product name
WT-002	Puller product range - hydraulic exterior pulling - TOP
WT-003	Puller product range - exterior pulling - BASIC

30-2+ Product data sheet www.kukko.com