



Product name

Universal 3-jaw puller with quick adjusting jaws

For removing bearings, gears, discs, etc.

Art. No. 30-3+

Series 30+

EAN 4021176731891



	Technical attribute	Metric	Imperial
	Spread	46 - 250 mm	1 7/8 - 9 7/8 inch
	Depth	200 mm	7 7/8 inch
	Spread used internal	180 - 340 mm	7 1/8 - 13 3/8 inch
	Hexagon drive (male)	27 mm	
	Maximum load	10 t	11 US t
	Maximum torque	250 Nm	184 ft lb
	Weight	8.8 kg	
	Space below	20 mm	3/4 inch
	Space next to it	67 mm	2 5/8 inch
	Number of jaws	3	3



Technologies



GLIDE & FIX

The improved geometry guarantees quick and easy movement of the jaws on the cross-beam.



ARMLOCK

The cross-legged jaws guarantee maximum stability for suspending the jaws in the slider.



QUICK ADJUST

The knurls allow the jaws to be quickly released and moved on the cross-beam without the need for tools.



SWITCH

A two-sided spindle tip provides optimal adjustment of the spindle to the shaft.



Spare part

Art. No.	Product name
626300	Mechanical pressure spindle.
3-202-S	3 quick adjusting jaws (set)
30-3-T	3-jaw cross bar

Accessories

Art. No.	Product name
9-1	Auxiliary hydraulic ram
9-2	Auxiliary hydraulic ram
9-3	Auxiliary hydraulic ram
3-202-S	3 quick adjusting jaws (set)
3-302-S	3 quick adjusting jaws (set)
3-402-S	3 quick adjusting jaws (set)
3-502-S	3 quick adjusting jaws (set)
K-600-025	Set of interchangeable pressure pads for KUKKO pressure screws



Also included in

Art. No.

Product name

WT-010

Puller product range - commercial vehicles - TOP