

WAVE 5000 - NEXT 5kW FM TRANSMITTER COMPACT VERSION



Prognostics

Analysis for predictive maintenance

Easy Care

Hot pluggable PSU - Easy to replace fans
Redundant power supply option

Controls

LCD display, Web server and SNMP

Integrated unique features

Micro SD card slot
FM, Satellite and Terrestrial receiver

Advanced Efficiency Boost

Efficiency over 75% with adaptive optimization

Digital Processing

Unique performances thanks to DDS digital modulator

Stereo & Soft clipper

Always included

Audio processor
Full telemetry with 3G/4G connection

This manual provides important guidelines for installing. Review this information carefully for proper installation. Both unit specifications and manual contents are subject to change without notice.

NEXT 5kW FM TRANSMITTER



GENERAL SPECIFICATION

Output frequency range	87.5 to 108MHz in 1Hz steps
Output Power	5kW (tol. +0/-0.5dB)
Output connector	EIA 7/8" flange
Spurious and harmonic suppression	Compliant with ETSI and FCC specification
Analog input	2x XLR female (Balanced; impedance 600Ω/10KΩ selectable)
MPX/SCA/RDS input	2x BNC female (Unbalanced; impedance 50Ω/10KΩ selectable)
Soft Clipper with band limitation	Included
Power consumption	Typ. 6,9kVA - Max. <7,5kVA
AEB - Advanced Efficiency Boost	Included
AC Input voltage and frequency	176-264Vac 230Vac, 47 to 63Hz single phase 400Vac three phase star conn. (with power neutral) and 230Vac three phase. delta conn. (without power neutral)
AC/DC Power Supplies	N.3 fully redundant power supplies, hot pluggable from the front panel
Operative temperature & fans	-5°C to +45°C @MSL. N.2 fans on the rear panel
Maximum operative altitude	3000m ASL. For higher altitudes please contact our sales dept.
Maximum operative humidity	95% non-condensing
Housing	Rack drawer 19" 4U, depth 70cm
Weight	<30Kg



SOFTWARE OPTIONS

S-AM-UN	Audio monitor for input or on-air signal + test tone generator
S-SD-UN	Micro SD card slot
S-AES-UN	Digital AES/EBU & AES192 (MPX over AES) inputs
S-FMRX-UN	FM receiver input (for regenerative FM repeater/ translator)
S-SWI-UN	Automatic input switching (n.3 MPX profiles – audio/ RDS)
S-RDS-UN	Static RDS coder
S-IP-UN	IP input (Icecast2 streaming & AES67)
S-DMPX-UN	Digital MPX over TS & Digital MPX over IP in/out
S-RDS+-UN	Dynamic RDS
S-ISO-UN	SFN/ Isofrequency operation
S-AP-DEL	Delossifier
S-AP-ARDS	Advanced RDS

Included in
S-FULL-UN

Only
with
H-AP

HARDWARE OPTIONS

H-SAT	Embedded Satellite receiver demodulator. DVB-S/S2 (L-band input) Low Symbol Rate with loop
H-SATDTT	Embedded Satellite and Terrestrial receiver demodulator. DVB-S/S2 (L-band input) and DVB-T/T2 and ISDB-T (VHF/UHF band input)
H-3G; H-4G	2G/3G or 3G/4G modem router for remote connection/telemetry and SMS
H-I/O	GPIO interface with n.3 isolated clean contact out, n.4 optoisolated in, n.4 analog out (0 to 5V), RF filter for router
H-AP-PRO	Integrated audio processor card with professional software license
H-SATDTT2	Second Redundant Embedded Satellite and/or Terrestrial receiver demodulator with seamless switching
H-CAM	CAM Slot (Common Interface Module)
H-ASI	ASI T.S. input (or output) interface
H-REF	10MHz and 1pps inputs
H-GNS	High stability reference oscillator GNSS (GPS + GLONASS) locked, oven clock 10MHz + 1pps outputs
H-AGNS	GPS/GLONASS receiving antenna (gain 26dB typ.) + 15 meters cable

NEXT 5kW FM TRANSMITTER



The software-based audio processor can be integrated in any Wave Transmitter, from low and medium compact versions to high power line. **H-AP-PRO Audio Processor** offers outstanding audio quality and comes with many unique features.



FM Composite Clipper

Up to 140% audio level at 100% modulation gives 2-3 dB extra headroom for highs. Improve your audio, being the loudest and cleanest station on the dial!

Stereo & RDS Coder

Built-in stereo and RDS encoder
RT+

Advanced Dynamics & EQ

Increases the dynamics for music that lacks dynamics. Adjusts the spectrum without compression, making it possible to generate a very consistent sound without sounding compressed

Dehummer

Improves the sound of MPEG2/MP3 style lossy compressed files, removing unwanted constant sounds, such as a 50/60 Hz hum from bad cables

Better FM reception

Improves stereo reception area up to 30Km

Declipper & Natural Dynamics

Repairs clipped audio, removes distortion
Restores Natural Dynamics

Delossifier

Improves the sound quality of MPEG2/MP3 style lossy compressed files