PPC-300WP WASHDOWN PORTION CONTROL SCALE TAILO

Features

- Waterproof IP68/65¹
- Complete Stainless Steel Construction
- Over/Under Indicator
- Large Removable Stainless Steel Platform
- Accurate 2,000 Divisions
- Large LCD Display
- Battery or AC Operation
- Adjustable Auto Shut-off
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms
- Multiple Units
- Capacities from 22 to 44 lb (10 to 20 kg)









Model	PPC-300WP				
	Pound	Kilogram	Ounce	Pound-Ounce*	Max. Tare
					Capacity
					Capacity
PPC-300WP-22	22 lb x 0.01 lb	10 kg x 0.005 kg	352 oz x 0.2 oz	22 lb x 0.2 oz	Capacity
PPC-300WP-44	44 lb x 0.02 lb	20 kg x 0.01 kg	704 oz x 0.5 oz	44 lb x 0.5 oz	Capacity
Accuracy	Class III, 2000 divisions				
Weighing System	Strain gauge load cell				
Certificate of Conformance	08-041				
Platform	9" x 7 %" stainless steel (230 x 194 mm)				
Display	7 segment LCD single display				
Character Size	0.5" x 1.2" (13.5 x 30 mm), 5 digits				
Power	6 VDC - 4 "D" batteries or optional AC adapter				
Battery Life	1400 hours of continuous use with alkaline batteries				
Housing Material	Stainless Steel				
Operating Temperatures	14° F ~ 104° F (-10° C ~ 40° C)				
Function	Checkweighing, grading, fixed: unit toggle, function toggle				

PPC-300WP's are manufactured as IP68. If units are opened, they can be closed on-site for an IP65 rating or returned to Yamato for re-sealing to ensure continued IP68 protection. Only Yamato autho-rized technicians using Yamato approved equipment can assure the integrity of the IP68 protective seal after it has been opened; opening of this unit by anyone else will void the IP68 warran<mark>ty against internal water damage.</mark> *Combined units, such as pound-ounce, are not legal for trade

Weigh Better Solutions • Weigh Better Support

Yamato Corporation

6306 W. Eastwood Ct. Meguon, WI 53092 Tel: 262.236.0000 Fax: 262.236.0036

Yamato Corporation

20451 James Bay Circle Lake Forest, CA 92630 Tel: 800.538.1762

Yamato Scale de Mexico

Av. Dr. Gustavo Baz 191, Bodega F Col. El Mirador, CP. 54080 Tlalnepantla de Baz, Mexico Tel: 52-55-2628-6140

Form No. YSS-PPC300WP-1116-02