

Seal N Flex 1 Plus Grey Revision Number 1.02

Revision date 30-May-2022 Supersedes Date: 08-May-2022

Section 1: Identification: Product identifier and chemical identity

Product identifier

Product Name Seal N Flex 1 Plus Grey

Product Code(s) 30619339

30619339; 30619340

Other means of identification

Pure substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Recommended use Adhesives and/or sealants

Uses advised against No information available

Details of manufacturer or importer

<u>Supplier</u> <u>Manufacturer</u>

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria

Bostik Australia Pty Ltd
51-71 High Street,
Thomastown Victoria

Thomastown Victoria

Australia Australia

ABN: 79 003 893 838 **ABN**: 79 003 893 838

E-mail address au-bostik-sds@bostik.com

Emergency telephone number

Emergency telephone number 24-hr Emergency: 1800 033 111

Section 2: Hazard(s) identification

GHS Classification

Not classified

Label elements

Hazard statements

Not classified

Other hazards which do not result in classification

Causes mild skin irritation.

Australia - EN Page 1/10

Seal N Flex 1 Plus GreyRevision date30-May-2022Revision Number1.02Supersedes Date:08-May-2022

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

Section 3: Composition and information on ingredients, in accordance with Schedule 8

Substance

Not applicable

<u>Mixture</u>

Chemical name	CAS No	Weight-%
Benzenesulfonyl isocyanate, 4-methyl-	4083-64-1	<0.01
Decanedioic acid, methyl 1,2,2,6,6-pentamethyl-4-piperidinyl	82919-37-7	0 - <10
ester		
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	41556-26-7	0 - <10
Toluene-2,4-diisocyanate	584-84-9	<0.01
Toluene 2,6-diisocyanate	91-08-7	<0.01
Glycidoxypropyltrimethoxysilane	2530-83-8	0 - <10
Non-hazardous ingredients	Proprietary	Balance

Section 4: First aid measures

Emergency telephone number Poisons Information Center, Australia: 13 11 26

Poisons Information Center, New Zealand: 0800 764 766

Description of first aid measures

Inhalation Remove to fresh air.

Eye contact Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper

eyelids. Consult a physician.

Skin contact Wash skin with soap and water.

Ingestion Never give anything by mouth to an unconscious person. Do not induce vomiting without

medical advice. Get medical attention immediately if symptoms occur. Rinse mouth.

Most important symptoms and effects, both acute and delayed

Symptoms Prolonged contact may cause redness and irritation.

Indication of any immediate medical attention and special treatment needed

Note to physicians Small amounts of methanol (CAS 67-56-1) are formed by hydrolysis and released, when

the product is exposed to moisture or water.

Section 5: Firefighting measures

Suitable Extinguishing Media

surrounding environment.

Unsuitable extinguishing media No information available.

Specific hazards arising from the chemical

Australia - EN Page 2/10

Seal N Flex 1 Plus Grev Revision date 30-May-2022 **Revision Number** 1.02 Supersedes Date: 08-May-2022

Specific hazards arising from the

No information available.

chemical

Carbon oxides. Carbon dioxide (CO2). Nitrogen oxides (NOx). Hydrochloric Acid. Hazardous combustion products

Special protective actions for fire-fighters

precautions for fire-fighters

Special protective equipment and Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

Section 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Ensure adequate ventilation.

For emergency responders Use personal protection recommended in Section 8.

Environmental precautions

See Section 12 for additional Ecological Information. **Environmental precautions**

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Pick up and transfer to properly labeled containers. Methods for cleaning up

Precautions to prevent secondary hazards

Prevention of secondary hazards Clean contaminated objects and areas thoroughly observing environmental regulations.

Section 7: Handling and storage, including how the chemical may be safely used

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep container tightly closed in a dry and well-ventilated place.

Recommended storage

temperature

Keep at temperatures between 50 and 95 °F / 10 and 35 °C.

Section 8: Exposure controls and personal protection

Control parameters

Exposure Limits This product contains titanium dioxide in a non-respirable form. Inhalation of titanium

dioxide is unlikely to occur from exposure to this product.

Chemical name	Australia
Toluene-2,4-diisocyanate	TWA: 0.02 mg/m ³
584-84-9	STEL: 0.07 mg/m ³

Biological occupational exposure limits

Appropriate engineering controls

Australia - EN Page 3 / 10

Seal N Flex 1 Plus GreyRevision date30-May-2022Revision Number1.02Supersedes Date:08-May-2022

Engineering controls Showers, eyewash stations, and ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin and body protection Wear suitable protective clothing.

Hand protection Wear suitable gloves.

Respiratory protection Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases

and vapors filter conforming to EN 14387.

Environmental exposure controls No information available.

Section 9: Physical and chemical properties

Information on basic physical and chemical properties

Physical stateSolidAppearancePasteColorGrayOdorSlight

Odor threshold No information available

Property Values Remarks • Method

pH No data available
pH (as aqueous solution) No data available
Melting point / freezing point
Initial boiling point and boiling
No data available
No data available

range

Flash point > 100 °C
Evaporation rate No data available
Flammability No data available

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapor pressureNo data availableRelative vapor densityNo data available

Relative density 1.3

Water solubility Insoluble in water Product cures with

moisture

Solubility(ies)

Partition coefficient
Autoignition temperature
Decomposition temperature
Kinematic viscosity
Dynamic viscosity
Explosive properties

No data available
No data available
No data available
No data available
No information ava

Explosive propertiesNo information available **Oxidizing properties**No information available

Other information

Solid content (%)

Liquid Density

No information available
No information available

VOC Content (%) No information available

Section 10: Stability and reactivity

Australia - EN Page 4/10

Seal N Flex 1 Plus Grey
Revision Number 1.02

Reactivity

Reactivity No information available.

Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

Conditions to avoid

Conditions to avoidNone known based on information supplied.

Incompatible materials

Incompatible materials None known based on information supplied.

Hazardous decomposition products

Hazardous decomposition

products

Carbon oxides. Nitrogen oxides (NOx). Thermal decomposition can lead to release of

irritating and toxic gases and vapors.

Section 11: Toxicological information

Acute toxicity

Information on likely routes of exposure

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Specific test data for the substance or mixture is not available. Causes mild skin irritation.

Ingestion Based on available data, the classification criteria are not met.

Symptoms Prolonged contact may cause redness and irritation.

Numerical measures of toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

ATEmix (dermal) 9,996.70 ATEmix (inhalation-vapor) 33.8616 ATEmix (inhalation-dust/mist) 19.825

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Benzenesulfonyl isocyanate,	=2234 mg/kg (Rattus)	LD 50 (Rattus) > 2000 mg/kg	>640 ppm (Rattus) 1 h
4-methyl-		OECD 402	
Bis(1,2,2,6,6-pentamethyl-4-pi	=2615 mg/kg (Rattus)	-	-
peridyl) sebacate			

Australia - EN Page 5/10

Seal N Flex 1 Plus Grey Revision Number 1.02

evision Number 1.02 Supersedes Date: 08-May-2022

Toluene-2,4-diisocyanate	=5800 mg/kg (Rattus)	> 16 mL/kg (Oryctolagus	=0.107 mg/L (Rattus) 4 h	
		cuniculus)	(vapour)	
Glycidoxypropyltrimethoxysilan	=8025 mg/kg (Rattus)	= 4250 mg/kg (Oryctolagus	>5.3 mg/L (Rattus) 4 h	
е		cuniculus)		

See section 16 for terms and abbreviations

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation Class

Classification based on data available for ingredients. Causes mild skin irritation.

Revision date 30-May-2022

Component Information					
Toluene-2,4-diisocyanate (584-84-9)					
Method Species Exposure route Effective dose Exposure time Result:					Results
	Rabbit	Dermal	0.5 mL	24 hours	Erythema (skin
					redness) edema

Serious eye damage/eye irritation No information available.

Component Information	Component Information						
Glycidoxypropyltrimethoxysilane (2530-83-8)							
Method	Species	Exposure route	Effective dose	Exposure time	Results		
OECD Test No. 405:	Rabbit	Eye			Eye Damage		
Acute Eye							
Irritation/Corrosion							

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

Component Information						
Toluene-2,4-diisocyanate (584-8	4-9)					
Method	Species	Exposure route	Results			
Not available	Guinea pig	Dermal	sensitizing			

Glycidoxypropyltrimethoxysilane (2530-83-8)					
Method Species Exposure route Results					
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitization responses		
Sensitization			were observed		

Germ cell mutagenicity No information available.

Carcinogenicity

The table below indicates whether each agency has listed any ingredient as a carcinogen.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	Australia	European Union	IARC
Toluene-2,4-diisocyanate 584-84-9	Carc. 2	Carc. 2	Group 2B
Toluene 2,6-diisocyanate 91-08-7	Carc. 2	Carc. 2	Group 2B

Legend

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

Component Information

Australia - EN Page 6/10

Seal N Flex 1 Plus Grey Revision Number 1.02

Revision date 30-May-2022

Supersedes Date: 08-May-2022

Toluene-2,4-diisocyanate (584-84-9)				
Method	Species	Results		
OECD 453	Rat	Carcinogenic		

Reproductive toxicity No information available.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard No information available.

Section 12: Ecological information

Ecotoxicity

Aquatic ecotoxicity

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Bis(1,2,2,6,6-pentameth yl-4-piperidyl) sebacate 41556-26-7	-	LC50: =0.97mg/L (96h, Lepomis macrochirus)	1	EC50: =20mg/L (24h, Daphnia magna)
Toluene-2,4-diisocyanate 584-84-9	-	LC50 (96h) =133 mg/L (Oncorhynchus mykiss) (OECD 203)	-	EC50 (48h) =12.5 mg/L Daphnia magna (OECD 202)
Glycidoxypropyltrimetho xysilane 2530-83-8	EC50 (96hr): 350 mg/l Pseudokirchneriella subcapitata	LC50 (96h) = 55 mg/L (Cyprinus carpio) OECD 203	-	EC50 (48h) =473 mg/L Daphnia magna

Persistence and degradability

Persistence and degradability No information available.

Component Information						
Toluene-2,4-diisocyanate (584-84-9)						
Method	Exposure time	Value	Results			
OECD Test No. 302C: Inherent	28 days	0%	Not readily biodegradable			
Biodegradability: Modified MITI Test	:					

Bioaccumulative potential

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Benzenesulfonyl isocyanate, 4-methyl-	0.6
4083-64-1	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	0.37
41556-26-7	
Toluene-2,4-diisocyanate	3.43
584-84-9	

Mobility

Australia - EN Page 7 / 10

Seal N Flex 1 Plus Grey
Revision Number 1.02

Mobility in soil No information available.

Mobility No information available.

Other adverse effects

Other adverse effects No information available.

Section 13: Disposal considerations

Disposal methods

Waste from residues/unused

products

Dispose of waste in accordance with environmental legislation. Dispose of in accordance

with local regulations.

Contaminated packaging Do not reuse empty containers.

Section 14: Transport information

ADG Not regulated

IATA Not regulated

IMDG Not regulated

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

No information available

Section 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

<u>Australia</u>

See section 8 for national exposure control parameters

Standard for Uniform Scheduling of Medicines and Poisons (SUSMP)

No poisons schedule number allocated

National pollutant inventory

Subject to reporting requirement

Chemical name	National pollutant inventory
Toluene-2,4-diisocyanate	10 tonne/yr Threshold category 1
584-84-9	20 MW Threshold category 2b total
	60000 MWH Threshold category 2b total
	1 tonne/h Threshold category 2a total
	25 tonne/yr Threshold category 1a total
	400 tonne/yr Threshold category 2a total
	2000 tonne/yr Threshold category 2b total

International Inventories

AIIC	Listed
NZIoC	Not Listed
ENCS	Not Listed
IECSC	Not Listed
KECL	Not Listed

Australia - EN Page 8 / 10

Seal N Flex 1 Plus GreyRevision date30-May-2022Revision Number1.02Supersedes Date:08-May-2022

·

PICCS Not Listed

Legend:

AliC - Australian Inventory of Industrial Chemicals

NZIOC - New Zealand Inventory of Chemicals

ENCS - Japan Existing and New Chemical Substances
 IECSC - China Inventory of Existing Chemical Substances
 KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

Europe

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorization:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

2015/863/EU - RoHS

This product does not contain Lead, Cadmium, Mercury, Hexavalent chromium, Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDE), Bis(2-Ethylhexyl) phthalate (DEHP), Benzyl butyl phthalate (BBP), Dibutyl phthalate (DBP) and Diisobutyl phthalate (DIBP) above the regulated limit mentioned in this regulation

Section 16: Any other relevant information

Prepared By Product Safety & Regulatory Affairs

Revision date 30-May-2022

Revision Note

Key or legend to abbreviations and acronyms used in the safety data sheet

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value * Skin designation

C Carcinogen

Section 11: TOXICOLOGICAL INFORMATION

LD50 (lethal dose)

Section 12: Ecological information

EC50 (effective concentration)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

Australia - EN Page 9/10

^{***}Indicates updated data since last publication.

Seal N Flex 1 Plus Grey **Revision Number** 1.02

Revision date 30-May-2022 **Supersedes Date**: 08-May-2022

End of Safety Data Sheet

Australia - EN Page 10 / 10