

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code

Product Range

Construction

Specie

Pattern Process

Finish Profile

Edge Profile

Top Layer Backing

Grade

Width Length

Thickness

Origin

Responsible Certification

Janka Hardness Rating

Formaldehyde Emmision

Pentachlorophenol Emission

Thermal Conductivity

Ruropean Reaction to Fire

Classification

AR8436

Ashton & Rose

Engineered

Oak

1-Strip

Brushed

UV Matt Lacquered

5Gc

4-Sided Bevelled

3.2mm (%in)

Pine Plywood

Various

207mm (85/32in)

1092mm (42⁶³%4in)

14mm (35%4in)

Europe

FSC 100%

F3C 100%

1360 lbf (6000N)

E1

< 5ppm

0.13 W/mK

Dfl-s1

ASHTON & ROSE

AR8436 CARTMEL



Yes

INSTALLATION METHODS

Fully Bonded

Nailed No

Floated on Underlay Yes (Recommended)

Over Under-floor Heating Yes* (To be installed over wet or

dry underfloor hearing systems)

Number of Boards in a Pack 7 pcs. x 1092mm OR

6 pcs. x 1092mm+ 1 pcs. x 1064mm

INSTALLATION AND WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by HFSco Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior no-tice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

HFSco Limited

Unit 11, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD