

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code AR8456

Product Range Ashton & Rose

Construction Engineered

Specie Oak

Pattern Herringbone

Process Brushed & Stained
Finish UV Matt Lacquer
Profile Click Fall Down

Edge Profile 4-Sided Micro Bevelled

Top Layer 2.5mm (⅓₃₂in)

Backing Pine Plywood

Grade Country

 Width
 130mm (5%in)

 Length
 725mm (28³5%4in)

 Thickness
 14mm (³5%4in)

Origin Europe
Responsible Certification FSC 70%

Janka Hardness Rating 1,120 lbf (4,980N)
Formaldehyde Emmision E1(EN 717-1)

Pentachlorophenol Emission < 5ppm (CEN/TR 14823) Thermal Conductivity λ 0.13 W/m K (EN 12664) Ruropean Reaction to Fire Dfl-s1 (EN 13501-1:2007)

Classification

ASHTON & ROSE

AR8456 BORWICK



INSTALLATION METHODS

Fully Bonded Yes* (recommended)

Nailed No

Floated on Underlay No

Over Under-floor Heating Yes* (Please ask for our technical

guidelines)

INSTALLATION AND WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by HFSco Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior no-tice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

HFSco Limited

Unit 11, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD