

TECHNICAL DATA SHEET

PRODUCT DETAILS

Product Code	AR8459
Product Range	Ashton & Rose
Construction	Engineered
Specie	Oak
Pattern	Herringbone
Process	Brushed & Stained
Finish	UV Matt Lacquer
Profile	Click Fall Down
Edge Profile	4-Sided Micro Bevelled
Top Layer	2.5mm ($\frac{3}{32}$ in)
Backing	Pine Plywood
Grade	Family
Width	130mm ($5\frac{1}{8}$ in)
Length	725mm ($28\frac{35}{64}$ in)
Thickness	14mm ($\frac{35}{64}$ in)
Origin	Europe
Responsible Certification	FSC 70%
Janka Hardness Rating	1,120 lbf (4,980N)
Formaldehyde Emmision	E1(EN 717-1)
Pentachlorophenol Emission	< 5ppm (CEN/TR 14823)
Thermal Conductivity	λ 0.13 W/m K (EN 12664)
Ruopean Reaction to Fire Classification	Dfl-s1 (EN 13501-1:2007)

ASHTON & ROSE

AR8459 LUNE



INSTALLATION METHODS

Fully Bonded	Yes* (recommended)
Nailed	No
Floated on Underlay	No
Over Under-floor Heating	Yes* (To be installed over wet or dry underfloor hearing systems)

INSTALLATION AND WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by HFSCO Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

HFSCO Limited

Unit 11,
Carnforth Business Park,
Oakwood Way,
Carnforth,
Lancashire,
LA5 9FD