

TECHNICAL DATA SHEET

PRODUCT DETAILS

Fixing	Glue Down
Finish	Embossed
Profile	Butt joint
Edge Profile	Bevelled
Wear Layer	0.3mm
Slip Rating	R10
Pack Size	3.9m ²
Width	180mm
Length	1220mm
Thickness	5mm

TECHNICAL

Reaction to fire	EN13501-1 EN ISO 11925-2 EN ISO 9239-1 ASTM E 648-06	Bfl – S1 Pass Pass Class I
Resistance to Chemicals	EN 423 ASTM F 925	Class 0 Pass
Resistance to Light Inflamability	EN ISO 105-B02 ASTM F 1515	≥6 <8
Wear resistance	EN 660-2 ASTM F 510	Wear Group : P
Dimensional stability	EN 434 ASTM F 2199	≤0.25% Pass
Acoustic noise reduction	EN ISO 717-2 EN ISO 140-8 EN	Lw= 6 dB
Static electrical propensity	EN 1815	Voltage: 0.5kV
Residual Indentation	EN 433 ASTM F 1914	≤ 0.1mm < 8 %
Anti-slip property	DIN 51130	R10
VOC emission	ISO 16000	A+
Phthalates	EN 14372 CPSC-CH-C 1001-09.3	N.D. Pass
Castor chair use	ISO 4918	Pass
Squareness	ASTM F 2055	Pass
Warranty (year)	20 Res.	10 Com.

BALANCE



HF51304 Connect Greige




HF4350
Balance Sesame



HF4351
Balance Ashen



HF4354
Balance Charcoal



HF4355
Balance Saddle

INSTALLATION AND WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by HFSCO Limited, Carnforth Business Park, Oakwood Way, Carnforth Lancashire LA5 9FD. At the time of writing and publication of the sheet, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties. The photographs used in this sheet are intended only as illustrations. No rights can be derived from them.

HFSCO Limited

Unit 11,
Carnforth Business Park,
Oakwood Way,
Carnforth,
Lancashire,
LA5 9FD