

TECHNICAL DATA SHEET

PRODUCT INFORMATION

Low density polyethylene underlay with integrated, metallised vapor barrier and overlap for fast assembly and good local unevenness compensation capability.

- · Closed cells LDPE foam used for installation of laminated and engineered floating floors.
- Integrated vapor barrier with overlap for fast installation.
- · Compensates local unevennesses up to 1,55mm.
- · Can be laid easily and quickly, since it is always flat and has a slippery surface.
- · 100 % recyclable, CFC and HCFC free.
- · Ecologically friendly.

VITAL UNDERLAY | 5MM 15M2

HF006



TECHNICAL DETAILS

Thickness

Length 15,000mm EN822 Width 1000mm EN822 Area Weight 0,07kg/m2 EN ISO 23997:2012 Density 18kg/m2 EN ISO 23996:2012 Reflected Walking Sound 3% IHD-W431 Impact Sound Reduction 18dB EN ISO10140, ISO717-2 EN 826:2013+A: FU1:2019 Temporary Loads Resistance 10kPa Static Loads (Furniture) Resistance >2kPa EN1606

5mm

Dynamic Loads (Walking) Resistance <100000 cycles EN13793

Local Unevenness Compensation 1,55mm EN-ISO868

Thermal Insulation 0,050m2K/W EN12667:2002 at 24 C

Protection Against Moisture >75m EN12086
Protection Against Falling Objects 1,500mm EN13329, EN438

Reaction To Fire Efl EN ISO11925-2,PN-EN13501-1

INSTALLATION & WARRANTY

All Hardwood Floor Store floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Hardwood Floor Store's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

EN823

© This technical data sheet was written by Hardwood Floor Store, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.